

PERFORMANCE SPECIFICATION

RELAYS, HYBRID AND SOLID STATE, TIME DELAY,  
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-83726C, dated 15 June 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

3.5.4, Add a subparagraph "d. Adjunct sealant shall only be applied to relays that have initially passed the gross leak seal requirement of this specification."

PAGE 22

4.7.2.3, delete

\* 4.7.2.4, delete "method 5008 of MIL-STD-883" and substitute "device screening (paragraph C.5.8) of MIL-PRF-83534".

\* 4.7.2.5 a., add "minimum" after "160 hours".

4.7.2.5 b. delete and substitute: "b. Test condition B".

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:  
Army - CR  
Navy - EC  
Air Force - 11  
DLA - CC

Preparing activity:  
DLA - CC

(Project 5945-1167)

Review activities:  
Navy - TD  
Air Force - 99