

MILITARY SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (ALUMINUM OXIDE),
ESTABLISHED RELIABILITY AND NON-ESTABLISHED RELIABILITY
GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-C-39018B, dated 23 March 1978.

SPECIFICATION SHEETS

- MIL-C-39018/1 - Capacitors, Fixed, Electrolytic (Aluminum Oxide) (Polarized), Non-Established Reliability, and Established Reliability, Styles CU12 (Uninsulated), CU13 (Insulated) and CUR13 (Insulated).
- MIL-C-39018/2 - Capacitors, Fixed, Electrolytic (Aluminum Oxide) (Non-Polarized), Styles CU14 (Uninsulated) and CU15 (Insulated).
- MIL-C-39018/3 - Capacitors, Fixed, Electrolytic (Aluminum Oxide) (Polarized), Non-Established Reliability and Established Reliability Styles CU16 (Uninsulated) and CU17 (Insulated), and CUR17 (Insulated).
- MIL-C-39018/4 - Capacitors, Fixed, Electrolytic (Aluminum Oxide) (Polarized), Non-Established Reliability and Established Reliability Styles CU71 (Insulated) and CUR71 (Insulated).
- MIL-C-39018/5 - Capacitors, Fixed, Electrolytic (Aluminum Oxide) (Polarized) (Stacked Foil), Non-Established Reliability, and Established Reliability Styles CU81 (Insulated) and CUR81 (Insulated).
- MIL-C-39018/6 - Capacitors, Fixed, Electrolytic (Aluminum Oxide) (Polarized), Established Reliability, Style CUR91 (Insulated).
- MIL-C-39018/7 - Capacitors, Fixed, Electrolytic (Aluminum Oxide) (Polarized), (Four-Terminal), Established Reliability, Style CUR19 (Insulated).
- MIL-C-39018/8 - Capacitors, Fixed, Electrolytic (Aluminum Oxide) (Polarized), Non-Established Reliability and Established Reliability, Styles CU01 (Insulated), and CUR01 (Insulated).
- MIL-C-39018/9 - Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), Established Reliability, Style CU02 (Insulated).
- MIL-C-39018/10 - Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), Established Reliability, Style CUR92 (Insulated).

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5910-1473)