

INCH-POUND

MIL-PRF-38170H

11 September 2000

SUPERSEDING

MIL-PRF-38170G(USAF)

20 March 2000

PERFORMANCE SPECIFICATION

TANK, MOBILE STORAGE, LIQUID OXYGEN TMU-27/M

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a trailer-mounted, 50-gallon mobile storage tank for air and ground transport, storage, and servicing of liquid oxygen, designated TMU-27/M.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data that may be of use in improving this document should be addressed to: Resources & Logistics Services Division, WR-ALC/TILCC, 420 Second Street, Suite 100, Robins AFB, GA 31098-1640, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

SPECIFICATIONS

FEDERAL

A-A-50271 Plate, Identification
A-A-58092 Tape, Antiseize, Polytetrafluoroethylene

DEPARTMENT OF DEFENSE

MIL-PRF-25961 Valve, Fill-Buildup-Vent, Liquid Oxygen Converter, CRU-50/A
MIL-PRF-38201 Valve, Filler, Liquid Oxygen, Female, CRU-59/E
MIL-C-83413 Connectors and Assemblies, Electrical, Aircraft Grounding,
General Specification for
MIL-PRF-83772 Hose Assembly, Cryogenic Liquid, Aircraft Servicing

STANDARDS

FEDERAL

FED-STD-595 Colors Used in Government Procurement

DEPARTMENT OF DEFENSE

AN929 Cap Assembly, Tube, Pressure Seal
MIL-STD-810 Environmental Engineering Considerations And Laboratory
Tests

HANDBOOKS

DEPARTMENT OF DEFENSE

MIL-HDBK-838 Lubrication of Military Equipment
MIL-HDBK-1791 Designing for Internal Aerial Delivery in Fixed Wing Aircraft

(Unless otherwise indicated, copies of the above specifications, standards and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government drawings form a part of this document to the extent specified herein. Unless otherwise specified, the applicable issues are those cited in the solicitation.

DRAWINGS

ORDNANCE CORPS

C8987830	Assembly, LOX Coupling, Male Half, All Sizes
B8987832	Gasket, LOX and LN ₂ , All Sizes
C8987855	Seat, LOX Coupling, 1 inch
C8987869	LOX Cap, 1 inch

USAF

48B7796	Ring Assembly – Tie Down, 10,000 Pounds
68A39469	Plug
68A39470	Body
68A39471	Vacuum Pump – Out and Relief Assembly
68A39472	Cap
68A39473	Vacuum Pump – Out Assembly
68B39474	Filter Assembly
7545352	Requirements for Finishes SA-ALC Ground Support Equipment

(Copies of drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the applicable issues of the documents, which have been adopted by the DoD are those listed in the specific issue of the DoDISS cited in the solicitation. Unless otherwise specified, the documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE/AMERICAN SOCIETY FOR QUALITY (ANSI/ASQ)

ANSI/ASQC Z1.4- Sampling Procedures and Tables for Inspection by Attributes (DoD-adopted)

(Application for copies should be addressed to American Society for Quality, P.O. Box 3066, Milwaukee, WI 53201-3066, or to the American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

ASME Boiler and Pressure Vessel Code

Section VIII Unfired Pressure Vessels

(Application for copies should be addressed to American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, NY 10017-2392.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E1417	Liquid Penetrant Examination, Standard Practice For (DoD adopted)
ASTM E1444	Particle Examination, Magnetic (DoD adopted)

(Application for copies should be addressed to American Society for Testing and Materials, 100 Barr Harbor Drive, Conshohocken, PA 19428-2959.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE ARP 901	Bubble-Point Test Method
SAE ARP 1176	Oxygen System and Component Cleaning and Packaging
SAE-AS4395	Tube Connection, Fitting End - Flared, Design Standard (DoD adopted)
SAE-AS8090	Equipment, Towed Aerospace Ground, Mobility (DoD adopted)

(Application for copies should be addressed to Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096-0001.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle cost.

3.3 Materials. All materials shall be suitably treated to resist corrosion due to electrolytic decomposition and any other atmospheric conditions that may be encountered during operational use or storage. The use of toxic chemicals, hazardous substances, or ODCs shall be avoided, whenever feasible (see 4.5.1).

3.4 Interface. The following shall be interfaced with the storage tanks:

- a. Liquid servicing hose (see 3.5.8.)
- b. Hoisting and tiedown attachments (see 3.5.12.7.)

3.5 Design.

3.5.1 Tank assembly. The tank assembly shall be a self-contained liquid oxygen transport, storage, and servicing unit consisting of a tow-wheeled trailer, a storage tank, a control housing assembly, piping and connections, and safety devices, including necessary controls and accessories. The tank assembly shall be capable of:

- a. Being filled with liquid oxygen at a supply location (see 4.5.1).
- b. Being transported while filled with liquid oxygen and pressurized to 50 pounds per square inch gage (psig) (see 4.5.1).
- c. Transporting the liquid oxygen about an airbase (see 4.5.1).
- d. Storing the liquid with minimum evaporation loss until needed to service the aircraft converters (see 4.5.1).

3.5.2 Storage tank. The storage tank unit shall consist of inner and outer shells, piping and connections, controls, and safety devices. The storage tank shall be interchangeable, and shall be removable, using common hand tools, from the control housing and chassis frame (see 4.5.1).

3.5.3 Pressure vessels. The liquid storage tank assembly, piping, and connections thereto shall meet the requirements of section VIII of the ASME Boiler and Pressure Vessel Code. Also, the inner shell shall be certified under the code for the specified working pressure (see 4.5.1, 4.5.2, 6.2).

3.5.4 Inner shell.

3.5.4.1 Design pressure. The inner shell shall have a maximum working pressure the same as the inner shell pressure relief device (see 3.5.4.2). The normal working pressure shall be not less than 50 psig for transferring and servicing liquid oxygen under the conditions specified herein. The inner shell shall withstand an absolute pressure of 100 microns of mercury (Hg) or less with the annular space at atmospheric pressure. The shell shall not sustain damage when the annular space is evacuated to a high vacuum or is pressurized to the outer shell pressure relief device maximum opening pressure (see 4.5.1, 4.5.2).

3.5.4.2 Inner shell safety head. A bursting-disc type safety head using a readily replaceable disc in a union-type fixture shall be provided to relieve the inner shell vapor phase pressure to the atmosphere should this pressure become excessive and the pressure relief valve fail to open. The safety head relief pressure shall be not greater than 1-1/2 times the inner shell maximum working pressure (see 4.5.1, 4.5.2, 4.5.2.1).

3.5.4.3 Inner shell vapor space pressure relief device. An automatic pressure relief device shall be connected into the vapor vent line between the outer shell and the vent line shutoff valve to relieve excess pressure (see 4.5.1, 4.5.3). The relief device shall open at a pressure sufficiently below the inner shell bursting-disc type safety head breaking pressure to ensure against rupture of the safety head unless the relief device fails, but not less than 50 psig, and shall be sized to insure against the inner shell vapor space pressure exceeding 65 psig under the conditions specified (see 4.5.11.5).

3.5.5 Outer shell.

3.5.5.1 Design pressure. The outer shell shall be designed for a working pressure that will ensure sufficient strength and rigidity to prevent distortion or damage when the annular space is evacuated to a high vacuum or pressurized to the outer shell pressure relief device maximum opening pressure (see 4.5.1, 4.5.2).

3.5.5.2 Vacuum seal-off valve. The outer shell shall have a vacuum seal-off valve that will serve as the vacuum pump-out for evacuation of the annular space, an isolation valve, and outer shell safety relief device (see 4.5.1, 4.5.3). The seal-off valve shall conform to USAF drawings 68A39469, 68A39470, 68A39471, 68A39472, and 68A39473.

3.5.6 Annular space insulation. The annular insulation space shall contain an insulation that will, together with evacuation of the annular space, ensure compliance with the tank evaporation rate requirement. The insulating material shall be of a composition that will not ignite or burn when heated to 400 °F in 99.5% pure oxygen gas at a pressure of not less than 10 psig. The insulation shall not settle or be displaced in service. If a getter (impurity absorbing) material is used in the annular space, it shall be secured in direct thermal contact with the inner shell (see 4.5.10).

3.5.7 Liquid lines. A single internal fill-drain and service line shall be provided. Externally, the line shall be connected to provide separate liquid fill-drain and liquid service lines, valves, filters, and disconnects (see 4.5.1).

3.5.7.1 Liquid fill-drain line. The tank assembly shall have a liquid fill-drain line for liquid oxygen flow or transfer into or out of the inner shell. The line shall be connected to the bottom of the inner shell and shall ensure complete drainage of the inner shell into the line. The installation shall ensure against liquid entering the line from the inner shell when all liquid line valves are closed and the tank is tilted 10 degrees along either the longitudinal or lateral axis. The fill-drain line shall have a manual shutoff valve as near as possible to the point where it enters the outer shell. The line shall terminate outside the control housing in a 1-inch external pipe thread for installation of the disconnect coupling. The fitting mounting shall withstand a

torque of 300 ft-lb per inch of nominal line size applied to the fitting in either direction. The mounting shall have clearance to allow use of a 24-inch wrench. The disconnect coupling shall consist of a coupling cap, seat, and gasket, conforming to Ordnance Corps drawings C8987869, C8987855, and B8987832, respectively, assembled as shown on drawing C8987830. The coupling shall be located to provide clearance for attachment of liquid transfer hoses without interference between the fill-drain line hose or coupling and the servicing hose. An automatic pressure relief valve shall also be provided in the fill-drain line between the shutoff valve and the disconnect coupling for venting excess pressure from the fill-drain line (see 4.5.1, 4.5.21).

3.5.7.2 Liquid servicing line. The tank assembly shall have a liquid servicing line for servicing liquid oxygen from the inner shell. The installation shall ensure against liquid entering the line from the inner shell when all liquid line valves are closed and the tank is tilted 10 degrees along either the longitudinal or lateral axis. The servicing line shall have a manual shutoff valve as near as possible to the point where it enters the outer shell. The line shall terminate outside the control housing in a ¾-inch external pipe thread fitting oriented to discharge vertically upward, for attachment of the liquid servicing hose. The fitting mounting shall withstand a torque of 300 ft-lb per inch of nominal line size applied to the fitting in either direction. The mounting shall have clearance to allow use of a 24-inch wrench. The fitting shall be located to provide clearance for attachment and use of the servicing hose without interference with other components. An automatic pressure relief valve shall also be provided in the servicing line between the shutoff valve and the hose for venting excess pressure from the servicing line and servicing hose (see 4.5.1, 4.5.21).

3.5.8 Liquid servicing hose. One 10-foot length of cryogenic liquid hose conforming to MIL-PRF-83772 shall be provided with the tank. One end of the hose shall be connected to the ¾ inch external pipe thread of the liquid servicing line disconnect fitting. The other end of the hose shall be provided with a female liquid oxygen filler valve conforming to MIL-PRF-38201. Provisions shall be made in the tank assembly for storing the hose in a coil and protecting it from damage during tank acceleration and other use conditions specified herein (see 4.5.1).

3.5.8.1 Liquid servicing hose bleed fitting. A bleed fitting shall be provided to permit purging of the female filler valve and transfer hose prior to servicing. The fitting shall open the check valve of the filler valve and shall discharge the gaseous and liquid oxygen below the control housing so that it will not impinge on the tank, its components, or operating personnel (see 4.5.1).

3.5.9 Vapor vent line. The tank assembly shall have a vapor vent line that will permit filling of the tank as specified (see 3.6.4). The line shall have an inside diameter of not less than 1 inch. The line shall extend along the top inside of the inner shell and shall have spray holes so that cleaning fluid pumped through the vent line will be sprayed against the inside top of the inner shell to flush sediment and other contaminants from the tank. The total area of the spray holes shall be at least as that of the cross sectional area of the vent line. The vent line shall have a manual shutoff valve as near as possible to point where it enters the outer shell, but shall be

readily accessible to the operator. The line shall discharge toward the ground in a safe location outside the control housing. The vent line shall terminate in a 1-inch, female pipe thread in an area convenient for attachment of a purging unit hose or an overboard vent line during air transportation (see 4.5.1).

3.5.10 Pressure buildup system. The tank assembly shall have a pressure buildup system to pressurize the inner shell vapor space to 50 psig when the tank contains 2.5 gallons or more of liquid oxygen. Operation of the buildup system shall not require control operation other than closing of the vapor vent line valve and opening the pressure buildup manual control valve (see 4.5.1).

3.5.11 Control housing assembly.

3.5.11.1 Control housing. A control housing shall be provided on the end of the tank opposite the trailer towbar to house and protect the tank controls, instrumentation, and accessories. The control housing shall be readily removable from the tank assembly for maintenance. The top of the housing shall be shaped to preclude the accumulation of snow, rain, or sleet. Ventilation openings shall be provided to prevent accumulation of gasses or fog during operation. Doors or hinged panels shall be provided and shall be equipped with latches for securing them in any position from fully closed to wide open even when subjected to wind gusts up to 70 mph. Door or hinged panel latches and position-regulating devices shall be readily operable by personnel wearing heavy arctic mittens (see 4.5.1).

3.5.11.2 Control panel. The control housing shall provide for a control panel with all instruments and controls readily visible and accessible. The controls, pressure gages, and instruments shall not be installed where they can be contacted by leaking liquid oxygen or water from vapor condensing on cold lines. All valve handles and gauge faces shall be not less than 27 inches above ground level. All gages, instruments, and manually-operated controls used in normal operation of the unit shall be located on the control panel. The control panel shall be protected by a panel or door when the tank is not in use for liquid transfer. The control panel shall be shielded from rain and snow when the door or panel is open (see 4.5.1).

3.5.12 Mobility configuration. The tank assembly configuration shall be that of a tow wheeled trailer with a steerable swing-up type retractable landing gear. The landing gear configuration shall be such that the tank assembly can only be towed with the landing gear in the retracted position. The latch or pin used to retain the landing gear in position shall be made from corrosion-resistant material. The tank assembly shall meet the requirements of SAE-AS8090 as specified for type II, group A mobility. The trailer chassis design shall be such that the tank shall not be damaged when the tow bar is raised high enough for the back of the unit to touch the ground (see 4.5.1, 4.5.14).

3.5.12.1 Wheels and tires. The tank assembly shall be provided with two main wheels equipped with size 6.00 x 9, 6-ply tires and tubes. The retractable wheel tire and tube shall be size 3.50 x 6, 4-ply (see 4.5.1).

3.5.12.2 Weight distribution. The tank assembly weight distribution shall be such that when the fully loaded unit is parked on a level surface, with the lunette eye 15 inches above the ground, not more than 85 pounds or less than 65 pounds force applied at the lunette eye will be required to raise the landing gear clear of the supporting surface. In addition, the weight shall be distributed to insure a downward force on the lunette eye throughout a vertical range of 10 to 30 inches above the ground (see 4.5.1, 4.5.14).

3.5.12.3 Storage attitude. The tank assembly shall be capable of being stored in a tilted position (towbar end down) regardless of the level of fill with the front wheel retracted. A protective bumper shall be provided if required to prevent damage to any component of the tank which may result from repeated dropping of the towbar end while the tank is resting on the two main wheels (see 4.5.1, 4.5.14).

3.5.12.4 Parking brakes. The tank assembly shall be provided with a two-wheel parking brake system similar to automotive-type parking brakes. The control lever shall be located at the front of the unit near the lunette eye (see 4.5.1).

3.5.12.5 Suspension. The tank shall be mounted solidly to the trailer chassis. A tire pressure, not to exceed 15 psig, shall be selected to provide the necessary riding quality to prevent damage to the tank or its accessories without the use of suspension springs (see 4.5.1).

3.5.12.6 Static discharge reel. A static discharge reel shall be provided on each tank assembly. The reel shall have capability for latching of the cable at any extended length and shall have automatic retraction. The cable shall have a length of 50 feet minimum and terminate with a MIL-C-83413 grounding connector (see 4.5.1).

3.5.12.7 Hoisting and tiedown attachments. Tiedown devices that shall serve for both tiedown and hoisting purposes shall be provided in accordance with (see MIL-HDBK-1791 for guidance). These tiedown devices shall include four or more tiedown ring assemblies conforming to drawing 48B7796. The tiedown devices shall permit hoisting, with a 3g acceleration force, of the complete tank assembly filled to design capacity with liquid oxygen. The rings shall be located on the tank assembly so that transportation personnel can easily rig safe slings from common cable and spreader bar components for hoisting by a single-hook overhead crane (see 4.5.1, 4.5.6.3).

3.5.13 Reliability. The tank assembly shall have a mean time between failures (MTBF) of not less than 21 servicing cycles at a 0.9 confidence level (see 4.5.17, 4.5.19).

3.5.14 Maintainability. Parts and assemblies shall be located and mounted to provide adequate clearance for repair and other maintenance and, where practicable, to permit removal and replacement of any part or assembly by removing or disconnecting only mounting bolts or fasteners, panel doors, tubing, or control cables to the part or assembly being removed. The tank assembly, where practicable, shall include readily detachable and attachable type fittings in the liquid and vapor lines to permit rapid component removal and replacement. Disconnect points shall be clearly indicated and identified. The design shall ensure operating clearance for operation, servicing and maintenance at low ambient temperatures by personnel wearing heavy

gloves or mittens, bulky clothing and footgear. The design shall ensure maintenance, servicing, and adjustments can be performed using only common hand tools. Intricate locking devices, controls, or fasteners that can be easily overtightened by personnel lacking feel through thick gloves or numbness shall be avoided. The tank assembly shall have a weather-proof compartment for storing the operation handbook and maintenance/inspection records (see 4.5.20, 4.5.20.1).

3.5.15 Pressure relief devices. The tank assembly design shall include pressure relief devices in any line or component that can be isolated by closing valves, or where dangerous pressures can develop. All pressure relief devices shall be installed at readily accessible locations and the design shall ensure that a discharge of pressure will not cause danger to personnel or damage to equipment. Incorporation of safety valves shall be in accordance with section VIII of the ASME Boiler and Pressure Vessel Code (see 4.5.1, 4.5.3).

3.5.16 Valves.

3.5.16.1 Shutoff and control valves. Valves shall provide positive shutoff when closed, and minimum resistance to flow when open. Each manually-operated control or shutoff valve shall be provided with an easily-turned handle with a diameter of 3 inches per inch of nominal size, but not less than 1 inch. If globe valves are used, those valves ½inch and larger nominal size handling low-temperature liquid or gas shall incorporate seats that can be renewed without removal of the valve from the tank piping. Sealing discs or plugs for these valves shall also be renewable without replacing the valve stems. All valves handling low-temperature liquid and gas shall have their packing glands located not less than the distance specified in table I from the valve center connection centerline (see 4.5.1).

TABLE I. Separation of Valve Packing Gland from Valve Connection Centerline.

Valve Nominal Size (inches)	Separation of Packing Gland from Connection Centerline (inches)
1/4	4
3/8	4
1/2	7
3/4	7
1	9
1-1/4	9
1-1/2	11
2	11
2-1/2	12
3	12

3.5.16.2 Drain valves. Manually-operated valves shall be provided for draining liquid from the fill-drain line disconnect coupling when removing the fill hose, and from the servicing line and its hose. The drain valves shall be readily accessible outside the control housing assembly and shall discharge beneath the control housing assembly (see 4.5.1).

3.5.17 Instrumentation.

3.5.17.1 Liquid level gage. A gage, flush mounted on the control panel and having a diameter of 2.5 inches minimum, shall be provided to indicate the quantity of liquid oxygen contained in the tank inner shell with an accuracy of $\pm 3\%$ of tank design capacity. The gage shall be graduated in gallons of liquid oxygen. If a differential pressure gage is used, the design shall ensure that breakage of the glass face will not subject the sensing element to damaging pressures when the inner shell is pressurized to 65 psig. If this type of gage is used, the assembly shall incorporate pulsation snubbers in the sensing lines to prevent undue fluctuation of the indicating needle (see 4.5.1).

3.5.17.2 Vapor phase pressure gage. A gage, flush mounted on the control panel and having a diameter of 2.5 inches minimum, shall be provided to indicate the inner shell pressure. The gage shall be graduated over at least 270° of the dial face, and shall be accurate to within $\pm 2\%$ of full scale range. The indicating range shall be approximately 1.5 times the normal working pressure of the tank inner shell. The gage shall not go off-scale before the inner tank relief pressure is reached. A tap that senses gage line pressure shall be provided near the gage in the form of an SAE AS4395E04 flared-type fitting for external test use. The fitting shall be sealed with an AN929-4 type cap (see 4.5.1).

3.5.18 Cleaning solvent drains. The tank assembly design shall allow complete removal of cleaning solvents and flushing liquids after cleaning operations. The use of removable threaded plugs or similar devices is acceptable in locations where drain valves would be impractical (see 4.5.1).

3.5.19 Dimensions. The overall outside dimensions of the tank assembly shall not exceed the following dimensions (with all access openings closed): a length of 90 inches; a width of 55 inches; and a height of 40 inches (see 4.5.1).

3.5.20 Weight. The weight of the empty tank and its accessories, including the trailer chassis, shall not exceed 720 pounds (see 4.5.1).

3.5.21 Tubing and lines. Tubing and lines shall be located in protected positions, securely fastened to frame or body structures, and provided with protection where they pass through members, except where a connector is provided at the frame (see 4.5.1).

3.5.22 Locking devices. Where practicable, all screws, pins, bolts, and other similar hardware, shall be equipped with locking devices. Safety wire, self-locking nuts, cotter pins, or lock-washers will be acceptable. Where practicable, lock-washers shall be secured to bolts or screws. Cotter pins shall be fabricated from corrosion-resistant steel or other corrosion-resistant material (see 4.5.1).

3.5.23 Thread sealer. Tape conforming to A-A-58092 or other pipe-thread sealing materials specifically approved by the procuring activity shall be applied to threads prior to assembly of all pipe-threaded fittings subject to contact by liquid/gaseous oxygen or nitrogen. The tape shall be applied starting with the third thread to prevent contaminating the system (see 4.5.1).

3.5.24 Lubricants. The tank shall meet all the requirements specified herein when components requiring lubrication are serviced with military or federal specification lubricants as described in MIL-HDBK-838 (see 4.5.1).

3.6 Performance.

3.6.1 Storage capacity. The tank shall store not less than 50 U.S. gallons of 99.5% pure liquid oxygen at its atmospheric pressure boiling temperature. The liquid storage tank assembly shall have an internal volume of not less than 55 U.S. gallons in order to provide an expansion (vapor) space of not less than 10% of the total design capacity (see 4.5.5).

3.6.2 Heat leak evaporation rate. The tank heat leak evaporation loss shall not exceed the equivalent of 14 pounds of oxygen per 24-hour day when the tank is filled to not less than 50% of design capacity with liquid oxygen and subjected to the tests specified (see 4.5.8.1, 4.5.8.2).

3.6.3 Pressure buildup system. The tank assembly pressure buildup system shall pressurize the inner shell vapor space to 50 psig when the tank contains 2.5 gallons or more of liquid oxygen. The buildup system shall pressurize the tank inner shell vapor space to 50 psig within 10 minutes after closure of the vapor vent line shutoff valve and initiating buildup when the tank is filled to between 15 and 20 % of rated capacity, and has been vented to atmospheric pressure for not less than 4 hours (see 4.5.9.1, 4.5.9.2).

3.6.4 Liquid fill-drain line flow rate. The fill-drain line shall be capable of liquid oxygen flow or transfer into or out of the inner shell at a rate of 10 gallons per minute (gpm) minimum without the pressure drop through the line and filter exceeding 3 psig. (see 4.5.11.1)

3.6.5 Liquid servicing line flow rate. The liquid servicing line shall be capable of transferring liquid oxygen from the inner shell through the servicing line and filter at a rate of 2 gpm minimum without the pressure drop through the line and filter exceeding 2 psig (see 4.5.11.2).

3.6.6 Vapor vent line. The vapor vent line shall permit the tank assembly to cool down within 15 minutes and allow filling flow rates up to and including 10 gpm without the inner shell vapor pressure exceeding 15 psig when the tank assembly is subjected to the conditions and tests specified (see 4.5.11.4). The vent line shall allow venting of liquid when the inner shell is being filled and the tank contains between 50 and 52 gallons of liquid (see 4.5.11.4, 4.5.11.5).

3.6.7 Vacuum retention. The tank assembly, after evacuation of the annular space, shall not show any increase in absolute pressure attributable to leakage or outgassing within 7 days (168 hours) when subjected to the tests specified (see 4.5.7.1).

3.6.8 Dissimilar metal vacuum joints. Any dissimilar metal vacuum joints used in the tank assembly shall withstand thermal shocks, axial, and lateral vibration as specified (see 4.5.16.1.1).

3.6.9 Shutoff and control valve cycling and leakage. The valves shall withstand a closing torque of at least 300 in.-lb per inch of nominal size, with the valve bodies at either ambient temperature or the atmospheric pressure boiling temperature of liquid oxygen or nitrogen. When subsequently closed with a torque of 60 ± 5 in.-lb per inch of nominal size and a pressure of 50 psig applied to the inlet, the valves shall not leak more than 2 cubic inches of free air, oxygen, or nitrogen gas per hour per inch of nominal size. The valves shall be capable of not less than 2000 cycles of operation when subjected to a differential pressure of 50 psig while closed, including at least 1,000 cycles at ambient temperature and 1,000 cycles with the valve body at the atmospheric pressure boiling temperature of liquid oxygen (see 4.5.13.1, 4.5.13.2, 4.5.13.3)).

3.6.10 Line filters. The liquid fill-drain line and the liquid servicing line shall each have a filter for the filtering of all liquid flowing into and out of the inner shell. Filters shall be of the in-line configuration conforming to drawing 68B39474. Each filter shall be installed such that it is readily accessible for inspection, cleaning, or removal. Sintered or powdered material shall not be used unless provisions are made to prevent media migration. The proper direction of flow shall be plainly marked on each side of the filter. The filters shall be a non-bypass type and shall withstand a pressure drop of 50 psi across their elements. Each filter shall remove 98% by weight of all particles whose smallest dimension is 10 microns or greater (10-micron nominal rating). The filter shall further remove all particles whose smallest dimension is 40 microns or greater (40-micron absolute rating). In addition, the filter shall be capable of a liquid oxygen flow rate of 25-gpm at a maximum pressure drop of 2 psig, and having previously ingested a minimum of 5 grams of particles of the sizes shown in table II (see 4.5.10).

TABLE II. Particle size distribution.

Size of Particle (microns)	Percentage by weight ($\pm 3\%$)
10 to 20	36
20 to 40	24
40 to 60	16
Over 60	24

3.6.11 Transportability.

3.6.11.1 Flight and taxiing acceleration forces. The tank assembly shall withstand the air transport flight and taxiing acceleration forces as described in MIL-HDBK-1791, except that the lateral loads shall be 3g instead of 1.5g, when empty or filled with liquid oxygen to any level up to and including design capacity. These same forces shall also apply while the tank assembly is being transported on a railroad car, ship, or truck (see 4.5.6.1, 4.5.18).

3.6.11.2 Emergency landing acceleration forces. The tank assembly shall withstand the emergency landing load shock force as described in MIL-HDBK-1791 when filled with liquid oxygen, except the shock pulse shall be an approximate one-half sine wave of not less than 30 milliseconds (ms) or more than 40 ms duration. The peak acceleration of the shock pulse shall be not less than 18g for all three directions of shock input (see 4.5.6.2, 4.5.18).

3.6.12 Aircraft servicing. The tank assembly, with a tank pressure of 30 ± 5 psig, shall deliver not less than 1 gallon per minute (gpm) through the servicing line hose and the aircraft liquid oxygen filler valve (both halves) (see 4.5.11.3).

3.6.13 Mobility. The tank assembly shall be capable of type II, group A mobility in accordance with SAE-AS8090, with the exception of the 50 pound per ton towing force requirement (see 4.5.14).

3.6.14 Maintenance downtime. The tank assembly shall permit maintenance by appropriately-skilled technicians (see 6.2) in not more than the downtimes specified below, with not more than two technicians required simultaneously for any task (see 4.5.20, 4.5.20.1).

3.6.14.1 Corrective maintenance downtime. The mean corrective maintenance downtime for all levels of maintenance below depot maintenance shall be not more than 45 minutes, including access time, with a related maximum corrective maintenance downtime of not more than 2 hours (see 4.5.20, 4.5.20.1).

3.6.14.2 Preventive maintenance downtime. The maximum preventive maintenance downtime, excluding depot maintenance and major overhaul, shall be not more than 2 hours, including access time, at the 0.9 percentile point (see 4.5.20, 4.5.20.1).

3.7 Item identification. A nameplate, permanently marked with the information below, shall be securely attached to the outside of the control housing assembly in a readily visible location as specified (see 4.5.1, 6.2)

Tank, Mobile Storage, Liquid Oxygen TMU-27/M
Specification MIL-PRF-38170
Stock Number
Manufacturer's Part Number (or identification)
Contract or Order Number
Manufacturer's Name or Trade-Mark and CAGE code
U.S. Property

3.8 Special markings.

3.8.1 Tank marking. The lettering USE AGE TOWING VEHICLE shall be applied with 1-inch silver reflective letters in a readily visible location on the front of the tank near the towbar (see 4.5.1).

3.8.2 Control marking. All valves, gages, controls, and indicators used during operation shall be identified by securely attached nameplates. The nameplates shall be in accordance with A-A-50271. Tags shall not be used. The indicating scale of each instrument, such as pressure gages, temperature indicators, and liquid level indicators, used for normal operation and control of the tank, shall be permanently and clearly marked with green and red to show the proper operating and the improper or danger zones respectively (see 4.5.1).

3.8.3 Warning plates.

3.8.3.1 Servicing line. A weatherproofed red warning plate containing the following information shall be provided adjacent to the liquid servicing line (see 4.5.1):

WARNING – TANK IS NOT TO BE FILLED
THROUGH THIS LINE - FOR
SERVICING ONLY.

3.8.3.2 Air transport. A weatherproofed red warning plate containing the following information shall be provided adjacent to the vent line disconnect fitting (see 4.5.1):

WARNING – ALL VALVES MUST BE CLOSED AND AN OVER-
BOARD VENT LINE ATTACHED TO THE VENT
LINE DISCONNECT FITTING DURING AIR TRANS-
PORT.

3.8.3.3 Tire inflation. A weatherproofed, red warning plate, cautioning against overinflation of the tires and containing instructions concerning the pressure to which they shall be inflated for proper operation, shall be attached to the unit near each wheel (see 4.5.1).

3.8.4 Operating and precautionary instructions. An information panel containing brief operating and precautionary instructions to preclude injury or damage shall be permanently affixed on or near the tank control panel (see 4.5.1).

3.8.5 Transportation data plate. A transportation data plate shall be provided as specified in SAE-AS8090 (see 4.5.1).

3.8.6 Lifting instruction data plate. A data plate containing instructions necessary for lifting the tank safely with a 3-g acceleration shall be securely attached to the outside of the control housing assembly near the transportation data plate. Instructions shall include information on rigging a safe lifting sling from common cable and spreader bar components (see 4.5.1).

3.8.7 Insulation identification plate. If insulation is installed in the tank annular space, an identification plate completely identifying the insulation shall be permanently affixed in an accessible location within the control housing assembly. If a powder-type insulation is used, the plate shall indicate the insulation weight in pounds (see 4.5.1).

3.9 Interchangeability. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable (see 4.5.1).

3.10 Purge Temperature conditions. To satisfy purging requirements, the tank assembly and all related components shall be capable of withstanding a purge air inlet temperature of up to 350°F for minimum duration time of 4 hours (while the fill line outlet air temperature is maintained at 220°F) without obtaining any damage (see 4.5.15).

3.11 Environmental conditions. The tank assembly shall operate under and withstand the following environmental conditions without damage, including damage that could contaminate its contents (see 4.5.16, 4.5.18):

- a. Operating temperatures. The tank shall perform all functions required herein in any ambient temperature between -65° and +125 °F, including exposure to solar, or equivalent heat radiation of 100 to 120 watts per square foot at the higher temperature, without shelter or external winterization provisions (see 4.5.16).
- b. Vibration forces. The tank assembly, when empty or filled to any level up to design capacity with cryogenic liquid, shall not be damaged by vibration forces that will typically be encountered during its transportation in aircraft, railroad car, ship, or truck (see 4.5.16.1).
- c. Storage temperature. The tank shall not be damaged by storage in any ambient temperature from -80° to +160 °F for not less than 72 hours (see 4.5.16.2).
- d. Humidity. The tank assembly shall not be damaged by operation or storage in any relative humidity up to and including 100% climates (see 4.5.16.3).
- e. Fungus. The tank assembly shall not be damaged by exposure to moist fungus growth such as encountered in tropical and subtropical climates (see 4.5.16.4).
- f. Salt fog. The tank assembly shall not be damaged by operation or storage in an atmosphere containing salt-laden moisture such as encountered near bodies of salt water and in transportation on shipboard (see 4.5.16.5).
- g. Rain. The tank assembly shall not be damaged by operation or storage under heavy rainfall as encountered in any locale, including the tropics (see 4.5.16.6).
- h. Sand and dust. The tank assembly shall not be damaged by operation or storage in an atmosphere containing airborne sand and dust particles such as encountered in normal and desert operations (see 4.5.16.7).
- i. Wind. The tank assembly shall not be damaged by storage and operation in wind velocities of up to and including 70 miles per hour (mph) (see 4.5.16.8).

3.12 General cleaning instructions. Following completion of fabrication and assembly operations, the tank shall be thoroughly cleaned and degreased to remove dirt; excess soldering, brazing, and welding flux; welding slag, scale, metal chips, loose or chipped paint, spilled chemicals and other foreign materials. Cleaning and degreasing shall be performed on surfaces contacting oxygen in accordance with SAE-ARP-1176 and to meet the following requirements (see 4.5.4):

a. When the tank is filled to 90% or more of design capacity with filtered liquid oxygen or nitrogen and allowed to set for not less than 2 hours, the residue remaining after evaporation of the first liter of liquid withdrawn through the fill drain line, with its filter removed, shall contain (see (see 4.5.4.3):

(1) No solid particles with any dimension greater than 500 microns.

(2) No fibrous particle (see 6.3.4) with a length greater than 3000 microns.

(3) No more than 25 milligrams total of both solid and fibrous particles.

b. When the liquid remaining in the tank after withdrawal of the above 1 liter sample is discharged through the liquid fill drain line and installed filter at a rate not less than 5 gallons per minute, the total amount of contaminant collected on the filter shall not exceed 0.1 gram (see 4.5.4.4).

c. Tank surfaces, fittings, and other parts that will be in contact with high purity oxygen shall be degreased in accordance with SAE ARP 1176. Precautions shall be taken to insure that solvents do not contact parts fabricated from incompatible materials. Petroleum and other flammable solvents shall not be used on such surfaces. All cleaning materials and solvents shall be thoroughly removed from the tank components following the cleaning and degreasing process (see 4.5.4.1, 4.5.4.2).

3.13 Finish and color. All exposed metal parts and surfaces, except parts and surfaces that contact high purity oxygen, shall be cleaned, treated, and finished per AF drawing 7545352 (see 6.5). The final finish paint color for the trailer chassis and wheels, the exterior of the tank and its mounting devices, and the control housing shall be dark green per FED-STD-595, color no. 24052 (see 4.5.1).

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 First article inspection. If required, first article inspection shall be performed on one complete tank assembly. This inspection shall include the examinations and tests of 4.3 and the tests indicated in 4.5. For a requirements cross reference see table III.

TABLE III. Requirements cross reference matrix.

Requirement	Verification	Requirement	Verification
3.2	4.5.1	3.5.16.2	4.5.1
3.3	4.5.1	3.5.17.1	4.5.1
3.5.1	4.5.1	3.5.17.2	4.5.1
3.5.2	4.5.1	3.5.18	4.5.1
3.5.3	4.5.1, 4.5.2	3.5.19	4.5.1
3.5.4.1	4.5.1, 4.5.2	3.5.20	4.5.1
3.5.4.2	4.5.1, 4.5.2.1	3.5.21	4.5.1
3.5.4.3	4.5.1, 4.5.3	3.5.22	4.5.1
3.5.5.1	4.5.1, 4.5.2	3.5.23	4.5.1
3.5.5.2	4.5.1, 4.5.3	3.5.24	4.5.1
3.5.6	4.5.10	3.6.1	4.5.5
3.5.7	4.5.1	3.6.2	4.5.8
3.5.7.1	4.5.1, 4.5.21	3.6.3	4.5.9
3.5.7.2	4.5.1, 4.5.21	3.6.4	4.5.11.1
3.5.8	4.5.1	3.6.5	4.5.11.2
3.5.8.1	4.5.1	3.6.6	4.5.11.4
3.5.9	4.5.1	3.6.7	4.5.7
3.5.10	4.5.1	3.6.8	4.5.16.1.1
3.5.11.1	4.5.1	3.6.9	4.5.13
3.5.11.2	4.5.1	3.6.10	4.5.12
3.5.12	4.5.1, 4.5.14	3.6.11.1	4.5.6.1, 4.5.18
3.5.12.1	4.5.1	3.6.11.2	4.5.6.2, 4.5.18
3.5.12.2	4.5.1, 4.5.14	3.6.12	4.5.11.3
3.5.12.3	4.5.1, 4.5.14	3.6.13	4.5.14
3.5.12.4	4.5.1	3.6.14	4.5.20.1
3.5.12.5	4.5.1	3.7	4.5.1
3.5.12.6	4.5.1	3.8	4.5.1
3.5.12.7	4.5.1, 4.5.6.3	3.9	4.5.1
3.5.13	4.5.17, 4.5.19	3.10	4.5.15
3.5.14	4.5.20, 4.5.20.1	3.11	4.5.16, 4.5.18
3.5.15	4.5.1, 4.5.3	3.12	4.5.4
3.5.16.1	4.5.1	3.13	4.5.1

(Table III provides a cross-reference matrix of the section 3 requirements tested or verified in Section 4.)

4.3 Conformance inspection. Conformance inspection shall include the examination and tests included in 4.3.1 and 4.3.2.

4.3.1 Individual tests.

4.3.1.1 Relief valves. Each relief valve shall be subjected to the test specified (see 4.5.3).

4.3.1.2 Tank. Each tank shall be subjected to the following tests as described (see 4.5).

- a Examination of product (see 4.5.1).
- b. Pressure test (see 4.5.2)(individual test excludes 4.5.2.1).
- c. Cleaning effectiveness tests (see 4.5.4).
- d. Individual article vacuum retention test (see 4.5.7.2).
- e. Evaporation loss rate individual acceptance test (see 4.5.8.2).

4.3.2 Sample tests. In addition to the individual tests, component tests shall be conducted, using commercial sampling techniques such as those contained in ANSI/ASQC Z1.4 (see 6.2), as shown below:

- a. Bursting disc sampling test. Bursting discs shall be subjected to the testing specified (see 4.5.2.1).
- b. Valve sampling test. Sample valves, selected from each type (same size, design, and construction) shall be subjected to the testing specified in 4.5.13.1 through 4.5.13.3.
- c. Liquid line filter sampling test. Sample filters, selected from each type (same size, design, and construction) shall be subjected to the absolute and nominal rating testing specified in 4.5.12.1 and 4.5.12.2.
- d. Dissimilar metal vacuum joint sampling tests. Sample joints, selected from each type (same size, design, and construction) shall be subjected to the testing specified in 4.5.16.1.1.

4.4 Test conditions. Unless otherwise indicated in the test methods, all tests shall be conducted at an atmospheric pressure of 28 to 32 inches of mercury, a temperature of 77 ± 18 °F, and a relative humidity of 80% or less. If these conditions are not obtainable, corrections shall be made to compensate.

4.5 Tests.

4.5.1 Examination of product. The tank assembly shall be examined to determine conformance to this specification with respect to materials, interface, design, finish and color, identification and other markings, and interchangeability. A mechanical inspection of all components and parts shall be conducted. All mechanical parts shall be checked for free and proper functioning. See table III for requirements cross reference.

4.5.2 Pressure test. Each component and circuit of the tank assembly that operates under positive pressure in normal service shall be pressure tested in accordance with section VIII of the ASME Boiler and Pressure Vessel Code. Automatic pressure relief devices need not be installed for this. Any distortion, damage, or leaks resulting from this test shall be cause for rejection (see 3.5.3, 3.5.4.1, 3.5.5.1).

4.5.2.1 Bursting disc test. A bursting disc, identical to the one used in the tank assembly, shall be subjected to a gradually increasing pressure, using clean, dry, oil-free air or nitrogen, until the disc ruptures. The burst disc rupture pressure shall be not greater than 1-1/2 times the maximum working pressure of the inner shell (see 3.5.4.2, 3.5.7.1, 3.5.7.2).

4.5.3 Relief valve test. Prior to installation on the tank, each relief valve shall be subjected to a gradually increasing pressure of clean, dry, oil-free air, oxygen, or nitrogen at its inlet until it starts to discharge. The pressure shall then be reduced until the valve completely reseals. This procedure shall be repeated until the valve has started to discharge, and resealed, not less than two times. Following this test, the valve shall be checked for leakage by application of a soap film (film across the outlet and over all outside surfaces) with not less than the maximum working pressure of the component which the valve will be used to protect, being applied at the inlet. Failure to open or reseat within the specified limits or an indication of leakage during the soap film test shall be cause for rejection (see 3.5.4.3, 3.5.5.2, 3.5.15).

4.5.4 Cleaning effectiveness tests.

4.5.4.1 Visual inspection. All equipment, pipes, and components that will contact liquid oxygen shall be visually examined for evidence of corrosion products, metal chips, scale, weld scale, oil, grease, paints, preservatives, decals, or other contamination or foreign matter. Any evidence of contamination or foreign matter shall require recleaning and retest.

4.5.4.2 Ultraviolet light inspection. All accessible surfaces and parts that will contact liquid oxygen shall be visually inspected for hydrocarbons with ultraviolet light. Any evidence of fluorescence shall require recleaning and retest.

4.5.4.3 Particulate matter. Following the cleaning and degreasing operations specified herein and equipment final assembly, the liquid storage tank assembly inner shell shall be filled to not less than 90% of design capacity with liquid oxygen or liquid nitrogen. The tank shall then be left undisturbed for not less than 2 hours. Following the 2-hour period, the filter shall be removed from the fill-drain line and a 2-liter or larger Dewar flask shall be placed under the discharge end of the fill-drain line, the shutoff valve opened, and not less than 1 liter of the first

liquid discharged through the line collected in the Dewar flask. This sample shall be evaporated to dryness and the residue examined for particulate matter. The liquid storage tank and the associated piping and fittings shall be recleaned and this test repeated until the particulate matter remaining as residue contains no solid particle with any dimension greater than 500 microns, no fibrous particle with a length greater than 3,000 microns, and no more than 25 milligrams total of both solid and fibrous particles.

4.5.4.4 Total solids. Following withdrawal of the 1-liter sample (see 4.5.4.3), the remaining load of contained liquid shall be discharged through the liquid fill-drain line and the filter at a rate of not less than 10 gpm. The filter shall be thoroughly cleaned and the removed material collected, dried, and weighed after each use. If more than 0.1 gram of contaminant material is collected on the filter during discharge of the liquid from the tank, the tank assembly and the associated piping and fittings shall be recleaned. Cleaning and testing shall be repeated until the amount of contaminant collected on the filter from discharging the specified tank assembly load is less than 0.1 gram.

4.5.5 Liquid storage capacity test. The tank storage capacity shall be determined by filling a liquid into the inner shell with tank setting on its wheels on a flat, level surface until the filling liquid overflows through the vapor vent line. The volume of liquid in the inner shell shall be not less than 50 U.S. gallons. The inner shell shall then be filled completely to determine total internal volume. The measured volume, accurate to within 0.5 gallon, shall be not less than 55 gallons. Venting of liquid shall occur when the tank contains between 50 and 52 gallons of liquid (see 3.6.1).

4.5.6 Transportability and handling test.

4.5.6.1 Air transport flight and taxiing acceleration forces. The tank assembly shall be filled to design capacity with a cryogenic liquid having a density of not less than 9.5 pounds per U.S. gallon and pressurized to not less than 45 psig. While so filled and pressurized, the tank shall be subjected to the flight and taxiing acceleration force loads as described in MIL-HDBK-1791, as modified (see 3.6.11.1). Liquid nitrogen may be used as the filling liquid if the acceleration levels are increased to not less than 1.42 times the specified values. Failure to meet the specified requirements shall be cause for rejection.

4.5.6.2 Emergency landing acceleration forces. The tank assembly shall be filled to design capacity with a cryogenic liquid having a density of not less than 9.5 pounds per U.S. gallon and pressurized to not less than 45 psig. While so filled and pressurized, the tank shall be subjected dynamically to the emergency landing acceleration force loads as described in MIL-HDBK-1791, as modified (see 3.6.11.2). Breaking loose of the unit from its tiedowns, separation of a component from the unit, or any discharge of liquid beyond the tank envelope shall be cause for rejection.

4.5.6.3 Hoisting and tiedown provision test. The tank assembly shall be filled to design capacity with a cryogenic liquid having a density of not less than 9.5 pounds per U.S. gallon. Weights totaling not less than 2,220 pounds shall be attached to the tank so that the combined weight of the filled tank and the weights will be supported by the hoisting and tiedown rings when the tank

is raised by an overhead crane. The tank and weights combination shall then be raised to a height of not less than 3 feet above the floor by a single-hook crane using the hoisting and tiedown rings, held in that position for not less than 1 minute, and then lowered to the floor. This procedure shall be repeated 3 times. There shall be no damage to or any distortion of any tank component (see 3.5.12.7).

4.5.7 Vacuum retention tests.

4.5.7.1 First article vacuum retention. Following the air transport flight and taxiing tests, and the lifting provision tests, the tank inner shell shall be filled with liquid oxygen to not less than 60% of design capacity. The annular space shall be evacuated and sealed. The vibration testing specified (see 4.5.16.1) shall be conducted on the tank following evacuation and sealing of the annular space, either prior to or during this vacuum retention test. The tank assembly shall then be permitted to temperature stabilize until a constant annular space absolute pressure determined through precision instrumentation, is obtained. Precision temperature readings shall also be obtained when the pressure readings are taken for temperature correction of the before and after absolute pressure readings. The inner shell vapor space shall then be pressurized to not less than 30 psig with gas obtained by vaporizing part of the contained liquid with the pressure buildup system, and the tank left undisturbed for not less than 7 days (168 hours) as filled and pressurized. Following completion of this testing, the inner shell vapor space pressure shall be reduced to atmospheric and the annular space absolute pressure, corrected for temperature, determined using the same instruments as above. The annular space absolute pressure shall not show any increase attributable to leakage or outgassing, or the tank shall be considered to have failed the test.

4.5.7.2 Individual article vacuum retention. The test for the individual article shall be the same as the first article retention test, except for the vibration portion of the test. During the 7-day vacuum retention period, the individual tank shall be subjected to vibration of not less than 30 minutes duration in one plane. The vibration input to the tank shall be at a constant acceleration amplitude of not less than 1.5g peak vector for the frequency applied. The vibration frequency shall be between 15 and 40 Hz, inclusive. Either a single, constant frequency or a periodic sweep of the specified frequency range may be used. At the completion of the vacuum retention test, the annular space absolute pressure shall not show any increase attributable to leakage or outgassing, or the tank shall be considered to have failed the test. The tank assembly shall also not show damage, such as fractures of pipes, brackets, welded connections, or other similar types of damage.

4.5.8 Heat leak evaporation loss rate tests.

4.5.8.1 First article heat leak evaporation loss. The first article heat leak evaporation loss rate test shall consist of the following individual test operations conducted in the order listed. Throughout the complete test, the inner shell vapor phase pressure shall remain as near atmospheric as necessary pressure drops through the measuring apparatus will permit (see 3.6.2).

- a. With the tank filled to not less than 50% of design capacity with liquid oxygen or liquid nitrogen, the tank shall be placed in a location where the ambient temperature will remain at not less than 125 °F throughout the periods specified.
- b. The inner shell vapor space shall be vented to atmospheric pressure for not less than 24 hours through the flow measuring apparatus that will be used for determining the evaporation loss rate.
- c. The tank shall remain under the specified ambient temperature and inner shell vapor phase pressure conditions for an additional 72 hours while heat leak evaporation rate losses for the tank are determined by passing all vapors vented from the inner shell through a recording or totaling-type gas flowmeter. During this 72-hour test period, the upper surface of the tank shall be exposed to the full impact of solar or equivalent heat radiation of 100 to 120 watts per square foot for three separate periods of not less than 8 hours each, with each exposure period followed by a period of not less than 16 hours during which no radiation is applied. The total weight of vapors vented during the test, the weight of vapors vented since the preceding reading, the average ambient temperature and barometric pressure to which the tank has been subjected during the preceding period, shall be recorded at intervals not to exceed 8 hours during the 72-hour test. The actual loss rate for each reading, the average actual loss rate over the entire 72-hour test period, and the average ambient temperature to which the tank was exposed during the 72-hour test period shall be calculated. The evaporation loss rates shall be reported as the pounds of liquid oxygen vaporized per 24-hour day, and shall not exceed the limit specified (see 3.6.2), or the tank shall be considered to have failed the test.
- d. The tank shall be removed from the high temperature test conditions and exposed to ambient temperature conditions for not less than 36 hours to permit temperature stabilization. The tank shall then be filled to not less than 60% of design capacity and pressurized to 30 psig and allowed to remain in this condition for a period of 7 days. The tank shall then be subjected to the individual acceptance evaporation loss rate test specified (see 4.5.8.2) to establish comparative data for determining whether production tanks are capable of complying with requirements (see 3.6.2).

4.5.8.2 Individual article heat leak evaporation loss. With the inner shell remaining filled to not less than 50% of design capacity, the tank shall be placed where it will be subjected to local or shop ambient temperatures throughout the following test (see 3.6.2):

- a. The inner shell vapor space shall be vented to atmospheric pressure for not less than 24 hours through the flow measuring apparatus that will be used for determining the evaporation loss rate. The heat leak evaporation loss rate for the tank shall then be determined by passing all vapors vented from the inner shell through a recording or totaling-type gas flowmeter for an additional period of not less than 72 hours.
- b. Throughout the test, the inner shell vapor phase pressure shall remain as near atmospheric as necessary pressure drops through the flow measuring apparatus will permit. The total weight of vapors vented during the test, the weight of vapors vented since the preceding

reading, the average ambient temperature and barometric pressure to which the tank has been subjected during the preceding period, shall be recorded at intervals not to exceed 8 hours throughout the 72-hour test. The actual loss rate in pounds for each reading, the average actual loss rate in pounds over the entire 72-hour test period, and the average ambient temperature to which the tank was exposed during the 72-hour test period shall be calculated.

c. The production item average loss rate for the 72-hour test period shall be corrected from the average temperature experienced during the test period to the average temperature at which the comparative data specified (see 4.5.8.1) was obtained, and the result reported as the pounds of liquid oxygen vaporized per 24-hour day. This loss rate shall not exceed the limit established by the comparative data obtained (see 4.5.8.1) for compliance with (see 3.6.2), or the tank shall be considered to have failed the test.

4.5.9 Pressure buildup tests.

4.5.9.1 Buildup with low liquid level. The tank assembly shall be filled with enough liquid oxygen to ensure between 2.5 and 3 gallons are in the inner shell after the specified stabilization. The tank shall then be left undisturbed with the inner shell vapor space vented to atmospheric pressure for not less than 4 hours. Following this stabilization period, the inner shell vapor vent line shutoff valve shall be closed and the pressure buildup valve opened. The inner shell vapor phase pressure shall reach 50 psig or the tank shall be considered to have failed the test (see 3.6.3).

4.5.9.2 Pressure buildup time. The tank assembly shall be filled with liquid oxygen to between 15 and 20% of capacity and left undisturbed with the inner shell vapor space vented to atmospheric pressure for not less than 4 hours. The inner shell vapor vent line shutoff valve shall then be closed and the pressure buildup system actuated. The time required after closing of the vent valve until the vapor phase pressure has reached 50 psig shall not exceed 10 minutes or the tank shall be considered to have failed the test (see 3.6.3).

4.5.10 Insulation combustibility. A sample of the insulation material used in the annular space shall be tested for combustibility as follows (see 3.5.6):

- a. Place approximately 0.5 gram of the material in an oxygen bomb.
- b. Pressurize the bomb to not less than 10 psig with oxygen gas having a purity of 99.5% or better.
- c. Raise the temperature of the oxygen bomb to not less than 400 °F and hold at that temperature for not less than 1 hour. A sudden temperature rise, charring of the insulation material, or other evidence of ignition or burning of the material shall be considered cause for rejection.

4.5.11 Liquid transfer tests.

4.5.11.1 Fill-drain line. Liquid oxygen shall be transferred into the tank through the fill-drain line at not less than 10 U.S. gallons per minute for a length of time adequate to determine the pressure drop through the line and filter. The pressure drop shall not exceed 3 psig. Liquid nitrogen may be used at a flow rate that will provide a pressure drop equivalent to that resulting from the specified liquid oxygen flow (see 3.6.4).

4.5.11.2 Servicing line. Liquid oxygen shall be transferred from the tank through the liquid servicing line at not less than 2 U.S. gallons per minute for a length of time adequate to determine the pressure drop through the line and filter. The pressure drop shall not exceed 2 psig. Liquid nitrogen may be used at a flow rate that will provide a pressure drop equivalent to that resulting from the specified liquid oxygen flow (see 3.6.5).

4.5.11.3 Aircraft servicing rate. With the servicing hose attached to the servicing line disconnect, the female liquid oxygen filler valve shall be connected to a male liquid oxygen fill-buildup-vent valve conforming to MIL-PRF-25961. The tank vapor phase pressure shall be increased to 30 ± 5 psig using the pressure buildup system, the servicing line shutoff valve opened, and the servicing rate determined by flowing the contained liquid oxygen through the servicing line, the servicing hose, the female filler valve, and the male fill-buildup-vent valve until the rate of flow has been established. The servicing rate shall be not less than 1 gpm or the tank shall be considered to have failed the test (see 3.6.12).

4.5.11.4 Vapor vent line. The tank assembly and all its components shall be subjected to an ambient temperature of 125 °F. After the tank assembly and components have stabilized at this temperature, liquid oxygen or liquid nitrogen shall be transferred into the inner shell through the fill line until the inner shell has cooled sufficiently to permit filling at the 10 gpm rate. The rate of transfer during cooldown shall be the maximum that will maintain an inner shell vapor phase pressure of less than 15 psig. The cooldown time shall not exceed 15 minutes, or the tank shall be considered to have failed the test. Following cooldown, the tank assembly shall be filled at a rate of not less than 10 gpm. The inner shell vapor phase pressure shall not exceed 15 psig at this flow rate, or the tank shall be considered to have failed the test (see 3.6.6).

4.5.11.5 Vapor relief capacity. Following the vapor vent line test (see 4.5.11.4), with the ambient temperature still at 125 °F and the tank remaining filled to not less than 90% of design capacity, the vapor vent line shutoff valve shall be tightly closed, the pressure buildup system control adjusted for maximum buildup rate, and all other valves closed. The inner shell vapor space excess pressure shall be permitted to vent through the relief device until the inner shell vapor pressure reaches its maximum reading. The vapor space pressure shall not exceed 65 psig under these conditions, or the tank shall be considered to have failed the test (see 3.6.6).

4.5.12 Filter tests.

4.5.12.1 Absolute rating. Compliance with the 40-micron absolute rating requirement specified (see 3.6.10) shall be substantiated by the bubble point method, such as SAE ARP 901, or other method approved by the procuring activity (see 6.2). The filter element shall be submerged in

Solox 190, or equivalent, fluid. The fluid level shall be maintained 0.5 inch maximum above the top of the element. The element shall be slowly pressurized from within and slowly rotated 360° at each pressure increment. The pressure shall be increased until the bubble point is determined. If the first bubble is emitted from the element at a pressure of less than 6 inches of water, the filter shall be considered to have failed the 40-micron requirement

4.5.12.2 Nominal rating. Compliance with the removal of 98% by weight of all particles whose smallest dimension is 10 microns or greater as specified (see 3.6.10) shall be substantiated as shown below. This test shall be conducted after completion of the 50-cycle servicing test specified (see 4.5.16).

- a. The filter shall be stabilized at 125 °F without any intervening servicing, cleaning, adjustment, or repair.
- b. Approximately 20 liters of oxygen or nitrogen liquid shall be filtered through a 5-micron Mitex™ membrane filter (see 6.7), or equivalent, to assure the test liquid is clean. This liquid shall then be contaminated with 10.0 grams of particles with a size distribution as shown in table II. The liquid shall be placed in a container, agitated to ensure a homogeneous mixture, and then transferred through the test filter in a time interval of not more than 45 seconds. The test filter shall be positioned so that flow is in a down direction and the discharge is directed into a clean, particle-free container with provisions to ensure positive retention of any particles passing through the test filter, and exclusion of external particles.
- c. The liquid shall then be allowed to vaporize, and the container flushed by use of a wash bottle containing approximately 200 ml of isopropyl alcohol solution which has been cleaned by filtering through a 5-micron Mitex™ membrane filter, or equivalent. The wash solution shall then be filtered through a new, pre-weighed 5-micron membrane filter (same type as above). This container wash procedure shall be performed four times using the same pre-weighed filter to filter the wash solution each time. An additional 200 ml of clean solution shall be used to wash the filter funnel and then filtered through the same pre-weighed membrane filter. Upon completion of the wash solution filtering, the pre-weighed filter shall be weighed again. If the weight increase is more than 0.2 gram, the test filter shall be considered to have failed the 98% retention of all particles 10 microns or larger requirement.

4.5.12.3 Filter pressure drop. Liquid oxygen shall be transferred through the filter at a flow rate of not less than 25 gpm for a length of time adequate to determine the pressure drop through the filter after contamination. Use of water as an alternate liquid shall be approved by the procuring activity. The liquid oxygen stream shall be contaminated with not less than 5 grams of particles of the size and distribution shown in table II. The 5 grams of contaminant shall be introduced into the stream at the approximate rate of 1 gram per minute, and shall not require more than 5 minutes. The pressure drop after the filter has been so contaminated shall not exceed 2 psig, or the filter shall be considered to have failed the test. The filter shall then be further contaminated

with particles until a constant pressure drop of not less than 50 psig across the filter element is reached. Following this, the filter shall be opened and inspected. Any permanent distortion or damage incurred by the filter element or housing as a result of the 50 psig pressure differential shall be cause for rejection (see 3.6.10).

4.5.13 Shutoff and control valve tests. The valve shall be subjected to the tests specified below in the order listed (see 3.6.9).

4.5.13.1 Cycling. The valve shall be closed with a torque of 60 ± 5 in-lb per inch of nominal size, and, using compressed air, oxygen or nitrogen gas, subjected to an inlet pressure of not less than 50 psig with the outlet open to atmospheric pressure. The valve shall then be opened to not less than the three-fourths open position, after which it shall again be closed with a torque of 60 ± 5 in-lb per inch of nominal size and the specified inlet pressure reestablished. This shall constitute one cycle. One thousand such cycles shall be accomplished without intervening valve lubrication, adjustment or repair while the valve body is subjected to ambient temperature. The thousand-cycle test shall then be repeated with the valve body submerged in liquid oxygen or liquid nitrogen. Damage to or improper operation of the valve as a result of this test shall be cause for rejection.

4.5.13.2 Overtorque. At the conclusion of the cycling test specified (see 4.5.13.1), the valve shall be removed from the liquid bath and permitted to stabilize at ambient temperature. The valve shall then, without intervening lubrication, adjustment, or repair, be fully opened, and closed with a torque of 300 ± 10 in-lb per inch of nominal size. Damage to or improper operation of the valve as a result of this test shall be cause for rejection.

4.5.13.3 Leakage. Following the overtorque test specified (see 4.5.13.2) and without intervening valve lubrication, adjustment or repair, the valve shall be fully opened, and closed with a torque of 60 ± 5 in-lb per inch of nominal size. The valve shall then be completely immersed in clear water with the inlet subjected, using compressed air, oxygen or nitrogen gas, to pressure of not less than 50 psig for not less than 10 minutes with the outlet open. Any leakage past the seat, through the packing, or through the valve body shall be collected and measured. Total collected gas leakage exceeding 2 cubic inches of free air, oxygen or nitrogen gas per hour per inch of valve nominal size shall be considered cause for rejection.

4.5.14 Mobility tests. The unit shall be subjected to the general tests of SAE-AS8090 and to those specified for type II mobility items (see 3.6.13). In addition, compliance with the weight distribution requirements specified (see 3.5.12.2) shall be verified. The adequacy of the stop required by (see 3.5.12) shall be verified by raising the tow bar of a filled tank until the center-of-gravity acts to continue upward movement of the tow bar until the stop contacts dry hardened concrete. No restraining force shall be applied to limit the impact of the contact. After each test the tank shall be inspected for misalignment, distortion, and defects to determine the unit was not adversely affected by the test (see 3.5.12.2, 3.5.12.3).

4.5.15 Purging Temperature Test. The tank assembly shall be subject to a purge test in accordance with Air Force purging requirements. Tests shall be conducted according to current Air Force tech order purge procedures. During testing, the tank assembly is required to withstand a purge air inlet temperature of up to 350 °F for a minimum time of four (4) hours while the fill line outlet air temperature is maintained at 220 °F. Tests shall be conducted (no less than 24 hours after purging) to ensure that no leakage or structural/ component deterioration has occurred (see 3.10).

4.5.16 Environmental conditions. The tank assembly shall be subjected to the following tests conducted in accordance with the specified methods of MIL-STD-810 (see 6.6). At the conclusion of each test, the tank assembly shall be examined for damage or deterioration, including that which could contaminate its contents (see 3.11).

4.5.16.1 Vibration forces. The tank assembly shall be filled to design capacity with liquid nitrogen and pressurized to not less than 45 psig. The filled and pressurized tank, with the servicing hose secured in the storage position, shall be subjected to the vibration testing specified in MIL-STD-810, method 514, category 1, basic transportation. The tank assembly shall be carefully examined after each test phase and following completion of the overall test. Damage to or failure of any tank assembly components, loosening of fasteners, loss of instrument calibration, or loss of vacuum in the annular space shall be considered a failure of the tank assembly to pass the test (see 3.11 b.).

4.5.16.1.1 Dissimilar metal vacuum joints vibration test. Vacuum joints of this type, if used, shall be tested as specified below (see 3.6.8):

- a. Subject the joint to 10 thermal shocks. Each thermal shock shall be accomplished by first heating the complete joint assembly to not less than 125 °F and then, while still at 125 °F or above, the joint shall be quickly submerged in liquid nitrogen at its atmospheric pressure boiling temperature. The joint shall remain submerged until it has cooled to approximately liquid nitrogen temperature. The joint will be considered to have reached this temperature when bubbles cease to emanate from its surface in large numbers.
- b. Secure one end of the joint (other end free) to a vibration device which will vibrate the joint in liquid nitrogen. The joint shall then be subjected to axial vibration at a frequency of 60 Hz and a double amplitude of 0.050 inch minimum for not less than 30 minutes while the joint is submerged in liquid nitrogen at its atmospheric pressure boiling temperature.
- c. The joint, still secured, shall then be subjected to lateral vibration at a frequency of 60 Hz and a double amplitude of 0.200 inch minimum for not less than 30 minutes while submerged in liquid nitrogen at its atmospheric pressure boiling temperature.

Any leakage rate increase detectable with a helium mass spectrometer operating at its maximum sensitivity, comparing checks prior to and following the temperature shock and vibration testing specified above, shall be cause for rejection.

4.5.16.2 Storage temperature.

4.5.16.2.1 Low temperature exposure. The tank assembly shall be filled to design capacity with liquid oxygen or liquid nitrogen and subjected to low temperature in accordance with MIL-STD-810, method 502.3, procedure I, using a chamber temperature of -80 °F and an exposure duration, after stabilization, of 72 hours minimum (see 3.11 c., 4.5.16.2.1.1).

4.5.16.2.1.1 Pressure buildup. After completion of the low temperature exposure, the unit shall be stabilized at -65 °F, the inner shell vapor vent line shutoff valve closed, and the pressure buildup system actuated. The length of time required after closing of the vent valve until the vapor phase pressure has reached 50 psig shall not exceed 10 minutes.

4.5.16.2.2 High temperature. The tank assembly shall be filled to design capacity with liquid oxygen or liquid nitrogen and subjected to high temperature in accordance with method 501.3, procedure I, using a chamber temperature of 160 °F and an exposure duration, after stabilization, of 72 hours minimum (see 3.11c.).

4.5.16.3 Humidity. The tank assembly shall be subjected to a humidity test in accordance with MIL-STD-810, method 507.3, procedure II, using the cyclic high humidity cycle and a test duration of 7 days (see 3.11 d.).

4.5.16.4 Fungus. Equipment samples adequately representing applicable portions of the tank assembly that might be damaged by exposure to fungus attack shall be subjected to a fungus test in accordance with MIL-STD-810, method 508.4, using a test duration of 28 days (see 3.11 e.).

4.5.16.5 Salt fog. The tank assembly shall be subjected to salt fog in accordance with MIL-STD-810, method 509.3, procedure I (see 3.11 f.).

4.5.16.6 Rain. The tank assembly shall be subjected to rain in accordance with MIL-STD-810, method 506.3, procedure I (see 3.11 g.).

4.5.16.7 Sand and dust. The tank assembly shall be subjected to the blowing dust test procedure in accordance with MIL-STD-810, method 510.3, using a temperature of 145 °F during the high temperature part of the procedure.

4.5.16.8 Wind. It shall be demonstrated, by testing or calculations, that the tank assembly will withstand 70 mph wind as specified (see 3.5.11.1 and 3.11.i). The tank assembly shall be empty for this demonstration.

4.5.17 Servicing cycle. The tank assembly inner shell shall be filled to design capacity with liquid oxygen or liquid nitrogen and the tank left with the vapor vent line shutoff valve wide open until all uninsulated components external to the outer shell have warmed to approximately ambient temperature. Following this stabilization, 50 servicing cycles shall be performed, with each cycle performed as specified below, in the order listed (see 3.5.13).

- a. Connect the servicing hose disconnect fitting to a container suitable for use with liquid oxygen or liquid nitrogen.
- b. Close the vapor vent line shutoff valve.
- c. Open the pressure buildup control valve until the inner shell vapor phase pressure has risen to not less than 50 psig, and then close the buildup control valve.
- d. Open the liquid servicing line shutoff valve and transfer not less than 1 gallon of liquid into the receiving container through the servicing hose.
- e. Close the liquid servicing line shutoff valve.
- f. Open the vapor vent line shutoff valve to vent the inner shell vapor space to atmospheric pressure.
- g. Allow the tank to remain with the vapor vent line shutoff valve fully open until all ice and frost are gone from the buildup system and servicing line. The application of external heat to expedite warmup is permissible.

The tank assembly shall complete the specified 50 servicing cycles without necessity for servicing or maintenance of any kind, or shall be considered to have failed the test.

4.5.18 Mechanical check. Upon completion of the above tests, a critical inspection shall be made of components to determine their operability and any damage or undue wear incurred during the tests. Steel parts subject to high stress and that are suspected of having defects shall be subjected to magnetic particle inspection in accordance with ASTM E1444. Nonmagnetic parts suspected of having defects shall be inspected with fluorescent liquid penetrant in accordance with ASTM E1417.

4.5.19 Reliability demonstration and test. Satisfactory completion of all tests required herein will be considered to demonstrate acceptable compliance with the quantitative reliability requirements of this specification (see 3.5.13).

4.5.20 Servicing and maintenance. All normal preventive maintenance and servicing operations specified in the contractor's maintenance and instruction handbook shall be performed to determine their adequacy, ease of accomplishment, and the accessibility of parts and assemblies for performance of same. As far as practicable, these tests shall be conducted as part of the normal preventive maintenance, servicing, and inspections performed in accomplishing the testing specified herein. Particular attention shall be given to maintenance with a minimum number of tools; servicing and operation by personnel wearing heavy gloves, and provisions made to prevent accumulation of dirt, snow, and ice, that may hinder servicing and operation (see 3.5.14).

4.5.20.1 Corrective and preventive maintenance. Compliance with corrective and preventive maintenance requirements shall be demonstrated through a maintenance demonstration procedure approved by the procuring activity (see 3.5.14).

4.5.21 Disconnect coupling torque resistance tests. The liquid fill-drain line disconnect coupling and the servicing line disconnect fitting shall each be subjected to a torque of not less than 300 ft-lb per inch of nominal line size applied to the coupling or fitting first in one and then in the other direction of rotation with a 24 inch wrench. Any twisting or distortion of, or damage to tank piping or connections, or lack of clearance to use the 24-inch wrench, shall be cause for rejection (see 3.5.7.1, 3.5.7.2).

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department or Defense Agency automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature which may be helpful, but is not mandatory.)

6.1 Intended use. The TMU-27/M tank assembly is for use in servicing aircraft liquid oxygen breathing systems and any other application where aviator's liquid oxygen is used. The unit can be airlifted when filled to capacity and placed in use immediately upon arrival.

6.2 Acquisition requirements. Acquisition documents must specify the following:

- a. Title, number, and date of this specification.
- b. Issue of the DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2).
- c. When first article is required (see 3.1).
- d. Item identification (see 3.7).
- e. If the sampling inspection level is to be other than normal (i.e., tightened or reduced) (see 4.3.2).
- f. Packaging requirements (see 5.1).

- g. If tank pressure certification documentation is required (see 3.5.3).
- h. A bubble-point test method if other than SAE ARP 901 (see 4.5.12.1).
- i. Appropriate skill level for maintenance personnel (3.6.14).

6.3 Definitions. For purposes of this specification, the following definitions will apply:

6.3.1 Failure. For reliability purposes, a failure is defined as any failure or malfunction that could prevent satisfactory (within specified limits) and safe operation in the primary functions of receiving, storing, transporting, and dispensing the specified liquid.

6.3.2 Pressures. All pressures referred to herein, unless specified as absolute or denoted by the symbol psia, will be interpreted as pounds per square inch (psi) gage.

6.3.3 Valve cycle of operation. A cycle of operation for a valve is defined as opening the valve from sealing a differential pressure of not less than 50 psig to the not less than three-fourths open position, and reclosing the valve with a torque of 60 ± 5 in-lb per inch of valve nominal size.

6.3.4 Fibrous particle. A fibrous particle is defined as a long, slender particle whose maximum cross sectional dimension is 40 microns.

6.4 International standardization agreement. Certain provisions of paragraphs 3.5.4.1, 3.5.8, and 3.6.12 are the subject of international standardization agreement Air Standardization Coordinating Committee Air Standard 14/3, STANAG 3547. When amendment, revision, or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels, including standardization offices, if required.

6.5 Finish. MIL-HDBK-808 can be used as a guide in conjunction with AF drawing 7545352.

6.6 Environmental testing. Test methods are specified in MIL-STD-810.

6.7 Membrane filter. The 5-micron Mitex™ membrane filter is available from the Millipore Corp., 80 Ashby Rd., Bedford, MA, 01730.

6.8 Subject term (key word) listing.

- Annular space
- Burst disc
- Cryogenic liquids
- Inner shell
- Mobility
- Outer shell
- Pressure vessels

6.9 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:

Air Force - 99

DLA – GS

Navy – AS

Army - AV

Preparing Activity:

Air Force - 84

(Project No. 3655-2006)

Review activities:

Navy - YD

