

MILITARY SPECIFICATION

WIRE, ELECTRIC, POLYIMIDE-INSULATED, COPPER OR COPPER ALLOY

This supplement forms a part of Military Specification MIL-W-81381A, dated 15 November 1972.

SPECIFICATION SHEETS

MIL-W-81381/1 through MIL-W-81381/6 - Canceled 18 December 1981

MIL-W-81381/7	Wire, Electric, Fluorocarbon/Polyimide Insulated, Light Weight, Silver Coated Copper Conductor, 600 Volts, 200°C, Nominal 5.8 Mil Wall
MIL-W-81381/8	Wire, Electric, Fluorocarbon/Polyimide Insulated, Light Weight, Nickel Coated Copper Conductor, 600 Volts, 200°C, Nominal 5.8 Mil Wall
MIL-W-81381/9	Wire, Electric Fluorocarbon/Polyimide Insulated, Light Weight, Silver Coated High Strength Copper Alloy Conductor, 600 Volts, 200°C, Nominal 5.8 Mil Wall
MIL-W-81381/10	Wire, Electric, Fluorocarbon/Polyimide Insulated, Light Weight, Nickel Coated High Strength Copper Alloy Conductor, 600 Volts, 200°C, Nominal 5.8 Mil Wall
MIL-W-81381/11	Wire, Electric, Fluorocarbon/Polyimide Insulated, Medium Weight, Silver Coated Copper Conductor, 600 Volts, 200°C, Nominal 8.4 or 15.4 Mil Wall
MIL-W-81381/12	Wire, Electric, Fluorocarbon/Polyimide Insulated, Medium Weight, Nickel Coated Copper Conductor, 600 Volts, 200°C, Nominal 8.4 or 15.4 Mil Wall
MIL-W-81381/13	Wire, Electric, Fluorocarbon/Polyimide Insulated, Medium Weight, Silver Coated High Strength Copper Alloy Conductor, 600 Volts, 200°C, Nominal 8.2 or 8.4 Mil Wall

FSC 6145

MIL-W-81381A
SUPPLEMENT 1B

SPECIFICATION SHEETS (Continued)

- MIL-W-81381/14 Wire, Electric, Fluorocarbon/Polyimide Insulated, Medium Weight, Nickel Coated High Strength Copper Alloy Conductor, 600 Volts, 200°C, Nominal 8.2 or 8.4 Mil Wall
- MIL-W-81381/15 (SAF) and MIL-W-81381/16 (USAF) - Canceled, 15 January 1971
- MIL-W-81381/17 Wire, Electric Fluorocarbon/Polyimide Insulated, Light Weight, Silver Coated Copper, 600 Volts, Nominal 4.6 Mil Wall
- MIL-W-81381/18 Wire, Electric, Fluorocarbon/Polyimide Insulated, Light Weight, Nickel Coated Copper, 600 Volts, Nominal 4.6 Mil Wall
- MIL-W-81381/19 Wire, Electric, Fluorocarbon/Polyimide Insulated, Light Weight, Silver Coated High Strength Copper Alloy, 600 Volts, Nominal 4.6 Mil Wall
- MIL-W-81381/20 Wire, Electric, Fluorocarbon/Polyimide Insulated, Light Weight, Nickel Coated High Strength Copper Alloy, 600 Volts, Nominal 4.6 Mil Wall
- MIL-W-81381/21 Wire, Electric, Fluorocarbon/Polyimide Insulated, Light Weight, Tin Coated Copper Conductor, 600 Volts, 150°C, Nominal 5.8 Mil Wall
- MIL-W-81381/22 Wire, Electric, Fluorocarbon/Polyimide Insulated, Medium Weight, Tin Coated Copper Conductor, 600 Volts, 150°C, Nominal 8.4 or 15.4 Mil Wall

Preparing activity:
Navy - AS
(Project No. 6145-0816)