

INCH POUND

MIL-PRF-24236C
SUPPLEMENT 1
2 March 2001

SWITCHES, THERMOSTATIC, (METALLIC AND BIMETALLIC),
GENERAL SPECIFICATION FOR

This supplement forms a part of Performance Specification
MIL-PRF-24236C, dated 3 September 1999.

SPECIFICATION SHEETS

MIL-PRF-24236/1	Switches, Thermostatic, (Bimetallic), Subminiature, Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 5 Amperes.
MIL-PRF-24236/2	Switches, Thermostatic, (Bimetallic), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 5 Amperes.
MIL-PRF-24236/11	Switches, Thermostatic, (Bimetallic), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 1 Amperes.
MIL-PRF-24236/13	Switches, Thermostatic, (Bimetallic), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 1 Amperes.
MIL-PRF-24236/15	Switches, Thermostatic, (Metallic), Type II, Hermetically Sealed, Overheat Detector, Adjustable, Single Terminal, 3 Amperes.
MIL-S-24236/16	Switches, Thermostatic, (Metallic), Type II, Hermetically Sealed, Overheat Detector, Adjustable, Dual Terminal, 3 Amperes. INACTIVE FOR NEW DESIGN.
MIL-PRF-24236/19	Switches, Thermostatic, (Bimetallic), (Subminiature), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 1 Amperes.
MIL-PRF-24236/20	Switches, Thermostatic, (Bimetallic), Subminiature, Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 2 Amperes and Low Level.
MIL-PRF-24236/24	Switches, Thermostatic, (Bimetallic), Subminiature, Type I, Hermetically Sealed, Single Pole, Double Throw (SPDT), 2 Amperes.
MIL-PRF-24236/25	Switches, Thermostatic, (Bimetallic), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 2 Amperes.

Preparing Activity:
DLA - CC

(Project 5930-1739)