

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (ALUMINUM OXIDE),  
ESTABLISHED RELIABILITY, AND NONESTABLISHED RELIABILITY  
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-39018C, dated 7 January 1991

|                  |   |
|------------------|---|
| MIL-PRF-39006/1F | Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), Non-Established Reliability and Established Reliability, Styles CU12 (Uninsulated), CU13 (Insulated), and CUR13 (Insulated). |
| MIL-PRF-39018/2D | Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Nonpolarized), Styles CU14 (Uninsulated) and CU15 (Insulated).   |
| MIL-PRF-39018/3E | Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), Non-Established Reliability and Established Reliability Styles CU16 (Uninsulated) CU17 (Insulated) and CUR17 (Insulated).    |
| MIL-PRF-39018/4B | Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), Non-Established Reliability and Established Reliability Styles CU71 (Insulated) and CUR71 (Insulated).                       |
| MIL-PRF-39018/6B | Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), Established Reliability Style CUR19 (Insulated).   |
| MIL-PRF-39018/7A | Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), (Four-Terminal), Established Reliability Style CUR19 (Insulated).  |

Preparing activity:  
DLA - CC

(Project 5910-2096-99)

AMSC N/A

FSC 5910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.