

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM,
ESTABLISHED RELIABILITY, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-39003H, dated 20 March 1992

| | |
|------------------|---|
| MIL-PRF-39003/1 | Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR13. |
| MIL-PRF-39003/2 | Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR09. |
| MIL-PRF-39003/3 | Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR23. |
| MIL-PRF-39003/4 | Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Nonpolarized, Sintered Slug), Established Reliability, Style CSR91. |
| MIL-PRF-39003/6 | Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug) Established Reliability, Style CSR33. |
| MIL-PRF-39003/9 | Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), High Frequency, Established Reliability, Style CSR21. |
| MIL-PRF-39003/10 | Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Styles CSS13 and CSS33 (High Reliability Applications). |

Preparing activity:
DLA - CC

(Project 5910-2094)

AMSC N/A

FSC 5910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.