

PERFORMANCE SPECIFICATION  
RESISTOR, VARIABLE, WIRE-WOUND  
(LOW OPERATING TEMPERATURE),  
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-19D, dated 11 June 1999 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete and substitute:

“

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: DSCC/VAT, Post Office Box 3990, Columbus, OH 43216-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

“

PAGE 2

1.2.1.3, Table II, delete footnote 1/

PAGE 3

2.2.1, Delete and substitute:

“(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Document Automation and Production Service, Building 4H (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094).”

PAGE 9

3.14, Delete and substitute paragraph title:

“Salt atmosphere (corrosion) for Salt spray (corrosion)”

PAGE 19

4.6.9, Delete and substitute paragraph title:

“Salt atmosphere (corrosion) (see 3.14) for Salt spray (corrosion) (see 3.14).”

MIL-PRF-19D  
AMENDMENT 1

Custodians:

Army - CR  
Navy - EC  
Air Force - 11

Preparing activity:  
DLA - CC

Review activities:

Army - AR, AT, AV, CR4, MI  
Navy - AS, CG, MC, OS  
Air Force - 99

(Project 5905-1675)