

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE),  
TANTALUM, ESTABLISHED RELIABILITY,  
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-39006E, dated 15 January 1998

MIL-C-39006/9	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR65.
MIL-C-39006/18	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR10.
MIL-C-39006/19	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR14.
MIL-C-39006/20	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR17.
MIL-C-39006/21	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR69.
MIL-PRF-39006/22	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR79.
MIL-PRF-39006/25	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR81.
MIL-PRF-39006/28	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), High Reliability, Style CLS79.
MIL-PRF-39006/29	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), High Reliability, Style CLS81.
MIL-PRF-39006/30	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR90
MIL-PRF-39006/31	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug), (Extended Range), 85°C (Voltage Derated to 125°C) Established Reliability, Style CLR91
MIL-PRF-39006/32	Capacitors, Fixed, Electrolytic (Non-Solid Electrolyte ) Tantalum, (Non-Polarize, Sintered Slug) 85°C (Voltage Derated to 125°C), Established, Reliability, Style CLR82

Preparing activity:  
DLA - CC

(Project 5910-2080)

AMSC N/A

FSC 5910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.