

MILITARY SPECIFICATION  
ATTENUATORS, FIXED  
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-A-3933E, dated 24 April 1985,  
and is approved for use by all Departments and Agencies of the  
Department of Defense.

PAGE 5

3.4.4.1, delete and substitute:

"3.4.4.1 Connector metal parts. Unless otherwise specified, the male center contact pins shall be captivated and made of corrosion-resisting steel or beryllium copper. Corrosion-resisting steel pins shall be type 302 or type 304 in accordance with QQ-S-763, or type 303 in accordance with ASTM A582. Beryllium copper pins shall conform to QQ-C-530 and shall be silver plated in accordance with QQ-S-365 or gold plated in accordance with MIL-G-45204, type II, class 1. The female center contact pins shall be captivated and made of beryllium copper conforming to QQ-C-530 and silver plated in accordance with QQ-S-365 or gold plated in accordance with MIL-G-45204, type II, class 1."

Custodians:  
Army - ER  
Navy - EC  
Air Force - 85

Review activities:  
Army - MI  
Air Force - 11, 17, 99  
DLA - ES

User activities:  
Navy - AS, MC, SH  
Army - AR

Preparing activity:  
Navy - EC

Agent:  
DLA - ES

(Project 5985-0998)