

INCH-POUND

MIL-PRF-83536B
SUPPLEMENT 1
15 April 2003

SUPERSEDING
MIL-PRF-83536A
SUPPLEMENT 1A
1 February 2000

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY,
25 AMPERES AND BELOW, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-83536B, dated 15 April 2003.

SPECIFICATION SHEETS

- MIL-PRF-83536/1 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 5 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coils
- MIL-PRF-83536/2 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 5 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-PRF-83536/3 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 5 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, DC Coils
- MIL-PRF-83536/4 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 5 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-PRF-83536/5 - Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 5 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coils
- MIL-PRF-83536/6 - Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 5 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-PRF-83536/7 - Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 5 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, DC Coils
- MIL-PRF-83536/8 - Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 5 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-PRF-83536/9 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coils
- MIL-PRF-83536/10 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-PRF-83536/11 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, AC Coils

MIL-PRF-83536B

- MIL-PRF-83536/12 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, DC Coils
- MIL-PRF-83536/13 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-PRF-83536/14 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, AC Coils
- MIL-PRF-83536/15 - Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coil
- MIL-PRF-83536/16 - Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coil
- MIL-PRF-83536/17 - Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, AC Coils
- MIL-PRF-83536/18 - Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, DC Coils
- MIL-PRF-83536/19 - Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-PRF-83536/20 - Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, AC Coils
- MIL-PRF-83536/21 - Relays, Electromagnetic, Established Reliability, 3PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coil
- MIL-PRF-83536/22 - Relays, Electromagnetic, Established Reliability, 3PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coil
- MIL-PRF-83536/23 - Relays, Electromagnetic, Established Reliability, 3PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, DC Coils
- MIL-PRF-83536/24 - Relays, Electromagnetic, Established Reliability, 3PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-PRF-83536/25 - Relays, Electromagnetic, Established Reliability, 6PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coil
- MIL-PRF-83536/26 - Relays, Electromagnetic, Established Reliability, 6PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coil
- MIL-PRF-83536/32 - Relays, Electromagnetic, Established Reliability, 3PDT, 25 Amperes (Resistive), Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coil
- MIL-PRF-83536/33 - Relays, Electromagnetic, Established Reliability, 3PDT, 25 Amperes (Resistive), Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coil
- MIL-PRF-83536/34 - Relays, Electromagnetic, Established Reliability, 1PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coil

MIL-PRF-83536B

MIL-PRF-83536/35 - Relays, Electromagnetic, Established Reliability, 1PDT, Low Level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coil

Preparing activity:
DLA - CC

(Project 5945-1193)