

INCH-POUND

MIL-C-28876/13D
AMENDMENT 1
04 MAY 1995

MILITARY SPECIFICATION SHEET

CONNECTORS, FIBER OPTIC, CIRCULAR, RECEPTACLE STYLE,
MULTIPLE REMOVABLE TERMINI, SCREW THREADS,
JAMNUT MOUNTING, WITH 45° STRAIN RELIEF, ENVIRONMENT RESISTING

This amendment forms a part of MIL-C-28876/13D, dated 9 July 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete "STRAIN RELIEF" and substitute "BACKSHELL".

FIGURE 1: Delete "STRAIN RELIEF COUPLING NUT" and substitute "BACKSHELL COUPLING RING".

FIGURE 1: Delete "STRAIN RELIEF HOUSING" and substitute "BACKSHELL HOUSING".

FIGURE 1, title: Delete "strain relief".

PAGE 2

FIGURE 1, tables: Delete the "BB dia" and "JJ thread class 2A" columns of the top table.

FIGURE 1, tables: Add the following row to the top table:

23	43.26 (1.703)	40.60 (1.598)	53.54 (2.108)	51.16 (2.014)	38.10 (1.50)	40.31 (1.587)	41.53 (1.635)	53.16 (2.093)	46.02 (1.812)	57.15 (2.250)	127.00 (5.000)	190.50 (7.500)
see note 5												

FIGURE 1, tables: Add the following row to the bottom table:

23	5	Yellow	1.625-18 UNEF
----	---	--------	---------------

FIGURE 1, title: Delete "strain relief".

PAGE 3

REQUIREMENTS, temperature: Delete in its entirety.

REQUIREMENTS, weight: Add to shell size "23" and to weight (ounces), maximum "28.0".

REQUIREMENTS, fiber optic cable, cable diameter: Delete and substitute:

"Cable diameter: 8.00 ± 0.50 mm (0.315 ± 0.020 inch), 11.80 ± 1.10 mm (0.425 ± 0.043 inch), or 20.75 ± 1.25 mm (.817 ± .049 inch) (see MIL-C-85045/13, MIL-C-85045/15, MIL-C-85045/17, and MIL-C-85045/18)."

MIL-C-28876/130
AMENDMENT 1

REQUIREMENTS: Add the new subsection:

"Protective caps: Each connector shall be supplied with protective caps over the front portion of the connector."

REQUIREMENTS, cleaning procedures: Delete and substitute:

"Cleaning procedures: Each shipment of connectors shall include recommended cleaning procedures. The following wording or equivalent is recommended "To clean, use wipe dampened with alcohol and blow dry with air"."

PAGE 4

TABLE I: Add the following row to the table:

"

23	F	1	P or S	1, 2, 3, 4, 5, or 6	22.00 (.866)	25.40 (1.000)	
----	---	---	--------	------------------------	-----------------	------------------	--

"

Delete "CONCLUDING MATERIAL" and substitute as printed herein.

"CONCLUDING MATERIAL

Custodians:

Army - CR
Navy - SH
Air Force - 85
NASA - NA

Preparing Activity:

Navy - SH

Agent:

DLA - ES

Review activities:

Army - MI
Navy - AS, MC, OS, YD
Air Force - 13, 14, 17, 19, 80, 90, 99
DLA - ES"

(Project 6060-0115-12)