

INCH-POUND

MIL-R-28750C
SUPPLEMENT 1
16 February 1993

MILITARY SPECIFICATION

RELAYS, SOLID STATE, GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-R-28750C, dated 16 February 1993

SPECIFICATION SHEETS

- MIL-R-28750/5 - Relay, Solid State, Hermetically Sealed, Class II, Isolated, ± 50 mA, ± 40 V, AC or DC, Analog Signal Switching, SPST (N.O.)
- MIL-R-28750/6 - Relay, Solid State, Hermetically Sealed, Class II, Isolated, 250 mA, 40 V dc, Signal Switching, SPST (N.O.).
- MIL-R-28750/7 - Relay, Solid State, Hermetically Sealed, Class II, Isolated, 100 mA, 250 V dc, Signal Switching, SPST (N.O.).
- MIL-R-28750/8 - Relay, Solid State, Hermetically Sealed, Class II, Optically Isolated, 600 mA, 50 V dc, Signal Switching, SPST (N.O.).
- MIL-R-28750/9 - Relay, Solid State, Hermetically Sealed, Class II, Optically Isolated, Zero Voltage Turn on, 1 Ampere (2 Amperes with Heat Sink), 40-440 Hz, Power Switching, SPST (N.O.).
- MIL-R-28750/10 - Relay, Solid State, Sealed, Class I, Optically Isolated, Zero Voltage Turn On, 25 Amperes, 250 Volts Maximum, 45-440 Hz, Power Switching, SPST (N.O.).

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0849)

AMSC N/A

1 of 1

FSC 5945

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.