

DETAIL SPECIFICATION

ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL
GENERAL SPECIFICATION FOR

This supplement forms a part of Detail Specification MIL-DTL-3933K, dated 12 April 2011

SPECIFICATION SHEETS

- MIL-DTL-3933/10 - ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL,
COAXIAL LINE (SERIES N),
FREQUENCY RANGE: DC TO 18 GHZ, CLASS III, MEDIUM POWER
- MIL-DTL-3933/14 - ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL,
COAXIAL LINE (SMA CONNECTORS),
FREQUENCY RANGE: DC TO 12.4 GHZ, CLASS IV, LOW POWER
- MIL-DTL-3933/16 - ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL
COAXIAL LINE (SMA CONNECTORS),
FREQUENCY RANGE: DC TO 18 GHZ, CLASS IV, LOW POWER
- MIL-DTL-3933/17 - ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL,
COAXIAL LINE (TNC CONNECTORS),
FREQUENCY RANGE: DC TO 18 GHZ, CLASS IV, LOW POWER
- MIL-DTL-3933/18 - ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL, COAXIAL
LINE (SERIES N),
FREQUENCY RANGE: DC TO 12.4 GHZ AND DC TO 18 GHZ, CLASS III,
LOW POWER
- MIL-DTL-3933/19 - ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL,
COAXIAL LINE (BNC CONNECTORS),
FREQUENCY RANGE: DC TO 4.5 GHZ, CLASS III, LOW POWER
- MIL-A-3933/23 - ATTENUATORS, FIXED, TO-5 CONFIGURATION, CLASS IV, LOW POWER
INACTIVE FOR NEW DESIGN
- MIL-A-3933/24 - ATTENUATOR, FIXED, COAXIAL LINE, (SMA CONNECTORS),
BULKHEAD, CLASS IV, LOW POWER
INACTIVE FOR NEW DESIGN
- MIL-DTL-3933/25 - ATTENUATORS, FIXED, MINIATURE, SPACE LEVEL, NON
SPACE LEVEL, COAXIAL LINE (SMA CONNECTORS),
FREQUENCY RANGE: DC TO 18 GHZ, CLASS IV, LOW POWER
- MIL-DTL-3933/29 - ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL,
CHIP, (SURFACE MOUNT), 0-20 DB,
FREQUENCY RANGE: DC TO 18 GHZ, CLASS IV
- MIL-DTL-3933/30 - ATTENUATORS, FIXED COAXIAL CONNECTOR
SPACE LEVEL, NON SPACE LEVEL,
TYPE 2.92 MM (SMK) FREQUENCY RANGE: DC TO 32 GHZ, CLASS III,
LOW POWER

MIL-DTL-3933K
SUPPLEMENT 1

- MIL-DTL-3933/31 - ATTENUATORS, FIXED COAXIAL CONNECTOR,
SPACE LEVEL, NON SPACE LEVEL, CONNECTOR TYPE 3.5 MM
FREQUENCY RANGE: DC TO 28 GHZ, CLASS III, LOW POWER
- MIL-DTL-3933/32 - ATTENUATORS, FIXED COAXIAL CONNECTOR,
SPACE LEVEL, NON SPACE LEVEL, TYPE 2.92 MM (SMK)
FREQUENCY RANGE: DC TO 42 GHZ, CLASS III, LOW POWER

Custodians:

Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

Project (5985-2011-023)

Review activities:

Army - MI
Navy - AS, MC, SH
Air Force - 71, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.daps.dla.mil>.