

SECTION

TECHNICAL WRITING STYLE GUIDE

This handbook is approved for use by all departments and agencies of the Department of Defense.

INTRODUCTION	1
WORDS	2
SENTENCES	3
PARAGRAPHS	4
GRAMMAR	5
PUNCTUATION	6
USAGE	7
ABBREVIATIONS AND SYMBOLS	8
CAPITALIZATION	9
COMPOUND WORDS	10
MATHEMATICS	11
NUMERALS	12
CROSS-REFERENCING	13
NOMENCLATURE	14
REFERENCES TO STANDARDS	15
TABLES	16
GRAPHS	17
FOOTNOTES	18
EDITING	19
LEXICON	20

REFERENCE LISTS

	Section Page
Abbreviation Rules	8/2
Capitalization Rules	9/6
Editing Marks	19/6
Forming Special Abbreviations	8/7
Greek Alphabet	8/12
Homonyms	8/5
Idioms	7/6
Malaprops	7/5
Metric Conversion	Inside back cover
Powers of 10 ⁻¹⁸ thru 10 ¹²)	9/
Spelling Difficult Words	7/7
Temperature Conversion (C F)	Inside back cover

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Maintenance Management Center, ATTN: DRXMD-EP, Lexington, Ky. 40511, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Capitalizing Quantity and Unit Symbols	9	Hyphenated Compounds in Titles	4
Capitalizing on Illustrations	9	Formal Nomenclature	4
Changes or Revisions	10	Formal Titles	5
Circuit Reference Symbols	10	Lists of Illustrations and Tables	5
Clarity	10	Proper Nouns	5
Consistency in Use	10	References to Publications	5
Panel Nomenclature	11	Table of Contents	5
Diagonal (/)	11	First Word Cap	5
Ditto Marks ("")	11	Lists, Tables, Charts	5
Greek-Letter Symbols	12	Sentence or Statement	5
Graphic Symbols	12	No Cap	5
Hyphenation	12	Letters	6
Illustrations Using Abbreviations or Symbols	13	Hardware Nomenclature	6
Italics	13	Informally Used Titles	6
Number	13	Referencing Informally	6
Parenthetical References	13	Signal Nomenclature	6
Periods	14	Special Capitalization Rules	6
Plurals	14	Copyright Trade names	6
Possessives	15	Government (The Word)	6
Prefixes for Unit Symbols	15	Mach	7
Redundancies	16	Revision or Change Data	7
Spacing	16	Type Styles	7
Temperature Symbol	17	Single-Letter Compound Noun	7
Thru or Through	17	Quick-Reference Capitalization Guide	8
Typewritten or Preprinted Symbols	17		
Verb Tense	18		
		9. CAPITALIZATION	
		Why and When Capitals?	2
		Capitalization Policy	2
		Minimize Use of Capitals	2
		Reasons for Minimizing Use of capitals	2
		Authority for Capitalizing	2
		Capitalizing Abbreviations and Symbols	2
		Modes of Capitalizing	3
		All Cap	3
		Computer Output Direct Pickup)	3
		Illustrations	3
		Headings	3
		Panel Nomenclature	4
		Table Titles	4
		Initial Cap	4
		Acronyms or Coined Words	4
		Captions	4
		Column Headings in Tables or Chart	4
		10. COMPOUND WORDS	
		Definition	1
		Authority	1
		Compounding	1
		Syllable or Word Stress	1
		Factors in Compounding	2
		Types of Compounds	3
		Solid Compounds	3
		Hyphenated Compounds	4
		Separate Words	5
		11. MATHEMATICS	
		Objective	1
		Problems	1
		Mechanics	1
		Style Rules	2
		Equations	3
		Spacing	4
		Italics	5
		12. NUMERALS	
		Spell Out Numerical Quantities	1

Use Numerals	3	Controls and Indicators With Panel Nomenclature	5
Don't Repeat Spelled-Out Number as a Numeral	3	Controls and Indicators Without Panel Nomenclature	6
Hyphen	3	Multiple Controls and Indicators With Same Panel Nomenclature	6
Slant Line	4	Controls and Indicators in Procedures	6
Zero	4	Location Data	7
13. CROSS-REFERENCING		Condensing Nomenclature in Tables and Illustrations	7
Scope	1	In Theory and Descriptive Material ..	7
Policy	1	In Congested Material	7
Methods for Minimizing Cross- Referencing	1	In Tabulations	7
Accuracy	2	In Maintenance Manual Procedures ..	8
Cross-Referencing Mechanics	2	In Artwork	8
Same Manual or Another Volume of Same Manual	2		9
Other Documents	3	15. REFERENCES TO STANDARDS	
Style	3	Government Specifications and Standards	1
Parenthetic, Short Cross- Reference	3	Manufacturer's Specifications for Materials	1
Parenthetic, Long-Cross- References	4	Manual Specification or Contract Number	2
Non-Parenthetic Cross-Reference ...	4	16. TABLES	
With Tables and Charts	4	Definitions	1
With Illustrations Using Figure Numbers	5	Table	1
In Headings	6	Chart	1
Underlining	6	Authority	1
Placement of Cross-References ...	7	When to Use Tables and Charts ...	1
Repetition of Complete Cross-Reference	7	Headings	2
		General Notes, References Etc	2
14. NOMENCLATURE		Layout	2
Definitions	1	Style	3
Nomenclature	1	Front Matter	3
Military Nomenclature	2	Possible Problems with Tables ...	4
Choice of Nomenclature	2	17. GRAPHS	
Military Nomenclature Assigned ...	2	Definitions	1
No Military Nomenclature Assigned	2	Use of Graphs	1
Nomenclature Below Unit Level ...	3	Common Problems with Using Graphs	1
Common Names and Manufac- turer's Names Without Part Numbers	3	Good Practices for Effective Graphs	2
Cost Considerations	3	Types of Graphs	2
Rules for Using Nomenclature	4	Conventional	2
Consistency	4	Bar Graphs	4
Straight-Reading Sequence	4	Stack Graphs	5
Articles (a, an, the)	4	Nomographs	5
Manufacturer's Part Number	5		
Multiple Components With Identical Basic Names	5		

Other Types 5
Graph Construction 5
Scale 6
Title Block 6
Limitations and Restrictions 6
Baseline 7
Interception of Lines 7
Deflector Lines 7
Graph Entry 7
Grids 7

18. FOOTNOTES

Applications 1
Authority 1
In Tabular Material 1
 When to Use 1
 Where to Place 1
 Style 2
In Illustrations 3
 General Notes (Complex
 Illustrations) 3
 General Notes (Simple
 Illustrations) 4
 Multiple-Sheet Illustrations 4
Changes and Revisions 4

19. EDITING

Definition 1
How a Writer Can
 Facilitate Editing 2
Suggestions to the Editor 2
Desirable Editor Attitudes 3
References for Editing 4
Proofreading 4
 Methods of Proofreading 5
 Iterations of Proofreading 5
Edit Marks 6
 Brief Summary 6
 Standard Edit Marks 7

20. LEXICON

Familiar Words 1
Preferred Verbs 16

Section 1

INTRODUCTION

	Page		Page
Objectives and Purposes	1	User Prerequisites	2
How to Use This Style Guide	1	Scope	2

OBJECTIVES AND PURPOSES

This *Technical Writing Style Guide* complements the *Technical Manual Writing Handbook*.

This Style Guide is intended to:

- a. Provide an authoritative guide to technical writing style.
- b. Include only the most important technical writing style information with emphasis on areas where errors are frequently made.
- c. Be easy to read, understand, and use.

The Style Guide does not supplant the official specifications nor any of the standard authorities that apply to instructional technical writing: its rules and suggestions supplement these general-type references by describing specialized applications of established principles, and by making orderly choices among the variations of style found in approved usage.

HOW TO USE THIS STYLE GUIDE

This Style Guide has been prepared using the principles, methods, techniques, and styles recommended both by it and the Handbook.

- a. Each topic or subtopic is presented in a one- or two-page module, where possible.
- b. Subtopics in each section are positioned as nearly as possible in alphabetic order for ease of location. For example, in section 9, in use of abbreviations or symbols, *ditto* marks are found before temperature symbols.
- c. A concise and to-the-point style is used.
- d. Examples of both good and bad usage are provided to clarify borderline cases.
- e. Special lists provide ready references. An index to these lists is located inside the front cover.

f. Indexing and accessing features used in this Style Guide allow information to be found quickly:

- Front cover index aligned with bleed-to-edge locators for sections
- Overall table of contents that shows scope and organization
- Detailed section table of contents for convenient local use with each section
- Alphabetical subject index
- Index of reference lists located inside the front cover
- Metric conversion tables located inside the back cover
- Specific headings for topic and subtopic

Cross-references in sections, or to other sections, are kept to a minimum. All pertinent information is at one location.

h. Examples and illustrations are placed on the same, or a facing page, with the associated discussion. Page layout is for optimum usability.

i. Page numbering system identifies each page with section number and page number.

The following suggestions will help you use the Style Guide properly:

- a. Don't expect this Style Guide to be a complete substitute for any required specification or standard.
- b. If a desired rule isn't in one section, look in another applicable section; or look in the index under the most obvious keyword.
- c. Look for the little things in using the rules and examples. Such things as precise word usage, proper capitalization, careful spacing, and accurate punctuation are highly important in technical writing.

USER PREREQUISITES

The manual writer must be familiar with the basic principles of modern standard English.

SCOPE

The Style Guide is not intended to be complete nor a comprehensive document on common English usage on any of the topics covered. It is intended only to highlight and summarize the important elements of *technical writing* style as compared to literary writing.

Don't expect to find, for example, all the correct uses of a colon - the Style Guide highlights only specialized uses of the colon valuable in technical writing. The Style Guide concentrates on problem areas in which frequent mistakes are made in technical writing.

Refer to the *U. S. Government Printing Office Style Manual* and any authoritative standard English composition text for additional style principles.

Section 2

WORDS

	Page		Page
Simple Words	1	Technical Words	2
Idioms and Jargon	1	Excessive Words	2
Specific Words	1	Pronouns: It, This, etc	3
Preferred Verbs	2	Use of Shall and Will	3
Words in Titles and Headings	2		

SIMPLE WORDS

Simple words are usually short words of few syllables. Use the simplest common words and phrases which convey the intended meaning.

Bad:

Atmospheric turbulence passing around the aircraft may affect the control surface.

Better:

Air turbulence affects control of the aircraft.

IDIOMS AND JARGON

Use idiomatic English in preference to formal English. Use the jargon of the user wherever it makes the material easier to understand and more interesting.

SPECIFIC WORDS

1. Use a word that is:

Concrete rather than vague.

Specific rather than general.

Familiar rather than formal.

2. Replace vague or blanket words with more precise words. Avoid words or phrases that are subject to interpretation.

EXAMPLES:

Poor

As required
adequate

Better:

hand-tighten
approximately 8 in.

3. Define key words that may be understood in more than one sense.
4. Guard against a word taking an unintended meaning in its context.

PREFERRED VERBS

Avoid using verbs that are unfamiliar, vague, or that can be misinterpreted.

EXAMPLES:

Poor:

Ascertain light is off.

Unlock parking brake.

Set the unit so that it can be *seen*.

Better:

Be sure light is off.

Release parking brake.

Position the unit so that it can be *seen*.

WORDS IN TITLES AND HEADINGS

Do

Use words that make titles and headings:

Brief

Accurate

Definite (specific)

Interesting

EXAMPLES:

Definite (Specific)

Interior Painting

Chassis dimensions

Avoid Using

The word *General*

The word *Miscellaneous*

Other non-specific words in titles or headings.

EXAMPLES:

Indefinite (General)

Painting

General Details

TECHNICAL WORDS

Use only when no other wording conveys the precise meaning.

EXCESSIVE WORDS

1. Avoid wordy writing. It is usually bad writing!
2. Eliminate unnecessary verbs that say nothing

Poor:

Corrosion *encountered* in the bore inter-fered with the results *obtained*.

Better:

Corrosion in the bore interfered with the results.

3. Save reader's time by avoiding trite phrases.

For Example:

<i>Instead of</i>	<i>Use</i>
For the purpose of	For
Furnish descriptive information	Describe
In the event that	When
Make application	Apply

PRONOUNS: It, This, etc.

1. When repeating a long technical term or word (part, process, principle, etc.) shortly after its first use, use *it*, *this item*, *this method*, etc., instead of the difficult or long term.

Correct: The electrolyte should be checked. It should . . .

2. When using a multiword series, repeat only the distinguishing word or words instead of the total series for each repetition.

Correct: Diphenylamine is an *explosive stabilizer* that can be detected by a single test on an alcoholic extract. This *stabilizer* is very . . .

USE OF SHALL AND WILL

- shall - mandatory requirement
- will - mandatory requirement
- should - non-mandatory desire or preferred method
- may - acceptable or suggested method

Section 3

SENTENCES

	Page		Page
Clarity	1	Sentence Construction	1

CLARITY

1. Arrange the parts of a sentence so that the meaning is clear on first reading.
2. Make sentences:
 - short
 - simple
 - concise
3. Rewrite sentences that are:
 - confusing
 - awkward
 - illogical
 - obscure
4. Break up long, complex, straggling sentences into several short ones.
5. Don't include words, phrases or clauses that have no direct bearing on the principal thought of the sentence.
6. Don't combine unrelated thoughts in a single compound sentence.

SENTENCE CONSTRUCTION

1. Use one main thought per sentence. Link together several closely related elements in one sentence only if they advance a point or provide an explanation.

Poor:

Check for lube oil, grease, hydraulic fluid, fuel oil, and water leaks and if leaks are discovered, report condition to organizational maintenance.

Better:

Check for leaks of lube oil, grease, hydraulic fluid, fuel oil, and water. If leaks are found, report them to organizational maintenance.

2. Indicate the coordinate rank of ideas by means of parallel structure.

Inconsistent:

Dented or crushed cartridge cases may cause them to jam in the chamber or *extracting problems*.

Parallel: (Consistent)

Dented or crushed cartridge cases may jam in the chamber or *fail to extract*.

During inspection, look for dents, cracks, burrs, *complete* assemblies, and foreign materials.

During inspection, look for dents, cracks, burrs, *incomplete* assemblies, and foreign materials.

3. Locate modifiers close to the word or phrase they modify. Arrange them in logical order to help the reader know, as he reads, what the modifier applies to. Start with what the reader needs to know first or must remember to enable him to understand the sentence.

Poor:

The blade should be rotated 360 degrees in a horizontal position slowly inside the turret mount of the forward power station, to engage the rotor.

The machinery space lights are controlled by two switches port and starboard near the access ladder.

Better:

To engage the rotor, the blade should be rotated slowly 360 degrees in a horizontal position inside the turret mount of the forward power station.

The machinery space lights are controlled by two switches, one near the port side of the access ladder and one near the starboard side.

4. Make sure the antecedent of a pronoun is immediately clear.

Vague:

After connecting the jumper to the relay socket, remove it.

Clear:

. . . remove the relay.

5. When a noun sequence contains words which look like verbs (but aren't), use *the* or some other construction so the reader understands the word is a noun or adjective.

Confusing:

Disconnect shaft assembly and intermediate gear box are secured by a disconnect coupling.

Better:

The disconnect shaft . . .

Section 4

PARAGRAPHS

	Page	Page	
Contents	1	Organization	1

CONTENTS

1. Each paragraph should deal with only one idea.
2. Include in each paragraph only as much as the reader can easily grasp.
3. Keep paragraphs short - three to five sentences.
4. Use concrete details to make a paragraph interesting and effective.

ORGANIZATION

1. Organize each paragraph around a topic sentence which gives the main idea of its contents.
2. Write sentences in paragraphs in logical order, so the thought progresses logically as the user moves from one sentence to another and from one paragraph to another.
3. Avoid breaking a paragraph down beyond the third subdivision. Breakdowns beyond this get too far from the main paragraph heading and make it hard for the user to understand the organization and subordination.

Section 5

GRAMMAR

1. Make each verb agree with its subject in number.

Examples:

Correct: *A series of tests was completed.*

Correct: *Two assemblies of the radio were removed.*

2. Use the active verb form (voice) rather than the passive.

Weak:

A singular verb *is used* with a singular subject.

This procedure *is applicable*.

Better:

Use a singular verb with a singular subject.

This procedure *applies*.

3. Use the passive voice properly when:

- The object or receiver of the action of the verb is more important than the doer.
- The doer of the action is not known.
- The emphasis is to be placed on the receiver instead of the doer.

Weak:

Excessive voltage can ruin the blower motor.

Three heavy brackets pin down the casing on . . .

Better:

The blower motor can be ruined by excessive voltage.

The casing is pinned down by three heavy brackets on . . .

Section 6

PUNCTUATION

	Page		Page
Punctuation Rules	1	Parentheses	4
Apostrophe	1	Period	4
Brackets	1	Quotation Marks	5
Colon	2	Semicolon	6
Comma	2	Slant Line	6
Dash	3	Spacing	7
Ellipsis	3	Underlining	8

PUNCTUATION RULES

1. Plan word order to require a minimum of punctuation.
2. Use punctuation to aid reading and prevent misreading.
3. When extensive punctuation is necessary for clarity, rewrite the sentence.

APOSTROPHE

Use an apostrophe to indicate:

- a. The possessive form of nouns.

EXAMPLE:

The company's proposals were well received

- b. Plurals of letters, numerals, and symbols.

EXAMPLES:

7's 's

a's TO's

BRACKETS

Do not use brackets to avoid parentheses within parentheses in typewritten copy. Rewrite the sentence.

COLON

Use a colon, if desired, to indicate subtitles.

EXAMPLES:

4-34. LUBRICATION: 156-45-001-A UNIT.

4-35. LUBRICATION: 156-45-001-B UNIT.

Use a colon to indicate material to follow - do not use a semicolon.

COMMA

Use commas

- a. Before *and* or *or* in a series of three or more.

EXAMPLE:

a, b, and c

- b. To separate five or more digits.

EXAMPLES:

14,560

234,095

- c. After introductory phrases and clauses when necessary for clarity or ease of reading.

EXAMPLES:

Using a special tool SP1145-56-02, turn the adjustment arm precisely to the inscribed "O" mark.

In general, applications of this ingenious circuit have not proved successful.

Don't use a comma

- a. In numerals of four digits (except when mixed in lists with five or more digits).

EXAMPLES:

3594

4598

- b. In common and decimal fractions.

EXAMPLES:

0.625061

3.14159265

- c. In part numbers and serial numbers.

- d. Between an equipment or part name and its type or part number.

EXAMPLES:

Dummy Load Adapter 480140-100

Electrical clip 919110-15

Between the name of an item and its circuit reference symbol unless the symbol is parenthetical in sense.

EXAMPLES:

The signal is then applied to limiter Q45.

But: Avc action is applied only to the third stage, Q56.

DASH

Dash - Use a dash when introducing items listed at the end of a sentence.

EXAMPLE:

The unit contains three channels - range-sweep generation, range-sweep expansion, and range-sweep limiting.

NOTES

- A colon could have been used instead of the dash.
- For enumerating it is always better to use list format, for example:

The unit contains three range-sweep channels:

Generation
Expansion
Limiting

ELLIPSIS

DEFINITION: Ellipsis refers to leaving out words that would be necessary to make a sentence grammatically complete; it is used to obtain a concise style.

1. *Minor ellipsis*, use:

Comma
Colon
Dash

EXAMPLE: (colon)

Set panel controls as follows:

POWER: ON
AZ: 20
EL: 45
SCAN: ONE BAR

2. *Major ellipsis* use:

... (3 periods) within a sentence
... (4 periods) at the end of a sentence

EXAMPLES:

Apply ... lubricant as shown in figure 5-56.
Use sealing compound type ...

3. Use ... for an intentional omission of an entry in a table if the omission could cause doubt

PARENTHESES

Use parentheses for

- Making condensed figure/paragraph references.
- Marking parenthetical matter for which separation by commas or dashes is insufficient.
- Letters or numbers appearing within a sentence to designate items of a list. Do not use a single parenthesis for this purpose.

EXAMPLE:

The project is divided into four phases: (1) planning, (2) research, (3) analysis, and (4) documentation.

PERIOD

Use a period

- After an abbreviation that spells an English word.
- In headings and titles in text, after each:

Paragraph number
 Paragraph heading
 Figure number

- After a parenthetical entry forming a complete sentence (within closing parenthesis).

EXAMPLE:

(See fig. 4-5.)

- After each sentence of a:

NOTE
CAUTION
WARNING
 Footnote

Don't use parentheses

- Within parentheses.
- To set off a complete sentence within a sentence.

EXAMPLE:

Poor: The mixer (See fig. 5-1.) is a silicon diode.

Better: The mixer (fig. 5-1) is . . .

Or: The mixer is a silicon diode. (See fig. 5-1.)

Don't use a period after

- An abbreviation (except for a, opposite)
- A symbol in a mathematical expression such as cot (cotangent), sin (sine), tan (tangent).
- Figure title.
- Section number.
- Section title.
- Paragraph number/title in table of contents.
- Figure number/title in list of illustrations.
- Entry in parentheses if it is not a complete sentence.

EXAMPLE:

. . . in the rf unit (fig. 4-5) located . . .

Use a period

- In tabular entries:

After each tabulation which is a long, complex sentence.

After any group of words immediately preceding a complete sentence. (Semicolons may be substituted in some cases.)

QUOTATION MARKS

Rules for using:

- Use quotation marks sparingly.
- Place periods or commas within closing quotation mark.

EXAMPLE:

At this point, apply the "sniff," "listen," and "touch" routine.

- Use quotation marks to enclose the first use of a bit of slang, jargon, or figurative language. Thereafter, if the expression must be used repeatedly, omit the quotation marks.

Use quotation marks

- To enclose a brief direct quotation.
- To enclose titles (sections, paragraphs, figures, etc) when used in references. Preferably make such references without stating the title.

Don't use quotation marks

- For emphasis.
- To enclose titles of technical manuals/ other publications (Underlining may be used.)
- To enclose names of:
 - Controls
 - Control positions
 - Indicating devices
 - Test points

unless required for clarity.

EXAMPLES:

Set SELECTOR switch to FM.
Set FREQ RANGE switch to 5.

- To designate letters referring to procedural steps as items in a list. Use underlining instead.

EXAMPLE

See paragraph 4-2C.

SEMICOLON

Use semicolons to separate:

- a. Independent clauses which are internally punctuated with commas.
- b. The clauses of a compound sentence where the usual conjunction (and, but, etc) has been omitted.

EXAMPLE:

Set BATTERY B switch to OFF; set BATTERY C switch to ON.

- c. Groups of similar or related items in run-on lists.

EXAMPLE:

Motor brushes, bearings, and wiring; oil-filled capacitors; cable connectors, lacing and sleeving.

- d. Tabulated procedural items not forming complete sentences.
- e. Short sentences in a relatively simple tabulation.

NOTE

Do not use a semicolon to indicate material to follow - use a colon.

SLANT LINE

Use a slant line (diagonal or virgule) to indicate:

- a. An "either-or" numerical relationship in condensed form.
- b. "Per" in condensed matter.

EXAMPLE: 96 m/sec

SPACING

Space before and after

- A symbol denoting an arithmetical operation.

EXAMPLE:

$$5 + 6 = 11$$

- A dash used as introduction to a listing.

EXAMPLE:

The set contains three controls - power switch, volume control, and temperature indicator.

- Space between an abbreviation/symbol and preceding numeral.

EXAMPLES:

25 ma
3 m
3.5 g
4 V

Don't space between

- A symbol of polarity or tolerance and the succeeding number.

EXAMPLES:

-12 V
17 ±3 ma
25 (+3, -5) pf

- A hyphen and the components of a hyphenated word.

EXAMPLES:

... rust-resistant sealing
... line-of-sight calculation

UNDERLINING

Use underlining on:

- Titles of other technical manuals/publications.
- Letters designating items or procedural steps.

EXAMPLES

Delete item c.
See step a.

- Such items as:

Primary paragraphs headings (in typewritten manuals only).

Unusually important words/phrases.

NOTE

Use underlining sparingly so as not to destroy the highlighting effect. Do not use for emphasis.

Section 7

USAGE

	Page		Page
Definition	1	Unnecessary Words and Redundancies	9
References	1	"Applied to"	9
Preferred Forms	2	Articles (a, an, the)	10
Familiar Words	4	"Comprise"	10
Homonyms	5	"Due to"	11
Malaprops	5	Jacks and Plugs	11
Idioms	6	Relays	11
Spelling	7	"Short Circuit"	11
Plurals	8	"Such that"	12
Procedures	8	Switches and Controls	12
Trade Names	8	"Thru"	13

DEFINITION

"Usage" means choosing the right:

- Word
- Expression
- Idiom

for each meaning, situation, or occasion. Although usage includes grammar, the Style Guide consideration of grammar is limited to highlighting common violations in technical writing. The emphasis is on "errors" that do not violate a grammatical rule, but are nevertheless contrary to established custom. Where several competing "correct" forms are possible, this section makes some arbitrary choices for standardization. The choices are determined by surveys of current usage in technical manuals, textbooks, and periodicals.

NOTE

If terms used in the manual are uncommon (or common terms with an unusual item-peculiar meaning), explain their meaning in a glossary and in the text the first time they appear.

REFERENCES

1. For further information on usage, see:

American-English Usage by Nicholson

Modern English Usage by Fowler

Webster's New International Dictionary (or its abridgment the *New Collegiate Dictionary*)

Electronics and Nucleonics Dictionary by Cooke and Markus

Communications-Electronics Terminology AFM100-39, the official word-definition publication

The United States Air Force Dictionary

Any standard textbook of formal grammar (senior high school or higher)

2. Use military terms in accordance with *Joint Chiefs of Staff (JCS) Publication 1* and any authorized dictionary or glossary of military terms.
3. Use terms for automatic electronic test and checkout in accordance with MIL-STD-1309.

NOTE

For cases not covered either by this Style Guide or the standard authorities listed above, determine usage by inspecting recently published technical textbooks or well-edited technical periodicals. Limit this check to publications of about the same level of technical difficulty as the material you are writing. Make certain that your reader can be expected to understand the terms and expressions you select for use.

PREFERRED FORMS

In the following list, generally use the words or expressions in the first column in preference to those in the second column. However, this typical list is based on the most frequently used technical manual applications of the words listed; in non-technical applications, the words given in the second column may be preferred.

Generally Preferred Form	Generally Unpreferred or Incorrect Form
control service	flipper
data is (when the word is synonymous with "information")	data are (not recommended except in formal writing or where plural usage is necessary for correct understanding by reader)
dived	dove
ensure (to make certain)	insure (means, primarily to protect against)
flammable (current USAF preference)	inflammable (former preference)
graticule (used with oscilloscope)	
indexes, appendixes, matrixes	indices, appendices, matrices (acceptable in formal writing)
indicates (on meters)	reads

lamp lights	lamp (or light) illuminates, light lights
locked on to	locked-on to, locked onto
optimum	most optimum
reinstall (to put back the original item)	replace (to put in a new item in place of the original one)
communication (simple or single type) between stations	Note: Use of singular and plural forms is in a confused state. As a general rule, avoiding using "communications" in a singular sense.
communications system (multiple service)	
plastic material or materials; a plastic	...
plastics (as a single word for plastic materials)	...
plastics industry	...
plastics engineering	...
remove nut (3) securing arm (4) to . . . (or "that secures")	remove nut (3) holding . . .
repairable/unrepairable (as of a defective unit)	reparable/irreparable (this spelling changes the syllable accent)
reticle (used with optical systems)	...
servopositioner	actuator
the example (or item) discussed above	said example, said item, etc
to the emitter (pin 2)	to emmitter 2, to emitter (2)
electromagnetic vibrator, synchronous vibrator (see below)	vibrator, chopper (correct in usage defined below)

"Synchronous vibrator": An electromagnetic vibrator that simultaneously interrupts dc voltage and mechanically rectifies the resultant ac voltage after ordinary transformation to higher (or lower) value.

"Chopper": An electromagnetic vibrator that chops an ac or dc voltage for subsequent electronic processing, such as amplification or time sharing. (Based on definitions in Cooke and Markus dictionary.)

FAMILIAR WORDS

Use the familiar or simple word rather than the unfamiliar or complex one, and the concrete word rather than the abstract - provided the more common word conveys the desired idea accurately to your reader. Use complex or abstract terminology only if there is no simpler way of expressing an idea.

NOTE

Remember that few words have exact synonyms; most of the words in the second column must be used sometimes - in some contexts, they are the preferred forms.

For Simplicity
Use:

ask
before
check that
circuit, circuits
class
concept
dry, dried up

enough
exact, strict
go
happen
help
include, consist of
inform
informed, aware
lift, raise
model, unit, type, variation, modification,
 alternate unit
name, panel name, lettering, callout

necessary, essential
often, seldom
part
partly
regardless
separate, distinct
set off, start, cause
stick, stick together
stop
sum up, summarize
the (number) unit
totaled, added up to
try
watch

Rather than:

inquire
prior to
determine that
circuitry
category
philosophy
desiccated (desiccant is good basic usage,
 however)
sufficient
meticulous
proceed
materialize
assist
comprise
apprise
cognizant
elevate
configuration* (good word when used
 according to dictionary definitions)
nomenclature (often an unnecessary term,
 except in "official" sense)
requisite
frequently, infrequently
percentage, proportion
partially
irregardless (always an illiteracy)
discrete
precipitate
adhere, cohere
cease
recapitulate
the (number) configuration*
aggregated
attempt, endeavor
observe

*Configuration = relative distribution or arrangement of parts in a structure, as in an antenna array. This definition, plus that of the dictionary, suggest that use of the term be generally restricted to any organized assortment of physical or geometric parts in which the structural or visual pattern is the significant characteristic.

HOMONYMS

Avoid the inadvertent use of the wrong one of a pair of "sound alike," referred to as homonyms. The following list may alert you to errors of this type.

bear	bare
complement	compliment
die, dying	dye, dyeing
discreet	discrete
dual	duel
fair	fare
fourth	forth
fuse	fuze
great	grate
hear	here
lead (metal)	led
lie	lye
peel	peal
pour	pore, poor
principal	principle
rite	right
site	sight
sign	sine
stationery	stationary
there	their
threw	through (thru)
to	too, two

MALAPROPS

Avoid inadvertent use of the wrong word. Unless you take care, you may write a grotesquely inappropriate word because of its superficial resemblance to the correct one. Errors of this type are referred to as malaprops (from Mrs. Malaprop, a character in fiction).

Words in both columns are correct but must be used as required by the context.

Intended Word	The Malaprop
alternative	alternate
basic	basal
cellular	cellulose
clean	cleanly
cleaned	cleansed

cleanness
 continuous
 creditable
 effect
 exponential
 fluorescent
 foreword
 germanium
 homogeneous
 hygrometer
 incredible
 intradepartmental
 misadjusted
 material
 nonresistive
 ordnance
 precedence
 precipitous
 proceed
 reliable
 respectively
 reversals
 simulated

cleanliness
 continual
 credible
 affect
 expotential
 florescent
 forward
 geranium
 homogenous
 hydrometer
 incredulous
 interdepartmental
 maladjusted
 materiel
 nonresistant
 ordinance
 precedents
 precipitate
 precede
 reliant
 respectfully
 reversion
 stimulated

IDIOMS

Clarify and simplify your writing by correct use of English idiom. An idiomatic expression may not make sense when you pull it apart word for word, or try to translate it literally into some other language, but the complete expression does make sense to any English-speaking person. The meanings of many idioms are precise enough that you can use them in any type of engineering or scientific writing. They are frequently the simplest means of developing accurate concepts in your reader's mind.

Remember that reputable idiomatic English is good English. As long as you avoid slang, your reader, regardless of his educational level, is not offended by use of his everyday language.

The following list of representative English idioms will help you recognize others of their kind.

To determine which preposition to use with a given controlling word for correct idiomatic English, look up the controlling word in Nicholson's *American-English Usage* or Webster's *New International Dictionary*. For example, to choose between "identical with" and "identical to," look up "identical."

Approved Idiom

Dressed-up Alternative

airplane (or aircraft) took off
 can do without, get along without
 climb down

airplane departed from surface of the land
 can function in the absence of
 descend

let out
make sure, make certain
touching one another (or each other)

roughed out the required maintenance plan

take care
take into account

the lamp (or light) comes on, goes off, goes
out (but does not "come in"), lights up, or
lights
will catch fire

SPELLING

Check your spelling. Particularly look out for mistakes in spelling words such as the following:

accommodate
all right (always two words)
chassis (singular and plural; not analogous
with basis)
concurrent, concurring, concurrence
desiccant
desirable, undesirable
develop (not "develope")
envelops (envelopes are containers)
feasible
flexibility
gauss (for both singular and plural)
incompatible, incompatibility
its (possessive pronoun)
liaison
miniscule

extend (or loosen)
ascertain
so placed that each of the several units
touches each of the units external to itself
(Note: The *New International Dictionary*
requires 70 words to define "one another"
and 50 to define "each other." Idiomatic
expressions provide remarkably concise
meanings.)
hastily prepared a tentative plan designating
the anticipated maintenance operations
apply caution
consider appropriate precautionary reser-
vations
the lamp (or light) illuminates, extinguishes,
incandesces, luminesces, becomes in-
candescent or nonincandescent
will ignite and burn

occurred, occurrence, occurring
parenthesis (singular), -es (plural)
procured, procuring

recommend, recommendation
reconnaissance
recurring, recurrent, recurrence
siege
seize, seizing
smooths (not analogous with soothes)
surveillance
too (as in too much, too fast)
torquing
transferred, preferred, deferred, referred
trunnion
volume (not analogous with column)

If the dictionary lists two or more spellings for the same word, use the first one given, except for spellings recommended for technical writing below:

adapter
aging
ax
biases, biasing

Boolean algebra
bus, buses
canceled, canceling
cannot ("can not" only for emphasis)

catalog
 diagrammed, diagramming
 disk (except phonograph disc or anatomical disc)
 fulfill, fulfilled, fulfillment
 gage (formerly gauge)
 gray
 gyros, servos, zeros, photos, salvos, (but: echoes)
 henrys
 judgment
 leveled, leveling
 louver

mileage
 movable, unmovable
 percent
 practice (noun and verb)
 preventive
 programmed, programming
 sizable
 skeptical
 skillful
 stenciled
 tunable
 usable, reusable, unusable

PLURALS

The dictionary does not spell out plurals that follow the regular rules. The rules are usually found in the introductory pages of the dictionary. The largest class most English words form plurals simply by adding s (nail, nails) or es (brush, brushes).

PROCEDURES

Use a sentence arrangement that guards against performing procedures in the wrong sequence. For example, if a tool or instrument is needed, provide a reference to that fact at the beginning of the first sentence of the procedural step, or take care of the situation by some other simple means.

EXAMPLES:

- Using special wrench 140-35-20A, tighten . . .
- With volt-ohm-millimeter set at 50 ma dc scale, measure current . . .

TRADE NAMES

When an accurate and easily recognizable standard-item name exists, avoid using a copyright trade name.

If a trademark name must be used, capitalize it.

The following lists a few typical trade names with possible standard-item equivalents.

Trade Name	Standard-Item Name (Or approximation)
Kodak	camera
Selsyn, Autosyn	synchro
Invar	Nonexpanding nickel-alloy steel
Variac, Powerstat	variable autotransformer
Multigraph	multilith press

Teflon

polytetrafluorethylene resin insulation

Better use the trade name!

Plexiglas

clear acrylic plastic

Electromatic

electric typewriter

Intrafax

facsimile system

UNNECESSARY WORDS/REBUNDANCIES

Avoid indirect, noncommittal, indefinite, or space-filling expressions. Guard against wordy and useless common expressions and sentence openings.

Guard against all types of loose writing. If a word or phrase is unessential, delete the offending expression or rewrite the sentence.

EXAMPLES (POOR USAGE):

- It can be said that
- It is obvious that . . .
- There are several reasons why . . .
- We must now proceed to . . .
- This is more readily understood in the form . . .
- A small, 2-ounce can of oil . . . (Omit either "small" or 2-ounce.")
- The agency ordered a total of 8000 sets. (Omit "a total of.")

APPLIED TO

Use applied to in preference to fed to in bringing a signal to a particular point.

Use fed to if signal power is consumed by the receiving device, or if the signal is applied to the point through a specified route.

Generally, applied to is adequate for the majority of purposes.

EXAMPLES (CORRECT):

- The sharp negative trigger from the collector of Q1145 is applied to the emitter of inverter Q1146.
- The signal is fed through a filter network to the base (pin 1) . . .
- Between signals, the excess current is fed to dummy-load resistors R19, R20, and R25.

ARTICLES (a, an, the)

Use	Omit in
As required for clarity.	Procedural steps.
In descriptive type special notations.	Tabular entries.
for precise expression.	Descriptive parenthetical inserts in step-by-step procedures.
In descriptive matter in straight text.	Illustrations.
In introductory descriptions for procedures and inspections.	Terse text.
	Text with illustrations.

Omit before nouns followed by:

- Part number
- Type number
- Circuit reference number
- Callout index number

EXAMPLES:

- The TIMING ADJ switch is . . . But: TIMING ADJ switch S45 is . . .
- The signal is applied to the control-grid circuit of shaper Q64 . . .
- GAIN control R46 (3) is located on unit control strip (2).

EXCEPTION: Sometimes clarity may require that you regard the number or symbol as being of a semiparenthetical nature. Thus:

The function of the control tube, Q85, is closely interrelated with that of the control relay, K65.

COMPRISE

The whole of anything comprises its constituent parts; it is not comprised of them. Use the word sparingly, but if you must, do so in the following manner: (See Nicholson's *American-English Usage*.)

CORRECT: The channel comprises a voltage amplifier, a relay tube, and a power-switching relay.

INCORRECT: The channel is comprised of a voltage amplifier, . . . (Use "consists of," "contains," "includes," as appropriate.)

DUE TO

Avoid using "due to" to modify a word or expression that cannot be grammatically (or idiomatically) modified by it. For example:

INCORRECT: The output potential is maintained at 5.3 v due to the action of limiter Q65.

CORRECT: The output potential is maintained at 5.3 by (or owing to, or because of) the action of limiter Q65.

Use of "due to" should be limited to introducing adjective-type modifiers, that is, modifiers that modify nouns. It should not be used to introduce adverbial modifiers as has been done in the incorrect sentence given above ("due to" modifies "is maintained").

CORRECT: The amplifier modification reduces distortion due to cross-modulation effects.

"Due to" correctly introduces an adjectival phrase that modifies "distortion" - a noun.

JACKS AND PLUGS

Refer to connectors as "jacks" and "plugs" only:

- if they are telephone-type jacks and plugs
- if the connector is designed to accept a test probe.

Refer to other types of connectors as "connectors."

RELAYS

"Energize" (and deenergize) is normally a transitive verb and needs an object; it needs something to energize.

Use	Don't use
... relay K ... is energized	... relay K ... energizes
... relay K ... becomes energized	
... contacts of energized relay K energized contacts of relay K ...

SHORT CIRCUIT

Prefer	To
"short cricuit" (noun)	"short" (colloquial)
"short-circuit" (verb)	

Abbreviation: "short." (Use period.)

SUCH THAT

Avoid using "such that" to modify a word or expression that cannot be grammatically (or idiomatically) modified by it. For example:

INCORRECT: The circuit functions such that the output trigger is delayed by only 0.03 microsecond.

- Correct by changing "such that" to "in such a manner that."

"Such that" can properly introduce only an adjective-type modifier, usually in the form of a dependent clause that modifies a noun. It must not be used in the form of a dependent clause that modifies a noun. It must not be used to introduce an adverbial modifier as has been done in the incorrect example above.

CORRECT: The total resistance is such that current flow is reduced to less than 2 microamperes.

- "Such that" correctly introduces the adjectival clause "current flow is reduced . . ." which modifies the subject "resistance."

SWITCHES AND CONTROLS

1. Button-type switch

Use

Don't use

Press

Depress

Press and Hold

EXAMPLE:

Press and hold SCOPE TEST switch until a series of dots appears across oscilloscope screen.

2. Continuous-action rotary control with specified dial reading or marking -

Use: "Turn . . . to . . ."

EXAMPLE:

Turn ATTEN control to 15.3.

3. Turning action when an indicating device must be observed to determine correct adjustment point.

Use: "Adjust . . . for . . ."

EXAMPLE:

Adjust ATTEN control for -45 dbm on meter M23.

4. Mechanically fixed or detented positions -

Use: "Set . . . to . . ."

EXAMPLES:

- Set STEP ADJ control R23 (fig. 4-6) to its sixth position (six clicks from full counterclockwise).
- Set INTERP switch to READ.

5. Unmarked positions -

Use parenthetical clarification, if possible

EXAMPLE:

Set POWER switch (2) to up (on) position.

THRU

Use thru:

- a. In numerical or alphabetical sequences.
- b. In certain copyright trade names.

In all other cases use through.

Correct

The modification applies only to units with serial numbers 9456 thru 9934.

The power supplies are described in paragraphs 8-34 thru 9-45.

Incorrect

The signal is applied to the emitter of Q15 thru resistor network R12, R15, and R18.

Section 8

ABBREVIATIONS AND SYMBOLS

Page	Page		
Why Abbreviations and Symbols?	1	How to Use (cont)	9
Brief Summary of Rules	2	Capitalizing on Illustrations	9
Definitions	3	Changes or Revisions	10
Abbreviation	3	Circuit Reference Symbols	10
Symbol	3	Clarity	10
Abbreviation versus Symbol	4	Consistency in Use	10
Acronym	4	Panel Nomenclature	11
Types of Abbreviations and Symbols	5	Diagonal (/)	11
Authorized References	5	Ditto Marks ("")	11
When Not to Use	6	Greek-Letter Symbols	12
Convenience	6	Graphic Symbols	12
Low-Skill-Level Readers	6	Hyphenation	12
Typewriter Symbols	6	Illustrations Using Abbreviations and Symbols	13
When to Use	7	Italics	13
Frequency of Use	7	"Number"	13
High-Skill-Level Readers	7	Parenthetical References	13
Reader's Need for Special Abbreviations	7	Periods	14
How to Form Special Abbreviations	7	Plurals	14
How to Form Special Symbols	7	Possessives	15
How to Use	7	Prefixes for Unit Symbols	15
Capitalizing Abbreviations (General)	7	Redundancies	16
Capitalizing Abbreviations (Titles)	7	Spacing	16
Capitalizing Acronyms	9	Temperature Symbol	17
Capitalizing Quantity and Unit Symbols		"Thru" or Through	17
		Typewritten or Preprinted Symbols	17
		Verb Tense	18

WHY ABBREVIATIONS AND SYMBOLS?

- To avoid distracting the user and wasting his reading time by needless spelling out of repetitious words or phrases, or abbreviations which have become words. Examples: ac, fm, db, ir, and other commonly used abbreviations.
- To save space and promote clarity in illustrations or tabular format.
- To communicate mathematical concepts or relationships.
- NEVER to make it easier for the writer!

- GENERAL RULES: 1. WHEN IN DOUBT, SPELL IT OUT.
2. HOLD USE TO MINIMUM.

BRIEF SUMMARY OF RULES FOR ABBREVIATIONS AND SYMBOLS

DO's

- Authority**
MIL-STD-12 - text
USAS Y32.2 - illustrations
Panel nomenclature
- Capitalization**
Abbr
Use capitals same as if spelled out.
Sym
Use symbols as shown in MIL-STD-12; keep lower-case symbols as given, even if other text is upper-cased.
- Common abbreviations**
Always use for benefit of user.
- Consistency**
Don't mix in. and inch. If you use in, use ft.
Don't mix Greek and Roman symbols.
Use panel nomenclature spelling throughout manual.
- Panel nomenclature**
Use exactly as it appears on panel throughout manual
- Redundancies**
Avoid.
Example: "dc" not "dc current."
- Revisions**
For major revisions use latest authorized abbr/sym even though older forms appear elsewhere in document (MIL-STD-12).
For minor revisions use existing forms.

DON'Ts

- Clarity**
Don't use if it could confuse user.
Avoid abbreviations which require period at end of sentence.
Avoid same abbreviation for more than one word.
- Hyphens**
Don't hyphenate. Noun and adj take same form.

Example: Ensure that ac is being supplied to the ac plug.
- Periods**
Don't use after a symbol.
Don't use after an abbreviation unless:

1. It spells another English word.

2. It could cause confusion.

3. It's needed for consistency.
- Plurals**
Don't pluralize.
- Possessive**
Don't make possessive.
- Tense**
Don't change to past or future - use the same abbreviation for all tenses.

Special appreviation/symbols (not listed in above authorities or this style guide)

Spell out on first use.

Introduce when necessary for clarity and ease of understanding or reading.

DEFINITIONS

Abbreviation - A shortened form or abridgment of a word, expression, or phrase used to save space and time. In this style guide essentially two types of abbreviations are considered:

- authorized abbreviations (MIL-STD-12)
- special abbreviations (not in MIL-STD-12)

Symbol - An arbitrary or convenitonal sign or combination of numbers/letters used to represent operations, quantities, elements, relations, or qualities. There are many kinds of symbols:

- single letter - capital/lower case, English/Greek
- number - 1 thru infinity, Arabic/Roman
- sign - arithmetic such as +, -, =
- mathematical
- chemical
- arbitrary - such as those commonly on typewriters
- graphic
- specialized - symbols designed specifically for the subject or project of the manual
- physical characteristics:

Example:

Quantity Symbol	Unit Symbol	Abbreviation of Word
length (<i>l</i>)*	Inch (in)	inch (in.)
potential (<u>V</u>)*	volt (V)	volt (v)

*Quantity symbols should be italics (MIL-STD)12), or underlined.

Abbreviation versus Symbol

Distinction often depends only on context. Whenever a choice exists between using an abbreviation or a symbol, MIL-STD-12 prefers use of the symbol. (See LOA.)

Example:

12 V dc (V is a symbol; dc is an abbreviation which describes the kind of potential).
not
12 Vdc (Vdc is an abbr.)

(NOTE: Always leave a space between a unit symbol and an abbreviation.)

Mathematical operations are performed only on symbols, not abbreviations.

EXAMPLE:

$$V = at = 5 \frac{\text{in}}{\text{s}} \times 2 \text{ s} = 12 \frac{\text{in}}{\text{s}}$$

Acronym - An acronym usually starts out as a specialized abbreviation but if it is used long enough, by a wide enough population, it eventually acquires the status of a word. Acronyms may be peculiar to one subject, field of knowledge, usage, or population, or they may acquire general usage - for example, radar (radio detection and ranging) specialized use, or snafu (situation normal - all fouled up) which could be used generally.

Acronyms are subject to word-usage rules - not abbreviation rules. However, be sure your user is familiar with the ones used. If there is doubt, spell each one out on first use and list it in the list of abbreviations or explain it in the glossary. As words, acronyms may be made plural, possessive, hyphenated or adjective use, or changed in tense.

Examples:

Several lasers . . .

. . . radar's range . . .

. . . MTBF-oriented procedures . . .

TYPES OF ABBREVIATIONS AND SYMBOLS

There are four categories of abbreviations and symbols considered in this style guide. It is necessary to categorize them in order to know how they need to be introduced to the user.

Category	Description	Rules of Introduction
1. Authorized, common	Those in MIL-STD-12 which are used so often their meaning is common knowledge.	May use without explanation or spelling out. (If there is any doubt about the reader understanding it, spell it out the first time used as shown below).
2. Authorized, unfamiliar	Those in MIL-STD-12 which are used infrequently and need to be explained to the user.	Explain/spell out the first time it is used in a manual, or if necessary the first time in each section of the manual. Example: This radio has agc (automatic gain control).
3. Special	Those not in MIL-STD-12 which are unique to the project/manual or Those which differ in spelling from MIL-STD-12. Abbreviations/symbols which may appear in any other style guide, list, or dictionary, but not in MIL-STD-12. Abbreviations/symbols which are panel nomenclature but which differ in spelling from MIL-STD-12. Commercial abbreviations which are different from MIL-STD-12.	Explain or spell out the first time it is used in the manual. List it in the list of special abbreviations and symbols* (LOA) in the manual.
4. Graphic	Symbols which appear in ANSI Y32.2 for use on illustrations and artwork.	Limit use to illustrations. Same rules apply as above, except substitute ANSI Y32.2 for MIL-STD-12.

*Special abbreviations and symbols may be combined in the same table (unless the list is very long and easier to use if abbreviations and symbols are separated.)

AUTHORIZED REFERENCES

The following documents may be used as the source of abbreviations and symbols. Any abbreviations or symbols not authorized by these documents, or spelled differently from the spelling in these documents, must be treated as special abbreviations.

MIL-STD-12 Abbreviations for Use on Drawings, Specifications, Standards, and in Technical Documents (Includes literary symbols).

MIL-STD-12 references the following:

MIL-STD-106 "Mathematical Signs and Symbols for Use in Physical Sciences and Technology"

ANSI Y10.3 "Letter symbols for Concepts in Mechanics of Solid Bodies"

ANSI Y10.5 "Letter Symbols for Quantities Used in Electrical Science and Engineering"

ANSI Y10.19 "Symbols for Units Used in Science and Technology"

Webster's *Third New International Dictionary, Unabridged* for chemical symbols.

ANSI Y32.2 "Graphic Symbols for Electrical and Electronic Diagrams."

General rules for abbreviations and symbols are also given in *U. S. Government Printing Office, Style Manual*.

WHEN NOT TO USE

Convenience:

Abbreviations or symbols should never be used for the convenience of the writer.

Be guided by the rule "When in doubt, spell it out."

Low-Skill-Level Readers:

Common abbreviations and symbols should be used with discretion, depending on the skill or education level of the user.

In general, the lower the skill level to which you are writing, the safer it is to avoid abbreviations and symbols, or explain them the first time they are used.

Typewriter Symbols:

Avoid common typewriter symbols to replace words except where necessary in charts or tables, where the symbol is part of panel or hardware nomenclature, or where it is helpful to the user. That includes:

% percent	' foot, feet
" ditto	" inch inches
∅ phase	/ per
& and	

If condensation of these words is necessary in text, use abbreviations instead of symbols (pct., ft., in., etc).

WHEN TO USE

Frequency of Use:

Keep use of abbreviations and symbols to a minimum.

Use only for benefit of user to:

- Save his reading time.
- Maintain status quo with familiar abbreviations he has always used, and may find confusing if spelled out.
- Ensure clarity where space is limited.
- Communicate mathematical ideas.

High-Skill-Level Readers:

If you are writing to pilots or experienced maintenance technicians, do not waste their time by spelling out or explaining common abbreviations or symbols. Such abbreviations as rf, ir, and ac, for example, have almost supplanted the spelled-out versions of these words and have acquired their own shades of meaning. However, if you have doubts as to how common an abbreviation may be, spell it out the first time. In tables and illustrations, abbreviations may be explained in a footnote.

Reader's Need for Special Abbreviations:

If the reader's need indicates a requirement for special abbreviations (not in MIL-STD-12) it may be necessary to obtain a contractual deviation to the manual specifications. Include any special abbreviations (LOA) in the technical manual.

HOW TO USE***Capitalizing Abbreviations (General)***

Capitalize abbreviations with the same capitalization you would use if the words were spelled out.

Examples:

Sealed fm circuits cannot be adjusted.

Dc voltage controls . . .

Adjust rc time constant . . .

Capitalizing Abbreviations (Titles)

In titles, capitalize abbreviations in accordance with what would be capitalized if spelled out.

Treat any normally lowercase abbreviation as a single word, and capitalize the first letter only.

Example:

Figure 11-3. +250 V Power Supply Ckt
8/7

HOW TO FORM SPECIAL ABBREVIATIONS

To form special abbreviations, use the letters from the word(s) being abbreviated. Make abbreviations as short as practicable; less than 80 percent of the spelled-out word(s). For example:

One word	Multiword	Compound word
Initial letter b - buoyancy d - deep	Initial letter of each word acb - air circuit breaker bc - between centers	Initial letter of each word egd - electrogasdynamics ls - loudspeaker
First portion galv - galvanize schem - schematic	First portion of each word raddef - radiological defense sonac - sonar nacelle	First portion of each element elhyd - electrohydraulic
First and last portion avn - aviation		
Omission of most vowels (some consonants) intcp - intercept wtrz - winterize		
Substitute letter (established by longstand- ing practice) xtal - crystal xmtr - transmitter		

HOW TO FORM SPECIAL SYMBOLS

Symbols should be selected from the specifications, including sources listed on page 7. Introducing new symbols may be done only if these sources prove lacking, and then only in accordance with established practice in the applicable field.

Abbreviations normally uppercased, are uppercased in titles.

Example:

CFE and GFE Units Required

For compound abbreviations (such as age, afc, rf) uppercase each letter unless the meaning requires lowercase.

Example:

AVC Test Points and Controls

Capitalizing Acronyms

When only the first letter of each word is used, use all capitals.

Examples:

APPR - Army package power reactor

STEP - supplemental training and employment program

MDC - maintenance dependencet chart

NOTE

Notice the spelled-out form does not need initial cap. even if the abbreviation has all capitals.

When more than the first letter of some words are used, use lowercase.

Examples:

loran - long-range navigation

sonar - sound navigation ranging

secant - separation control of aircraft by nonsynchronous techniques

When proper names are used on any word which uses more than first letter of any word, use initial cap.

Examples:

Pepco - Potomac Electric Power Co.

Inco - International Nickel Co.

Armco - Arabian-American Oil Co.

Capitalizing Quantity and Unit Symbols

Don't. Not in text; not in illustrations. Use as listed in MIL-STD-12. (MIL-STD-12 gives some unit symbols with a first letter capitalized -- honoring the person from whose name the unit was derived.) Lowercase symbols should remain lowercase even in applications where other lettering is uppercase.

Capitalizing on Illustrations

Generally illustrations are prepared with all uppercase letters. Abbreviations for use on illustrations are given in MIL-STD-12. However symbols lowercased in MIL-STD-12 must

remain lowercase. The reason for this is that sometimes an uppercase symbol has a different meaning than the lowercase one.

Changes or Revisions

When making changes or revisions to a manual, the specification allows the latest version in effect at the time of revision to be used. However, when this is different from the one in the unchanged parts of the manual, care must be taken that the user is not confused by two versions of the same abbreviation or symbol.

Circuit Reference Symbols

Uppercase circuit reference quantity symbols, such as C, R, L. For abbreviations of the related terms use:

c - capacitance
cap. - capacitor
res. - resistor/resistance
ind - inductor/inductance

In some multiple-letter abbreviations, letter symbols may be used lowercased:

lc - inductance-capacitance
rc - resistance-capacitance
lcr - inductance-capacitance-resistance

Examples:

Lcr design computations . . .
. . . rc time constants . . .

Clarity

Strive for clarity at all times.

Where the same abbreviation could have more than one meaning (cw - continuous wave; cw - clockwise) be sure that it is easily understood as intended. If there is any doubt, spell the words out in full, or if their use is frequent, form a special abbreviation which can be explained so as to leave no ambiguity.

Examples:

clockwise - cw (common)
continuous wave - cnw (special abbreviation)

Consistency in Use

Be consistent in using abbreviations and symbols. Do not indiscriminately mix abbreviations and spelled-out words in similar or parallel constructions. For example, don't abbreviate "inches" and spell out "feet" in similar applications.

Do not unnecessarily mix Greek and Roman symbols.

Establish standards for abbreviation and symbol usage on a manual or document. Be sure the list is kept current and distributed among all writers on that project.

Consistency in Panel Nomenclature

Panel nomenclature must be written exactly as it appears on the panel, even if it contains abbreviations or symbols not in accordance with MIL-STD-12 and NASI Y32.2. If not in MIL-STD-12 and ANSI Y32.2, treat it as a special abbreviation and spell out first time used.

Example:

Adjust amplitude of signal using SWP C&G (sweep centering and gain) control R19.

Precedence: Panel Nomenclature

If there is a conflict between abbreviations in panel nomenclature (or nomenclature on hardware) and the abbreviations in MIL-STD-12, the panel or hardware nomenclature abbreviation has precedence and may be used throughout the manual. For example, if panel nomenclature is GRD for ground (gnd, MIL-STD-12), you may use "grd" for ground throughout the manual. In that case, list "grd" as a special abbreviation in the list of special abbreviations.

Diagonal (/) (Also called solidus, slash, slant, or virgule.)

May be used as needed with symbols to substitute for "per" or "divided by."

Example:

in/sec - inches per second
m³/day - cubic meters per day

Diagonal may also:

- a. Separate alternatives.

Example:

... design for high-speed/high-heat application ...

- b. Separate successive divisions (as months or years) of an extended period of time.

Example:

... changes covering 1974/75 ...

Ditto Marks ("")

Not authorized. Avoid them. Most often if you find yourself repeating information frequently enough to be tempted to use them, it is a sign of poorly organized data. Reorganize.

Example:

Bad (Repeated Data) Output	Good Output (v)
15 V	15
17 V	17
19 V	19
22 V	21
...	...

Greek-Letter Symbols

Avoid using Greek capital-letter symbols which are easily confused with English letters. (A, B, E, Z, H, K, M, N, O, P, T, and X.)

A	α	alpha	Ν	ν	nu
B	β	beta	Ξ	ξ	xi
Γ	γ	gamma	Ο	ο	omicron
Δ	δ	delta	Π	π	pi
Ε	ε	epsilon	Ρ	ρ	rho
Ζ	ζ	zeta	Σ	σ	sigma
Η	η	eta	Τ	τ	tau
Θ	θ	theta	Υ	υ	upsilon
Ι	ι	iota	Φ	φ	phi
Κ	κ	kappa	Χ	χ	chi
Λ	λ	lambda	Ψ	ψ	psi
Μ	μ	mu	Ω	ω	omega

Graphic Symbols

Select for illustrations from ANSI Y32.2. If a required graphic symbol is not in ANSI Y32.2, list that symbol in a list of special graphic symbols.

NOTE

Remember that the use of symbols from ANSI Y32.2 is restricted to illustrations or artwork - not accompanying text.

(Self-adhesive preprints of graphic symbols may be used on illustrations in accordance with the same restrictions as for hand-drawn symbols.)

Hyphenation

Do not hyphenate abbreviations when using two or more abbreviations as a compound modifier.

Examples:

rf variation not r-f variation

dc voltage not d-c voltage

Illustrations Using Abbreviations or Symbols

All the rules for using abbreviations or symbols apply to illustrations as well as text, except in illustrations space is at a premium and more abbreviations or symbols may be required. However, the fact that an abbreviation or symbol has been used on an illustration is no reason for using an abbreviation or symbol in text where space is not a consideration.

MIL-STD-12 gives abbreviations all uppercase for use on illustrations.

In most cases the uppercase and lowercase abbreviations are the same, but not always.

Use symbols as given in MIL-STD-12, uppercase or lowercase. Even in illustrations which have all other letters uppercase, symbols which are lowercase in the specification must remain lowercase. Changing a lowercase symbol to uppercase may change its customary accepted meaning.

Italics

MIL-STD-12 (ANSI Y10.5) requires that symbols for physical quantities (such as F - force, Q - electrical charge, I - electrical current) be written in italics. Since most typewriters do not have this capability, underlining may be substituted. However, confusion may result. Therefore, it is recommended that abbreviations of physical quantities be avoided as much as possible by spelling out.

Number

Use "no." as the abbreviation for "number." Use a period to avoid confusion with "no" (the negative). However, check your detail specifications in case another requirement exists.

Parenthetical References

When you can't avoid cross-referencing, abbreviate short references in parentheses.

Examples:

... (fig. 3-21) ...
... (para 4-230) ...

Spell out references which are part of a sentence but not in parentheses.

Examples:

... action described in figure 3-21 ...
... description in paragraph 4-230 ...

Periods

Do not use a period after an abbreviation unless:

- a. The abbreviation spells some other English word.
- b. The abbreviation is the last word in a sentence.
- c. It may be confusing to the reader without a period.

Examples:

No periods	Periods helpful
sync	ant. cap.
xmtr	coax.
para	in.
cm	pot.
etc	sect.
	fig.
	am.

Exceptions:

- When abbreviations are used as symbols in mathematical expressions, omit all periods.

Examples:

cot (cotangent)
sin (sine)
tan (tangent)

- In pairs, or sets of words, use periods for consistency.

Examples:

long. (longitude)
lat. (latitude)

Suggestion:

Avoid sentences that end with an abbreviation that needs a period because it spells another word. When that happens, rewrite the sentence or spell out the abbreviation. For example, "Check the if." could cause confusion. Better: "Check the if. before . . .", or "check the intermediate frequency."

Plurals

Generally, use an abbreviation in one form only; do not make it plural.

Examples:**Singular**

1 in.
0.5 g (gram)
part no. 199820-100

Plural

25 in.
15 g (gram)
part no. 199820-100, 199820-110,
and 199820-120

Exceptions:

- Where space is a problem on a chart or a table, it is permissible to pluralize an abbreviation if it makes the meaning clearer to the user. For example: "remove xtals" or "check rcvr test tgts."
- Some detail specifications require that a plural abbreviation, such as Nos., be used in certain applications. Others require lowercase (no. or nos.). Before using these variations make certain it is actually required.

Possessives

Do not make an abbreviation possessive. Use the same basic form of the abbreviation; the user can supply the possessive case mentally if necessary.

Prefixes for Unit Symbols

The symbols for unit prefixes are included in the MIL-STD-12

NOTE

Do not compound prefixes, such as millimicro or megomega; it may cause confusion. Use one prefix only denoting the highest order of magnitude.

Abbreviate the prefix "micro" by using the letter "u" (U in illustrations). MIL-STD-12 authorizes the Greek letter μ , but this symbol is seldom provided on typewriters. It could be supplied by rub-ons from artist's aid sheets, or hand-drawn, but it is best to avoid it by spelling out "micro."

<u>Prefix</u>	<u>Multiple</u>	<u>Symbol for Prefix</u>
tera	10^{12}	T
giga	10^9	G
mega	10^6	M
kilo	10^3	k
hecto	10^2	h
deka	10^1	da
deci	10^{-1}	d
centi	10^{-2}	c
milli	10^{-3}	m
micro	10^{-6}	μ
nano	10^{-9}	n
pico	10^{-12}	p
femto	10^{-15}	f
atto	10^{-18}	a

Redundancies

Avoid unintended redundancies when using abbreviations. Remember the word for which the abbreviation or symbol stands and avoid it directly.

Example, avoid:

if. frequency
ac current

use:
if.
ac

Exception:

Combinations, in which another modifier separates the abbreviation from its redundancy are permissible, such as:

dc plate current
ac heating current

Avoid repeating "dc" when a polarity (+ or -) is given with the numeral; or "ac" if the frequency is given. Only when the polarity is irrelevant, or the supply frequency is irrelevant, use "V dc" or "V ac."

Avoid	Use
+28 V dc	+28 V

Spacing

Space abbreviations as shown in MIL-STD-12. Leave a space before and after the abbreviation and other text.

Leave a space between a number and the abbreviation of the unit of measurement which follows:

Examples:

+28 V
25.5 ft
3 g

Leave a space before and after a symbol denoting arithmetic operation.

Example:

5 + 6 = 11

When combining a unit symbol with an abbreviation, leave a space between them.

Examples:

17° E (17 degrees east)
 8 cm w (8 centimeters wide)
 14 V dc

Exception:

In mathematical expressions, close the space between g (gravity) and the preceding number (2.5g). In text treat g as an abbreviation and leave space (4.5 g).

Temperature Symbol

The degree symbol may be used together with the designated temperature scale. The degree symbol and the letter for the scale should not be separated, but written together as, for example °C or °F.

NOTES

- The Centigrade temperature scale has been superseded by the Celsius scale; Centigrade is no longer used.
- The degree symbol has been deleted from the Kelvin scale; K stands for degree(s) Kelvin.

Thru/Through

Use "thru" when referring to any series such as serial-number effectivities, page numbers, dates, or consecutive items of any kind.

Example:

. . . . units 19 thru 28 require . . .

For all other applications use "through."

Example:

Pull cable through opening A . . .

Typewritten or Preprinted Symbols

If a manual is prepared on a machine which cannot produce a symbol, such as a Greek letter or +, the symbol may be spelled out - as "porm" for "plus or minus."

Such usage must be explained the first time it is used in the manual and must be explained as applicable in the manual's foreword, preface, glossary, introduction, or section on how-to-use the manual; and listed in the list of special abbreviations and symbols.

NOTE

Self-adhesive preprints, if used, must be carefully edited to ensure accuracy and completeness.

Verb Tense

When a verb is abbreviated, use the same abbreviation for all tenses.

Examples:

insp - were inspected
insp - are inspected
insp - will be inspected

NOTE

The above rules of syntax apply to abbreviations and to symbols. They do not apply to acronyms, which are inflected in the same way as word.

Examples:

NSIA's programs . . . (possessive)
. . . applies to all radars.

Section 9

CAPITALIZATION

Page	Page		
Why and When Capitals?	2	Proper Nouns	5
Capitalization Policy	2	References to Publications	5
Minimize Use of Capitals	2	Table of Contents	5
Reasons for Minimizing	2	First Word Cap.	5
Authority for Capitalizing	2	Lists, Tables, and Charts	5
Capitalizing Abbreviations and Symbols	2	Sentence or Statement	5
Modes of Capitalizing	3	No Cap	5
All Cap	3	Letters	6
Computer Output (Direct Pickup)	3	Hardwasre Nomenclature	6
Illustrations	3	Informally Used Titles	6
Headings	3	Referencing Informally	6
Panel Nomenclature	4	Signal Nomenclature	6
Table Titles	4	Special Capitalization Rules	6
Initial Cap	4	Copyright Trade Names	6
Acronyms or Coined words	4	Government (The Word)	6
Captions	4	Mach.	7
Column Headings in Tables or Charts	4	Terms	7
Hyphenated Compounds in Titles	4	Revision or Change Data	7
Formal Nomenclature	4	Type Styles	7
Formal Titles	5	Single-Letter-Compound Nouns	7
Lists of Illustrations and Tables	5	Quick-Reference Capitalizaiton Guide .	8

All rules for uppercasing or lowercasing in a manual must be in accordance with the specifications to which the manual is being prepared. Specification requirements vary widely. For example, some require that each figure have a formal number and a title that uses initial caps on each word centered under the illustration, while other specifications permit a lowercase title to be placed on any part of the illustration or no figure title at all. Capitalization is merely a means to an end; any style is acceptable as long as it is:

Used consistently.

Nondistracting.

Helpful to the user.

Prepared in accordance with applicable contractual specification requirements.

The rules given in this section are based on the *U. S. Government Printing Office Style Guide* and on standard English usage.

WHY AND WHEN CAPITALS?

- Headings.
- The beginning of a statement. (Standard English usage.)
- Distinguishing one particular object from the general class of similar objects (formal identification).
- Avoiding confusion.
- Specification requirements.
- Emphasis.
- Showing respect, when a word is derived from an individual's name.
- On illustrations when equipment for lowercasing is not available.
- Computer output when lowercase printer is not available.

CAPITALIZATION POLICY

Minimize Use of capitals.

Some publishing organizations use capitals liberally whenever a choice of uppercase or lowercase exists. This style guide recommends the opposite: given a choice, lowercase. The policy is called capitalizing down.

A good rule to remember is: if there is not a good reason to capitalize, don't. Personal preference is usually not a good reason because it results in inconsistencies.

Reasons for minimizing use of capitals

- a. Government specifications require uppercase for defined special purposes; its unrestricted use for other purposes weakens the impact of the required ones.
- b. Emphasis is obtained visually by using contrast. If excessive capitalizing is used, the contrast, and hence the purpose of the capitals, is lost.
- c. Lowercase text, particularly if lengthy, results in easier, faster reading.

AUTHORITY FOR CAPITALIZING

Use the *U. S. Government Printing Office Style Manual* as a general guide for capitalizing.

CAPITALIZING ABBREVIATIONS AND SYMBOLS

Capitalize abbreviations in accordance with the same rules that would apply if the words were spelled out.

Exception:

Some abbreviations are always uppercased in MIL-STD-12.

Never capitalize lowercase symbols! (Capitalizing may change their meaning.)

MODES OF CAPITALIZING

1. All Cap - EVERY LETTER OF EVERY WORD

a. Computer output (direct pickup)

When computer output, or other automatically mechanized printed output, is available for direct pickup (photographically) in such formats as equipment lists, wiring lists, signal flow data, all uppercase letters may be used if lowercase printing equipment is not available. When lowercase capability exists, applicable rules for capitalizing should be observed.

b. Illustrations

- All text on illustrations may be all cap. if lowercase typing capability is not available.
- All abbreviations on illustrations as shown in column 1 of MIL-STD-12.

EXCEPTION: If ALL-CAP text contains a lowercase symbol, do not uppercase the symbol; it may change the meaning.

c. Headings

- Capitalize as required by specifications.
- Unless otherwise called out by specifications, one recommended style for capitalizing headings is shown below:

A _____	PART ONE
AUXILIARY EQUIPMENT	
B _____	CHAPTER 3
OPERATING INSTRUCTIONS	
Section I. OPERATING CONTROLS	

PRIMARY HEADING

Stand-Alone Heading
Run-in Heading.

a. First-Level Subparagraphs.

(1) **Second-Level Subparagraphs.**

(a) **Third-Level Subparagraphs.**

Use all cap on such manual headings as:

Chapter (B)	Preface	Glossary
Part (A)	Table of Contents	Index
Foreword	List of Tables	Appendixes
	List of Illustrations	

- d. Panel Nomenclature
Capitalize control, indicator, and test point nomenclature as shown on the equipment (usually panel nomenclature is all cap).
- e. Table Titles
At top of table - use all cap.
At bottom of table - use initial cap.

2. Initial cap - First letter of each important word.

*The following words in headings or titles are not important unless:
they are part of panel nomenclature
they are the first word of a title

articles - a, an the,
short prepositions- at, by, down, for, in, of, on, up, to (unless it is part of an infinitive - e.g.,
Orders To Stand By)
conjunctions - and, as, but, if, or, nor

- a. Acronyms or coined words
Initial - cap proper names in shortened form, when the shortened form contains more than the first letter of any word.

Example: Pepco (Potomac Electric Power Company)

- b. Captions
Initial-cap captions or titles of illustrations and tables except when the table title is on top.

Example:

Figure 2-1. Functional Description of the Radar Set

- c. Column Headings in tables or charts
Initial-cap all important words.
- d. Hyphenated Compounds in Titles
Initial-cap all important words.
Example:
Description of Pulse - Forming Circuits
- e. Formal nomenclature
Initial-cap items with specific part or identification number when written in the order below (former nomenclature order).
Test Set TS-23/U
Fire Control System MD-4

but, lowercase the following:

- ... the TS-23/U signal generator
- ... MD-4 fire control system

f. Formal titles

Initial-cap formal titles of people.

Examples:

- The matter was referred to General Miles.
- ... direct your answer to C. P. Adams, Project Manager.

g. Lists of illustrations and tables

Initial-cap all titles included in these lists (i.e., titles of figures, illustrations, diagrams, and tables).

h. Proper nouns

Initial-cap each word in multinoun names.

Examples:

- United States Army
- U. S. Armed Forces (but armed forces when used in the general sense)

i. References to publications

For user convenience, avoid referencing whenever possible.

When referencing is necessary, capitalize as follows:

- Formal Title - Initial-cap.

Example:

Handbook of Service Instructions for Fire Control System MG-24.

- Informal title - Lowercase

Example:

... the handbook of service instructions for the MG-24 fire control system.

j. Table of Contents

Initial-cap titles or headings of paragraphs.

3. First Word Cap - First letter of first word only.

a. Lists, Tables, and Charts

Uppercase the first letter of the first word in:

- Each entry in a legend, table or chart
- Each entry in a tool or equipment list, whether with or without part numbers
- Each item of list format

Example:

- The operations include:
 - Mounting the frame under the chassis
 - Aligning the lens after disassembly

b. Sentence or Statement

Uppercase the first letter of the first word of each new sentence (or statement having the effect of a sentence), whether in text, keyed text, or tabular format.

NO CAP - ALL LOWERCASE

Lowercase the following unless required otherwise by specifications or for consistency or some special reason:

- a. Letters that designate the following:
- Steps or substeps of a procedure or items in a list
 - Parts of an illustration (a, b, etc). Also references to these parts.
 - Axes on a graph (designated by x, y, and z)
 - Terminals (designated by x, y, and z) unless such letters are part of panel nomenclature

- b. Hardware nomenclature
When no panel nomenclature exists, lowercase controls, indicators, and test points, even though they are uppercased on diagrams or illustrations.

- c. Informally Used Titles
Lowercase titles without a specific name.

Examples:

commanding officer section head project director chairperson

- d. Referencing Informally
- Lowercase names of systems, units, components, tools, fixtures, or test equipment written without a part number, or written in non-formal* order.

Examples:

... the E-3 fire control system (non-formal order)

... the connecting cable

*In formal order, all items which have panel nomenclature must be written exactly as shown on the nameplate.

- Avoid cross-references to other parts of the manual whenever possible, but if unavoidable, use lowercase:

Examples:

paragraph 4-12

page 6-3

- e. Signal Nomenclature
Lowercase in text, even when uppercased on illustrations or diagrams.

SPECIAL CAPITALIZATION RULES

1. Copyright Trade Names

If their use cannot be avoided by using the equivalent standard item name, capitalize names like Xerox, Kodak, Teflon.

2. Government

Capitalize the word government when referring to the U. S. Government.

Example:

... Government - furnished equipment (GFE)

3. Mach

Lowercase mach (for speed of sound) although derived from a person's name.

4. Terms

Unless followed by an identifying number, lowercase such terms as:

contractor - furnished equipment
engineering order
instrument landing system

publication number
technical order (TO)
ground controlled approach

If followed by a specific number, use initial caps.

5. Revision or Change Data

Unless the applicable specification calls for lowercase letters, capitalize letters designating information added by changes or revisions. For example, three pages added between pages 8 and 9 are designated as pages 8A, 8B, and 8C.

Omit capital letters I and O when they may be confused with numbers.

6. Type Styles

Lowercase when referring to type styles (e.g., roman*, italics).
*but Roman numerals.

7. Single-Letter Compound Nouns

Capitalize the single letter in such nouns as:

I-beam X-ray Y-axis

QUICK-REFERENCE CAP GUIDE

QUICK-REFERENCE CAPITALIZATION GUIDE

Topic	General Rule	Page Ref.
Abbreviations	Cap. same as if words were spelled out.	9*/11, 10/2
Column headings	Initial-cap important words.	4**
Controls, indicators, test points	As shown on equipment. If no panel marking, use lower case.	3.6
Copyright product names	Initial-cap only.	4.7
Divisions of a manual	All-cap, except when referencing; then use lowercase.	3.6
Hyphenated words in titles	Initial-cap important words.	4
Illustrations vs text	Using all cap. on illustrations is not authority for cap. in text.	3.6
Lowercase symbols	Never cap.	2
Unimportant words in titles (usually)	Lowercase.	2
Proper nouns/names	Initial-cap.	4
References —		
Informal, not specifically identified	Lowercase.	6
Not in nameplate order	Lowercase.	6
Formal, specific	Initial-cap.	4
Cross-referencing in manual	Lowercase.	6
Signal names	Lowercase	6
Table of contents —		
Titles of sections	All-cap.	3
Headings of paragraphs	Initial-cap.	4
Titles of tables —		
On top	All-cap	3
On bottom	Initial-cap	3

*The first digit of a double-digit number identifies another section.

**Single-digit numbers refer to pages in this section.

Section 10

Compound Words

	Page		Page
Definition	1	Types of Compounds	3
Authority	1	Solid Compounds	3
Compounding	1	Hyphenated Compounds	4
Symbol or Word Stress	1	Separate Words	5
Factors in Compounding	2		

DEFINITION

Compound: A word composed of two or more words joined with a hyphen or written in solid form (wavelength, pulse-width).

A word consisting of various combinations of words, combining forms, or affixes (as Kilohm, subunit, supersearch).

AUTHORITY

Use the *U. S. Government Printing Office Style Manual* as a general guide for compound word forms.

COMPOUNDING

The rules for compounding are not static and are full of exceptions. Word forms constantly undergo modification. For example, two-word forms often have hyphens at first; then, with frequent usage, the hyphen is dropped and the two words become one word. Often the transition is from two-word to one-word form, bypassing the hyphen stage.

Correct current usage for individual compounds is shown in the list of compounds at the end of this section. The authorized *GPO Style Guide* contains a longer list which you should check when necessary to determine a correct form. For each compound used, be sure you are in accord with the following usability rules:

- a. Make certain reader does not have to back up and read the compound several times before comprehending it.
- b. Be consistent throughout manual.

Syllable or word stress

The compound form can often be determined by where the stress falls when the sentence is read aloud. Usually when the stress falls on the first word, or first syllable of the compound as it precedes the word it modifies, the words are either hyphenated or solid. On the other hand, when the stress falls on the last word or syllable, all words are written without hyphens as separate words (open).

Examples:

Hyphenated or Solid	Open
We are using up-to-date equipment. Time-of-flight information will determine the program Setup of the equipment was completed. Perform lockon.	Our equipment is up to date. Information was delayed regarding the time of flight. The equipment was set up. Review the procedure so you can lock on to target.

Factors which contribute to hyphenation/compounding rules are:

- Relative familiarity**
- Syllable stress (in reading)**
- Exact connotation**
- Word form (noun, adjective, verb)**
- Special cases**

Example:	-
crossband	- solid
cross section	- open, to prevent tripple "s"
antiaircraft	- solid
anti-British	- hyphenated to retain capital "B"
preamplifier	- solid
Pre-position	- hyphenated, to avoid confusion with "preposition" (a part of speech)
electroscope	- solid
electro-optics	- hyphenated to avoid first reading of "oo" sound
rust resistant	- open The compound is rust resistant.
rust-resistant	- hyphenated as adjective. A rust-resistant compound . . .

TYPES OF COMPOUNDS

Solid Compounds

1. A word root used with a prefix, combining form, or suffix such as:

anti
co

de
in

pre
re

Examples

antijam
coordinate
counterclockwise

deenergize
microinch
preamplifier

readjust
reinstall
wavelike

Exceptions:

pre-World War II
un-American

re-creation
un-ionized

and many others, based on:

clarity
usage
intended meaning
emphasis

2. Two short nouns joined together to make another noun.

Examples:

airship
cleanroom
darkroom

motorboat
pinhole
workweek

3. A noun made up of a short verb and an adverb.

Examples:

breakdown
countdown
lockon

lockout
mockup
throwaway

NOTE: When compounds like these are not used as nouns, they are open (separate words).

Examples:

Rotate . . . to lock on to target.
. . . will cause insulation to break down.

Exceptions:

cut-in
run-in
tie-in

Hyphenated Compounds

1. Word with duplicate prefix.

Examples:

counter-countermeasures
sub-subgroup
north-northeast

2. Word prefixed by:

Examples

ex	ex-employee
self	self-test
quasi	quasi-particle

3. Two-word fraction or number.

Examples:

thirty-two
one-half

4. Word with single-letter modifier (preceding noun or participle).

Examples:

x-ray
y-axis
l-shaped

5. Modifying phrases or words which precede the word they modify.

- Present/past participle combined with another word.

Examples:

rust-resistant coating
air-conditioned room
fire-tested materials

- Unit modifier (combination of adjectives and nouns which together modify a noun.)

Examples:

high-frequency-test results
alternating-current output
5-second delay
long-life-cycle system

NOTE: When two or more numerical values modify the same unit of measurement, use a hyphen and a space after each number which is remote from the unit. For example:

1. Attach several 3-, 5-, and 6-inch strips.
2. Use only 5- and 10-watt resistors.

- Prepositional phrase, improvised to suit the specific situation.

Examples:

line-of-sight calculations
trial-and-error approach

6. Coordinate forms (equal rank).

Examples:

left-right	receiver-transmitter
east-west	input-output
undervoltage- overvoltage	

7. Compound verb.

Examples:

field-test	die-cast
arc-weld	air-cool
hand-carry	self-test

Separate Words (When to use)

- a. Words appear in normal sequence and meaning is clear.

Examples:

digital computer signal
fire control system
oscillator frequency adjustment

- b. First word is an adverb ending in "ly."

Example:

carefully arranged program
closely observed target

- c. First word of two-word modifier is a comparative or superlative.

Examples:

higher level decision
better calibrated meter
greatest measured value

- d. First two words of three-word modifier are adverbs.

Examples

very well defined area
longer than usual extension
not too distinct noise

- e. Compounds are composed of signal/unit nomenclature.

Examples:

time transfer signal
store modified status voltage
high voltage supply unit

- f. Modifying words are independent.

Examples:

top round indicator
long extended lever
green cylindrical tube

- g. Foreign phrases are used.

Examples:

per diem employee
ex officio member

- h. Second element of modifier is a number or letter.

Examples:

class II changes
appendix C pages
point 4 program

- i. Chemical, scientific, technical terms are used.

Examples:

carbon monoxide poisoning
methyl bromide solution
photoconductive detector equipment

antireflection coating materials
optical filter wavelength

- j. Confusion could result from use of hyphen, as when a numerical value of compound is preceded by +, - or \pm .

Examples:

+28 volt power source (*not* +28-volt power source)

+8° C temperature setting (*not* +8-° C temperature setting)

Section 11

MATHEMATICS

Objective	1	Equations	3
Problems	1	Spacing	4
Mechanics	1	Italics	5
Style Rules	2		

OBJECTIVE

Coverage of mathematical style is primarily directed against the ever-present risk of error in transcribing complex symbolical data from one document, or style, to another.

Formation of numbers and symbols, arrangement and spacing, placement of subscripts and superscripts, and all other details must be foolproof.

PROBLEMS

Errors in printed copy are often due to the unclear or inconsistent style practices of the rough-draft writer, or the failure of the writer to proofread such copy at every stage of transcription.

MECHANICS

1. Make every detail of each mathematical symbol or expression unmistakably clear, regardless of how well the symbol or expression may be known in engineering. The item will be taken literally as you write it by the typist, and printer.
2. Supplement your original draft with oral or written instructions, as necessary, to take care of all foreseeable problems.
3. Hold the use of mathematical expressions to a minimum controlled by the real needs of your reader. Never use a mathematical expression, except of the most elementary type, if simple English words can be used as a good substitute.
4. Don't use mathematics in technical manuals as a form of shorthand aimed only at the convenience of the writer; direct necessary mathematical treatments toward making data clearer to the reader.
5. Generally write mathematical expression by hand; this method gives you better control over style, aymbology, and typography.

If an expression is to be written by you in a space left open in the typed draft, make this fact clear to the typist in each instance. Indicate the amount of horizontal and vertical space you will require (inches or typewriter spaces).

6. Avoid use of uppercase letter when it is your intention that lowercase be used in the final copy.

STYLE RULES

1. Make certain that all expressions that are included in a single line are free from ambiguity. Use parentheses where necessary.

EXAMPLES:

Ambiguous: . . . channel output signal $gt/V \sin L$ is applied . . .

Clear: . . . channel output signal $(gt/V) \sin L$ is applied . . .

Clear: . . . channel output signal $gt \sin L$. . .



2. Don't try to crowd complex or hard-to-read expressions into single lines of type. Increase the line spacing to accommodate a horizontal-line division indication, as in the third example above.

NOTE

Generally prefer the style in which the horizontal division line is fully extended, so as to make $gt \sin L$ read $gt \sin L$, except where an item such as gt has a significance that requires its retention in the separated form.

V V V

3. Center and indent any complex or hard-to-read expression in a clear space between the lines of text. If a series of such expressions is to be written, start them at the typed-area margin or indent them in any consistent manner. Center and indent any important expression, regardless of complexity, to introduce or emphasize it.

EXAMPLE:

The value of the cutoff wavelength λ_c is

$$\lambda_c = \left(\frac{90^\circ}{\theta_1 + \theta_2} \right) \lambda_{co}$$

where $\lambda_{co} = 2a$ cutoff wavelength without ridges and satisfy the approximate equation

$$\cot \theta_2 + (b_1/b_2) \cot \theta_1 = 0.$$

4. Punctuate mathematical equations in much the same manner as text, but don't use the customary commas to set off nonrestrictive expressions placed in a cleared space between line of text.

EXAMPLE:

Figure 8-12 shows that the described condition

$$E_c + \frac{E_b}{\mu} = 0$$

exists when the grid of V35 is just sufficiently negative to neutralize the attracting power of the plate at the cathode.

(The commas that would be required in an equivalent "nonrestrictive" situation in text are omitted)

5. Use terminal periods after expressions at the end of sentences, except when the terminal arrangement of the expression is such that use of a period would be meaningless or confusing to the reader.

EXAMPLE:

The equivalent circuit (fig. 4-23) shows that

$$\left. \begin{array}{l} \text{Amplification in middle} \\ \text{range of frequencies} \end{array} \right\} \frac{e_o}{e_s} = \mu n.$$

6. Don't introduce an expression with a colon (:), unless the words "as follows", "the following," or the like are also used.

EXAMPLE:

The impedance formed by the reactance in series with resistor R7 is

$$Z = \sqrt{R^2 + (\omega L - \frac{1}{\omega C})^2}$$

(The terminal period is omitted for clarity.)

7. Avoid use of the slant bar in writing any but the simplest mathematical expressions, particularly in a typeset book.

EQUATIONS

1. When a long expression must be carried over to a succeeding line, divide the expression at one of the following points:

Set the first portion of the equation flush with the left margin of the allotted area and the second portion flush with the right margin of that area.

- Just before an equals sign (=) in an equation.
- Just before a plus (+) or minus (-) sign separating elements of comparable rank.
- Just before a multiplication sign (x). Use this type of multiplication indication whenever line interruption is necessary at a multiplication point.

EXAMPLES:

$$\begin{aligned} 15r + 8r - 11r + 20r(r-1) + 23r^2 \\ = 20r(r + 14r(r^2 + r^2)) \end{aligned}$$

... in this circuit the plate current is given by the equation

$$I_p = a_1 \left(E_g + \frac{E_p}{\mu} \right) + a_2 \left(E_g + \frac{E_p}{\mu} \right)^2 + a_3 \left(E_g + \frac{E_p}{\mu} \right)^3$$

2. 2. In a series of equations, align the major equals signs.

EXAMPLE:

Solution: Since $P = EI$

the line current is $I = \frac{P_L}{E_L} = \frac{21,400}{230} = 93.0 \text{ amp}$

and the field current is $I_f = \frac{E_L}{\mu} = \frac{230}{100} = 2.3 \text{ amp}$.

3. Make any enclosing symbol, such as parentheses () or braces { }, just wide enough to align with the highest and lowest points of the matter enclosed.

Similarly, make any dividing or covering element, such as the horizontal division symbol (_____) or the top of the radical sign $\sqrt{\quad}$, must wide enough to align with the right and left outer edges of the matter divided or covered.

EXAMPLES:

The input impedance is determined by

$$Z_i = Z_1 \left[m(1-m) \frac{(K-1)^2}{K} + 1 \right]$$

The frequency of peak attenuation, f_p , is

$$f_p = \frac{1}{2\pi} \sqrt{\frac{f_0^2}{1-m^2}} = \frac{(18 \times 10^3)}{1-(0.6)^2} = 18.75 \text{ MHz}$$

4. Use parentheses, brackets, and braces in the following order to set off parts of an equation:

$$\{ [()] \}$$

SPACING

Leave one space before and after:

The symbols +, -, x (times), /, =.

Trigonometric-function abbreviations (sin, cos, tan, etc).

Fractions not directly enclosed by parentheses or brackets.

Omit space between:

A trigonometric-function abbreviation and an exponent (sin², cos³).

Symbols +, -, × and number indicating at polarized value or a tolerance (+ V, 120+3 V ac).

Omit space before:

punctuation marks exponents
subscripts reciprocals
superscripts

(a² F³, D')

ITALICS

Use italics

Letters used as mathematical symbols in typeset mathematical expressions.

Don't use italics

Circuit reference symbols (R, C, ...) used to designate specific electrical parts.

Letters used to spell:

words
abbreviations
units of measurement

Arabic numerals

Operation symbols

+, -, [], ()
(Don't slant these.)

Section 12

NUMERALS

	Page		Page
Spell Out Numerical Quantities	1	Hyphen	3
Use Numerals	3	Slant Line	4
Don't Repeat Spelled-out		Zero	4
Number as a Numeral	3		

NOTE

See the *Writing Handbook* for information on Measurements and Tolerances.

SPELL OUT NUMERICAL QUANTITIES

Spell out numerical quantities under the following circumstances:

- a. Numbers under 10 in text matter unless they are:
- Followed by a unit of measurement, time, or quantity
 - Used in series with other items expressed as numerals.

NOTE

Rule includes ordinal numbers - first, second, etc.

EXAMPLES

The unit contains four missiles.

The seventh stage is not biased.

The unit contains 4 missiles and 11 rockets.

Timing is controlled by the 11th and 12th relay stages.

Each Missile is 4 feet 1 inch long.

- b. A number that must appear at the beginning of a sentence or heading. It is preferable to rephrase the sentence/heading.

EXAMPLES:

Wrong: 19 units were shipped.

Better: Nineteen units were shipped.

Rephrased: The factory shipped 19 units.

- c. A number of less than 100 immediately preceding another number.

EXAMPLES:

The order consisted of nineteen 8-pound units.

But

The order consisted of 119 8-pound units.

- d. A number in an indefinite expression.

EXAMPLES:

... a thousand and one possible trouble symptoms ...

... the systems to be produced in the early sixties ...

NOTE

Use of the words nearly, about, around, approximately, etc. doesn't make an expression "indefinite" in the sense referred to above. Write "approximately 8 inches," not "approximately eight inches."

- e. A fraction that stands alone in a sentence or is followed by "of a," "of the," etc.

EXAMPLES:

Installation took one-fourth of the allowed time; alignment, three-fourths.

The adjustment group did three-fourths of the work within 8 hours.

Only one-fourth of an inch now remains of the material.

- f. Round numbers (hundred, thousand, million, etc), unless they

- They are used in a series which includes precise numbers.
- They precede a unit of:

Measurement

Time

Quantity

- The spelled-out form is clearer.

EXAMPLES:

... a hundred missiles ...

... 100 missiles and 42 interceptors ...

... 100 feet, 100 years, 42 percent ...

... one trillion dollars ...

... 15 trillion dollars (or \$15 trillion) ...

USE NUMERALS for the following:

a. Any numerical expression of 10 or more (except as indicated above).

b. Expressing units of:

Measurement

Time

Quantity

regardless of magnitude.

EXAMPLES:

9 inches

1 year

55 quarts

c. Phase rating of power source - except for the expression "single-phase" power.

EXAMPLE:

The system provides 3-phase power.

DON'T REPEAT spelled-out number as a numeral.

Except for required use in a legal or quasi-legal document, don't repeat a spelled-out number as a numeral. (A Government regulation may require such a dual listing of numbers in specific instances.)

EXAMPLES:

Wrong: The launcher has four (4) missiles installed.

Right: The launcher has four missiles installed.

HYPHEN

To indicate a range of numbers occurring in condensed data, use a hyphen between the limit numbers. (The hyphen then means "thru.") If ambiguity is possible, spell out "thru."

EXAMPLES:

1-4 feet
pages 264-381
the 1950-1960 period

2. Omit the hyphen in unit modifiers in which the numerical value of the compound is preceded by +, -, or \times .

EXAMPLES:

the +28 volt power supply

But

the 28-volt dc and 29-volt ac power sources.

3. Omit hyphens with abbreviations or symbols.

EXAMPLES:

the 28V power supply

the 28 V dc and 29 V ac power sources

SLANT LINE

To indicate in a concise manner that either one number or another applies, use a slant line between the numbers. If required for clarity, explain this usage the first time it appears in a given application. Be careful the slant line cannot be interpreted as "per" or "divided by."

EXAMPLES:

GAR-1/2 missiles (meaning either GAR-1 or GAR-2 missiles)

ZERO

Use a zero before the decimal point for any decimal number less than one; treat such a number as singular grammatically.

EXAMPLES:

0.15 inch or 9.9547 centimeter
But 1.0001 inches

Section 13

CROSS-REFERENCING

	Page		Page
Scope.....	1	Parenthetic, Short Cross-reference .	3
Policy.....	1	Parenthetic, Long, Cross-reference .	4
Methods for Minimizing Cross-Referencing	1	Non-Parenthetic Cross-reference ...	4
Accuracy.....	2	With Tables and Charts	4
Cross-referencing Mechanics	2	With Illustrations Using Figure Numbers	5
Same Manual/Another volume		In Headings	6
of Same Manual	2	Underlining	6
Other Documents.....	3	Placement of Cross-references	7
Style.....	3	Repetition of Complete Cross-reference	7

SCOPE

Cross-referencing pertains to directing the reader from one place in a manual to another as follows:

- a. To pertinent information in another place in the same manual. This includes from text to illustration/tables and vice versa.
- b. To other volumes of the same manual.
- c. To other publications.

POLICY

Cross-referencing should be kept to the minimum because it makes a manual difficult and time-consuming to use.

METHODS FOR MINIMIZING CROSS-REFERENCING

1. When information is short and consecutive, make it part of the paragraph in which it is introduced.
2. Use "above" or "below" when cross-reference is to paragraphs closely preceding or following.
3. Repeat cross-referenced material appearing in any other publication when the material is short (less than two pages, or can be condensed to two pages).
4. In text with illustrations place text and illustration on the same page or facing pages.
5. In unit manuals, use the words "from system" or "to system" whenever possible, to minimize cross-referencing.

NOTE

When cross-referencing cannot be avoided, limit it to:

- Same manual
- Another volume of same manual
- Publications available to technician (which have a recorded distribution to his organization.)

ACCURACY

Do everything possible to ensure accuracy of all cross-references in the manuscript and in the final copy. Check each cross-reference directly. Following any change or correction in the manuscript, recheck each cross-reference that could possibly be affected.

When a change or revision has been made to a manual, recheck all cross-references, including those in portions of the manual that were otherwise not changed or revised. Check cross-references to other:

Parts	Paragraphs	Illustrations	Volumes
Chapters	Subparagraphs	Zone numbers	Pages
Sections	Procedures	Tables	Technical manuals
Subsections	Procedural steps	Charts	Legend index numbers

CROSS-REFERENCING MECHANICS

Same Manual or Another Volume of Same Manual

1. If material is numbered, cross-reference by applicable number of:

Part	Paragraph	Illustration
Chapter	Subparagraph	Table
Section	Procedure	Chart
Subsection	Procedural step	

2. If material is unnumbered, cross-reference by name or title of applicable:

Paragraph	Illustration
Subparagraph	Table
Procedure	Chart

This to be used only if cross-reference can be clearly understood and easily located

Other Documents

NOTES

- Don't cross-reference specifications or standards for essential information concerning procedure performance.
 - Don't make cross-reference to publications of a temporary nature or to those unavailable because they are limited to certain organizations or activities.
1. Cross-reference other publications by identifying numbers.
 2. Cross-reference Government specifications and standards by basic number as listed in the Department of Defense, Index of Specifications and Standards (DODISS).

STYLE

Parenthetical, Short Cross-reference

1. Within a sentence, use:

Type of format -

fig	abbreviated
para	

section	
appendix	spelled out
chapter	

followed by applicable reference number.

EXAMPLES:**1-3. MODES OF OPERATION.**

The E-99 fire control system (fig. 1-4) provides the following modes of operation:

- r. Perform preliminary adjustments (para 4-6).
- s. Perform rf sensitivity adjustment (para 4-11 thru 4-15).

12-13. The test unit is manufactured in two forms - - portable and rack-mounted. The portable form (fig. 12-9a) is usually provided on initial procurements. A space is left available in the test position rack for the other type (fig. 12-9b), which may be procured on special order.

2. Between sentences, write a complete sentence, using "see" followed by the cross-reference. (Place closing period inside closing parenthesis.)

EXAMPLES:

8-32. In making the following adjustment, observe the general rules for performing operations of a critical nature. (See para 8-5 thru 8-8.) The adjustments will fail if . . .

6-31. **TIMING SECTION.** The timing section of the remote-station synchronizer (503 unit) is identical with that used in the local synchronizer (003 unit). (See para 6-9.) The 503 unit is .

NOTE

Don't use complete sentence-type cross-references within another sentence or preceding the terminal period of a sentence. Within a sentence:

Change:

(See fig. 6-1.) to (fig. 6-1)

or to ". . . as shown in figure 6-1."

Parenthetical, Long Cross-reference

In text spell out all cross-reference categories such as figure, paragraph, section, etc.

EXAMPLE:

23-8 . . . (For a detailed discussion of the control circuit, see paragraph 19-23.)

Non-Parenthetical Cross-reference

In text, spell out all cross-reference categories such as figure, paragraph, section, etc.

EXAMPLES:

8-45. . . . The procedure for making the adjustment is shown in figure 8-23.

1-1. **PURPOSE OF EQUIPMENT.** Radar Set AN/APG-99, shown in figure 1-1, performs the following functions:

- a. . . .
- b. . . .

With Tables and Charts

1. In simple tabular listings (parts, tools, legends) be brief and concise - (fig. 1-4) or (para 4-6).

EXAMPLES:

crimping tool (fig. 3-8)
special pliers (fig. 3-0)
special wrench (fig. 3-10)

NOTE

If "see" must be used for clarity, do not capitalize; do not use terminal period: (see fig. 3-8). This rule does not apply to text.

2. If many items contain cross-references, a separate column may be used for them; entries then should not use parentheses.

EXAMPLE:

Item	Fig.
crimping tool	3-8
special pliers	3-9
special wrench	3-10
...	...

With Illustrations Using Figure Numbers

1. For index (callout) numbers:

- a. Use format: 34, figure 2-6.

index figure

 number first

When a general cross-reference to figure number is provided at the beginning of the paragraph, use index number only.

EXAMPLE:

Rotate cam (6) . . .

- b. When several cross-references in a paragraph refer to the same figure, indicate figure number in first cross-reference only. This cross-reference applies until the sequence is broken by a cross-reference to a different page or figure number.

2. Figures placed in the manual for general reference purposes may be referred to in blocks.

EXAMPLE:

A schematic diagram is provided for each unit. (See figure. 12-1 thru 12-56.) These diagrams are arranged in order of . . .

3. Make illustration zone cross-reference as follows: . . .
 - (zone 2B, fig. 7-8) . . .

Omit the sheet number if the cross-reference includes a zone number (or numbers).

Omit the figure number in a cross-reference to another zone in the same figure: . . . (zone 4C) . .

In Headings

1. Parenthetical cross-reference in subordinate* paragraph heading:

*Stand-alone, secondary heading (not followed by run-in text).

10-34. RF AMPLIFICATION SECTION. (See fig. 10-16.)

23-34. MODULATION SELECTION AND CONTROL SECTION. (See fig. 23-12)

NOTE

A boldface primary heading should not be followed by cross-reference.

2. Use parenthetical cross-reference in run-in secondary paragraph heading:

- a. Place period after heading.
- b. Make cross-reference a complete sentence.

EXAMPLE:

42-8. AGC CHANNEL V4, V5, V7, and V9. (See fig. 42-9.)

The agc channel develops the voltage that . . .

3. Where heading is followed immediately by steps of a procedure or items of a list - make cross-reference a complete sentence:

12-6. REMOVAL OF RF UNIT.

(See fig. 15-13.)

- a. Set PWR switch (5) to OFF.

Underlining

In cross-referencing to lowercase letters indicating:

- a. Steps of a procedure
- b. Portions of an illustration
- c. Items in a list

Underline the designated letters for:

- a. Italics in typeset manual
- b. Emphasis in typewritten manual

EXAMPLE:

Garbled: Repeat step as if adjustment is needed.

Improved: Repeat step as if adjustment is needed

Better: If adjustment is needed, repeat step as.

Placement of cross-references

1. When using a cross-reference in a sentence, or between sentences, place the cross-reference following the first word or phrase to which the reference is exactly applicable (but maintain a readable sequence of words). Avoid both ambiguity and unnecessary awkwardness.

Misleading: The two transmitters of the system (fig. 2-18) are mounted in forced-air-cooled cabinets. The illustration depicts the units partly withdrawn from the cabinets to show the locking mechanism.

Correct: The two transmitters (fig. 2-18) of the system . . .

Or: Figure 2-18 depicts the transmitters partly withdrawn from their cabinets to show the locking mechanism.

2. Place cross references to the right, or below, figure titles.
3. Don't regard cross-references used with figure titles as part of the title. Don't, for example, include the cross-reference with the figure title in the front matter.

Style below figure:

Style in front matter:

Figure 1-3. Installation Requirements (See table 1-5).

Figure	Page
1-3. Installation Requirements . . .	1-12

Repetition of Complete Cross Reference

Within a paragraph, regard a given complete cross-reference as applying until a new cross-reference appears; this permits use of the simplified form: (1), (5), etc. If you then wish to return to some other cross-reference, repeat that cross-reference in full.

EXAMPLE:

- a. Set PWR switch (5, fig. 7-2) to ON.
- b. Set RNG switch (4) to 200 MI.
- c. Connect test probe (17, fig. 7-3) to TEST jack (2).

Section 14

NOMENCLATURE

	Page		
Definitions	1	Controls and Indicators With Panel	5
Nomenclature	1	Nomenclature	6
Military Nomenclature (AN, JAN, etc) ...	2	Controls and Indicators Without Panel	
Choice of Nomenclature	2	Nomenclature	6
Military Nomenclature Assigned	2	Multiple Controls and Indicators with	
No Military Nomenclature Assigned	2	Same Panel Nomenclature	6
Nomenclature Below Unit Level	3	Control and Indicators in Procedures .	
Common Names and Manufacturer's		Location Data	7
Names without Part Numbers	3	Condensing Nomenclature in Tables	
Cost Considerations	3	and Illustrations.....	7
Rules for Using Nomenclature	4	In Theory and Descriptive Material	7
Consistency	4	In Congested Material	7
Straight-Reading Sequence	4	In Tabulations	8
Articles (a, an, the)	4	In Maintenance Manual Procedures....	8
Manufacturer's Part Number	5	In Artwork	9
Multiple Components With Identical Basic			
Names	5		

DEFINITIONS

Nomenclature: Nomenclature refers to names assigned to items in agreement with an organized designation system.

Name + part/type/model number = nomenclature

EXAMPLES:

Power Supply 448102-100

Power Supply 448102-100 and 448102-200

Power supply (when it identifies a specific unit)

NOTES

- Hereinafter, the term "part number" is assumed to encompass part, type, and model numbers.
- Names of units are nomenclature even without part numbers. However, names of such common items as "resistor," "switch," etc, are not nomenclature.

Official and regularly assigned names of the following are nomenclature:

Test instruments	Indicating devices
Tools	Controls
Fixtures	Control positions
Circuits	Test Points
Signals	

Military Nomenclature: Systems and units procured by the Government may sometimes be assigned military nomenclature.

Descriptive name + coded type number = military nomenclature

NOTE

Military nomenclature, if assigned, takes priority over manufacturer's nomenclature. (It may appear in lieu of the manufacturer's nomenclature on the nameplate, with the manufacturer's nomenclature on the same nameplate, or on a separate nameplate on the equipment.)

CHOICE OF NOMENCLATURE

Military Nomenclature Assigned

If military nomenclature has been assigned, use it to the exclusion of manufacturer's (contractor's) nomenclature. However, a set of simplified nomenclature can be adopted providing it is cross-referenced to military nomenclature.

The cross-reference index, such as a list of equipment supplied, should include simplified names based on official ones. The simplified names may then be adopted and used consistently throughout the remainder of the manual, or sets of manuals.

If no military nomenclature assignments are planned, or the assignments are delayed, use the manufacturer's (contractor's) nomenclature.

No Military Nomenclature Assigned

In the absence of official military nomenclature, assign unit nomenclature from the following sources (arranged in the order of precedence). Simplified nomenclature may be established in this case also.

- a. The nameplate.
- b. The identification plate (nameplate) drawing.
- c. Top assembly drawing for the unit.
- d. The master index.
- e. The schematic diagram.

Nomenclature Below Unit Level

For assemblies, modules, subassemblies, or parts, assign nomenclature per title block of manufacturer's assembly drawing, except convert modifiers to straight-reading sequence.

In text, simplify drawing title names by omitting secondary modifiers, but be sure clarity and consistency are maintained.

Omit part numbers for items below unit level unless numbers are:

- Needed for clarity.
- Required for specification.

Common Names and Manufacturer's Names Without Part Numbers

For precise identification of common names or official manufacturer's names used without part numbers, clarify any such name by following it with a parenthetical, simplified "unit" number derived from the full part or assembly number, and the word "unit."

EXAMPLE:

"Horizontal Situation Indication 464080-100 (080 unit) . . . The 080 unit . . ."

NOTE

Thoroughly explain the simplified unit identification method to the reader.

Use any such simplified unit name-and-number identification method whenever required, particularly in:

- Section titles
- Paragraph headings
- Figure titles
- First mention of unit in text

COST CONSIDERATIONS

To avoid unnecessary change and revision costs, limit the use of complete part, type, and model numbers to the:

- Titlepage
- Introductory description
- Introductory artwork
- List of equipment supplied
- List of test equipment and special tools required

Thereafter use the name portion of the nomenclature, or a consistent adaptation of that portion, unless the number is required to distinguish between like items.

RULES FOR USING NOMENCLATURE

Consistency

Keep nomenclature consistent within publication and within a series of related publications. Don't call an item one name in one portion of a manual and another in some other portion.

Straight-Reading Sequence

Where nomenclature selected from manufacturer's engineering sources or from a Government agency is listed in inverted form, rearrange the nomenclature in straight-reading sequence (unless otherwise specified in contract or specification).

EXAMPLE:

Converter, angle data = angle data converter
(inverted form) (straight-reading sequence)

Straight-reading sequence should be used:

On title page
Throughout manual

If a "complete" military nomenclature is used, write it as listed in the official source document, except convert it to straight-reading sequence. This is required for clarity and readability of the text.

Don't insert explanatory modifiers not present on the nameplate; if such modifiers are needed, add them parenthetically, in lowercase, following the complete nomenclature.

EXAMPLES:

INCORRECT: Power Suppler (indicator) PP-34/APG-45
CORRECT: Power supply PP-34/APG-45 (indicator power supply)
CORRECT (title page): POWER SUPPLY PP-34/APG-45 (INDICATOR POWER SUPPLY)

Articles (a, an, the)

Omit the article preceding nomenclature that includes the part number unless the article is required for clarity.

EXAMPLES:

The instructions for Flight Data Computer 446-46-0001-1 are given in paragraph 21-8.

The faulty units include Receiver-Control C-1683/ARR-44.

Using special socket wrench 586-50-3A, install the . . .

Manufacturer's Part Number

Don't refer to subunits or parts by manufacturer's part number unless:

This is the only means of obtaining clarity.

Such identification is required by the controlling specification.

Multiple Components With Identical Basic Names

When two or more components have identical basic names, include appropriate descriptive modifiers in the common-name nomenclature assignments.

EXAMPLES:

Nameplate:

Power Supply 49901-100

Common name:

low-voltage power supply

Nameplate:

Power Supply 49902-100

Common name:

high-voltage power supply

Controls and Indicators With Panel Nomenclature

In all references to controls, control positions, test points, and indicating devices having panel or chassis nomenclature, write the nomenclature exactly as it appears on the panel or chassis.

Don't enclose such nomenclature in quotation marks unless required for clarity.

If correction or clarification of spelling or of an abbreviation is necessary, make the correction parenthetically the first time the item is referred to. If variations of panel nomenclature exist, as may be the case with units of standard test equipment, include a NOTE explaining that the panel names are typical and may vary slightly from one unit to another.

EXAMPLES:

Set MASTER switch to OFF.

Turn EL SCAN control to HOR.

Set OPER switch to SP.

Set TEST switch S1801 (3) to position A.

Adjust SIG XTAL CUR ADJ (signal crystal current adjustment) for 3 ma on XTAL CUR meter M1.

In instructions involving controls and indicators with panel nomenclature, identify these items by panel name only. Omit the circuit reference symbol (R105, C56, etc) unless:


The instruction requires the operator to refer to an illustration showing the reference symbol.

The reference symbol itself appears on the panel.

EXAMPLES:

Set OPR CONTROL switch to REM.

Set OPR CONTROL switch S54
(fig. 4-6) to REM.



When the reference symbol is part of the panel nomenclature or a suitable reference is given.

Controls and Indicators Without Panel Nomenclature

If the control or indicator is unmarked on the panel, reference to circuit reference symbol (reference designator) may be necessary. Make sure the reader knows how to identify the item physically.

Multiple Controls and Indicators With Same Panel Nomenclature

If there are two or more controls or indicators with identical panel nomenclature, the circuit reference symbol is necessary. Make sure the reader knows how to identify the intended item.

EXAMPLE:

Set OPR CONTROL switch S54 (3) to REM.

Set OPR CONTROL switch S76 (6) to ADD.

Controls and Indicators in Procedures

In procedures involving controls and indicators with functional names only (no panel names), identify these items both by functional name (lowercase) and reference symbol. Omit the functional name after first mention of the item if doing so doesn't impair clarity.

Upon re-referring to such an item after a space involving a step or two (depending on length of steps), again use both identifiers.

Include references to illustrations that show the reference symbols, observing all applicable rules. Make certain that the control can be identified physically

EXAMPLES:

Adjust horizontal centering control R67 to center the sweep trace on screen.

If a suitable figure reference has appeared earlier.

Set attenuator switch S23 (fig. 8-12) to give output indication of 8 dbm on DBM meter M16. Advance S23 from this position, one step at a time, until . . .

Location Data

To give locations of controls and indicators, particularly in procedures, use parenthetical or simplified unit numbers.

EXAMPLES:

Set controls of 2A7 unit . . .

Set SYNC SELECT control (888 unit) to position 8.

[888] SYNC SELECT control: set to position 8.

Condensing Nomenclature in Tables and Illustrations.

Omit unit name.
Use simplified unit number only.

In Theory and Descriptive Material

Clarify control nomenclature that includes special (unapproved) abbreviations by spelling out the complete words in parentheses following the first use of the nomenclature, and thereafter as required for clarity.

EXAMPLE:

The amplitude is adjusted by SWP C & C (sweep centering and gain) control R1608.

Don't use stock numbers, part numbers, and SMR (source, maintenance, and recoverability) codes in text unless necessary for clarity.

In Congested Material

Use the military type number or the manufacturer's type or part number as a modifier with the name following the type number. A clearly abbreviated form, or the entire part number may be used. Write the name all lowercase.

EXAMPLES:

Military nomenclature:

Pulse Generator Set AN/UPM-15

Modifier use:

the UPM-15 pulse generator set, the AN/UPM-15 pulse generator set, or the UPM-15

Company nomenclature:

Rocket Control Power Supply 464087-161

Modifier use:

... the 464087-161 rocket control power supply ... or ... the III rocket control power supply (087-161 unit) ... (to distinguish unit from another variation).

In Tabulations

The AN military type numbers may themselves be used as nouns. However, first make certain that the unit or system has been clearly identified by more formal nomenclature. Either the complete type number, or a clearly identifiable abbreviated form, may be so used.

EXAMPLES:

AN nomenclature:

Insulation Test Set AN/PSM-1A

Noun use:

the AN/PSM-1A, or the PSM-1a

As long as clarity is maintained, this rule may also be applied to manufacturer's model, type, or part numbers. For a straight "numerical" part number, usually include the word "unit," "circuit," "modification," "version," etc after the number.

EXAMPLES:

The Model 650 (or the Model 650 vtvm) ...

The 630-A voltohmmeter differs from the 630-PL in that the ...

The 463080-120 circuit differs in ...

In Maintenance Manual Procedures

Use the applicable repair parts breakdown to determine the nomenclature of assemblies, subassemblies, and parts called out.

In using repair parts list nomenclature, omit secondary modifiers where these contribute nothing to clarity. Quite often (particularly when index numbers are used), you can reduce the nomenclature to the basic noun - nut (3), bolt (7), screw (31), etc.

When using functional nomenclature for an item, show the repair parts list nomenclature (basic noun and any essential modifiers) first, and then, parenthetically, the functional name. If the item is something other than a control, retain the basic identical noun.

EXAMPLES

Parts list:

Resistor, variable R103

Maintenance manual legend:

Variable resistor R103 (AZ PHASE control)

Maintenance manual text:

the AZ PHASE control . . . or . . . AZ PHASE control R103

In Artwork

Follow all of the above rules for the selection and use of nomenclature. Avoid the use of stock numbers and part numbers wherever possible. Try to limit their use to tables and legends.

Section 15

REFERENCES TO STANDARDS

	Page	Page
Government specifications and Standards 1		Manual Specification or Contract Number 2
Manufacturer's Specification for Materials	1	

GOVERNMENT SPECIFICATIONS AND STANDARDS

1. If an official Government specification exists for a material you are referring to, you must identify the material by Government specification number rather than the manufacturer's number. (See the *Department of Defense (DOD) Index of Specifications and Standards* for applicable specification number of materials such as lubricants, sealing compounds, abrasives, etc.) In addition to the Government specification number, include the applicable military service's part number or NSN (National stock number) whenever possible in the list of materials.
2. If you can't otherwise determine a number from the *DOD Index of Specifications*, obtain the information from the procuring agency.
3. When a Government specification or standard is referred to, use only the basic number, omitting any revision-letter suffix unless reference to a specific revision is essential.

EXAMPLE:

Revised issue number:
Military Specification MIL-H-16005C

Reference in manual
Military Specification MIL-H-16005

4. On the first reference, and as required for clarity, precede any Government specification or standard number with identification of the originating branch of the Government or with identification of coverage. Thereafter reference may be limited to the type number of the specification.

First reference: "... solvent (Federal Specification P-S-661) ..."

Subsequent references: "... P-S-661 solvent ..."

MANUFACTURER'S SPECIFICATIONS FOR MATERIALS

- a. Avoid references to manufacturer's specifications for materials, if possible.
- b. If the correct Government specification can't be identified, or doesn't exist, refer to the material by its exact commercial designation, plus the words "or equivalent" (if valid). Check this designation carefully.

MANUAL SPECIFICATION OR CONTRACT NUMBER

Don't refer to the manual specification or contract number used in the manual, unless this is required by the contract or the controlling specification.

Section 16

TABLES

	Page		Page
Definitions	1	General Notes , References	
Table	1	Etc.	2
Chart	1	Layout	2
Authority	1	Style	3
When to Use Tables and Charts	1	Front Matter	3
Headings	2	Possible Problems with Tables	4

DEFINITIONS

Table: Technically, a **table** does not contain artwork.

Chart: When artwork is included in a table, the term **chart** usually applies.

For purposes of technical manuals, the use of artwork with tabular material is encouraged wherever it makes the material easier to use or understand. The terms **table** and **chart** and the associated requirements may be used interchangeably.

Consider tables to be a type of illustration.

AUTHORITY

The U. S. Government Printing Office Style Manual should be used as a general guide for the style and format of tables and tabular material.

WHEN TO USE TABLES AND CHARTS

Use tables, charts, and other illustrations instead of text in sentence-paragraph format wherever possible, particularly for:

- **Statistical data** (equipment supplied, equipment characteristics, test equipment and special tools, operating and adjustment controls, etc)
- **Wiring data**
- **Procedures**
- **Special abbreviations**
- **Condensed alignment and adjustment data, or inspection standards**
- **Voltage and resistance data**
- **Mathematical data**
- **Computer data**
- **Test data, test sequences**
- **Physical descriptions**
- **Maintenance schedules**
- **Any similar data**

NOTE

For continuous-type data where interpolation is necessary for a specific desired value, use a graph instead of a chart or table.

HEADINGS

1. Provide a concise heading to identify the specific content of each tabular column.
2. When column entires contain measurable quantities, include the unit of measure in the heading.

NOTE

If there are several different units of measure in the same column:

- Reorganize the data to group same units together, if possible.
 - Place units of measure next to each entry.
3. If a column is subdivided, provide subheadings for the secondary columns. Don't subdivide secondary columns; reorganize the table instead.
 4. Repeat the column headings for each sheet of the tabulation. However, if two sheets of tabulation are printed on facing pages in "landscape" view, the column headings may be omitted on the second sheet, so that the entries then run continuously across both pages.

GENERAL NOTES, REFERENCES, ETC.

1. When table title is at the top:

Place a general NOTE, CAUTION, or WARNING, or other general reference applicable to the entire tabulation, between the table title and the top of the ruled form.

2. When table title is not at the top:

Place general notations below the enclosure used for the column headings and above the first tabular entries. Place a horizontal rule below the space occupied by the introductory general data.

3. Make any general introductory table, figure, or paragraph reference in the tabulation in the form of a NOTE.
4. Place a NOTE, CAUTION, or WARNING at any required point in the tabulation. If necessary to conserve space, spread the information across more than just the column or columns to which it applies, providing the application of the information is clear to the reader.

LAYOUT

1. Keep the tabular layout neat and well balanced. A skillfully arranged table or chart is similar in many ways to a skillfully composed piece of artwork. Check each tabulation visually to ensure proper layout.

2. Keep the material in the various columns of a tabulation reasonably well balanced. If crowding occurs in a column, rearrange the layout to provide greater horizontal space at that point.
3. Avoid lengthy special notations in a column, which cause long blank spaces in adjacent columns. If possible, spread the notation over more than one column as indicated above.
4. Avoid columns which are blank or in which relatively few entries are made. When there are relatively few entries in a column, it is better to use notes, or include the information in another column. Consider reorganization of data.

STYLE

1. Observe the principle of parallel construction in relating column entries to the related column heading.
2. Except where required for clarity, omit the articles (a, an, the) in all tabular entries.
3. If necessary for condensing in tabulations, use elliptical (grammatically incomplete) types of expression to reduce wordage. Make certain that this method preserves clarity and that methods of condensing are consistent within each tabulation.

EXAMPLES:

POWER: ON; AS: 20; EL: 45; SCAN: ONE BAR.

(Note: The colons indicate the ellipses. The complete wording is: Set POWER switch to ON; set AS switch to 20; etc.)

4. Use three spaced dots (. . .) at any point in the tabulation where an entry is not required, but might be expected by the reader. This assures the reader that an entry has not been accidentally omitted.

Omit the spaced periods in instances where no reader could reasonably expect an entry.

5. Order row entries in some logical, correct sequence. If technically correct, alphabetize them.
6. Limit ruled lines in a table to those actually required, for example, to separate columns vertically and isolate column headings.

FRONT MATTER

In front-matter listings of formal tabulations identified as figures, make certain that each listing makes clear that a tabulation, rather than an illustration, is involved. Whenever this clarification is necessary, add the word *chart* or *table* in parentheses following the title.

Don't regard this parenthetical word as part of the title for this application. Don't include either word parenthetically in the title accompanying the actual tabulation.

Make certain that production personnel understand that these two parenthetic words are not to appear in the titles in the body of the manual.

EXAMPLES

(Excerpts from typical List of Illustrations)

<u>Number</u>	<u>Title</u>	<u>Page</u>
	...	
12-9	Interconnection and Wiring Table (12 Sheets)	12-24
	...	
7-3	Typical Voltage and Resistance Measurements (Chart).....	7-26
	...	

POSSIBLE PROBLEMS WITH TABLES

1. Difficulty in visually following a row across the width of the table, particularly when one column entries are blank.

POSSIBLE SOLUTIONS:

- a. Move columns closer together.
- b. Increase vertical spacing between lines (leading).
- c. Reorganize data to reduce width of table.
- d. Use dot leaders between columns.
- e. Use horizontal lines between rows, or groups of rows.
- f. Use a double space to separate groups.
- g. Use three spaced dots (. . .) for blank entries.

2. Difficulty in reading because column headings blend in with column data.

POSSIBLE SOLUTIONS:

Highlight column headings by:

- a. A box around headings.
- b. Underlining.
- c. **Boldface type.**
- d. Larger type in headings than in entries.
- e. Different margins from column content.

3. Difficulty in reading numerical data in columns.

POSSIBLE SOLUTIONS:

Aline numerical data:

- a. Decimal numbers on the decimal point.**
- b. Scientific notation on the operation symbol.**
- c. All other numerical data flush right.**

Section 17

GRAPHS

	Page		Page
Definition	1	Graph Construction	5
Use of Graphs	1	Scale	6
Common Problems with		Title Block	6
Using Graphs	1	Limitations and	
Good Practices for		Restrictions	6
Effective Graphs	2	Baseline	7
Types of Graphs	2	Interception of Lines	7
Conventional	2	Deflector Lines	7
Bar Graphs	4	Graph Entry	7
Stack Graphs	5	Grids	7
Nomographs	5		
Other Types	5		

DEFINITIONS

Graphs are pictorial means used to present variable information.

A graph is a diagram (as a series of points, a line, a curve, or an area) that represents the variation of a variable in comparison with that of one or more other variables.

USE OF GRAPHS

Graphs should be used as tools to reduce the amount of text in a technical manual as frequently as feasible. Graphs should be used wherever possible to replace, supplement, or simplify text in technical manuals. They should be designed for maximum clarity, usability, and understandability.

Graphs should be used instead of tables on continuous-type data where interpolation is required.

To provide background information and stimulate interest, it is usually desirable for graphs to present extremes (or total capability of the equipment) even if that information is not required for operational use.

Common Problems with Using Graphs.

1. Complex, hard-to-understand presentation of information.
2. Too much information given on a single graph.
3. Graphs too small, or improperly scaled, for good legibility.
4. Data lines too close together to be easily read.
5. Improper use of shading and crosshatching.

Good Practices for Effective Graphs

1. Keep the essential message clear; use simple presentations.
2. Use single-line presentations instead of multi-line presentations, provided information is within readable or usable tolerance.
3. Make use of the maximum image area.
4. Draw data lines at least 1/8 inch apart.
5. Continue the two outside lines of a series of converging lines to a point, intersection, or end of the graph. Discontinue the other lines in a series when they converge to 1/8 inch separation.
6. Avoid crosshatching over grid patterns. Use shading or coloring instead, or omit the grid pattern in the area containing the crosshatching.
7. Avoid reverse printing (white lettering on black background), except if it will be used in dark-adaptive ambient where reflectivity may be improved by white lettering.
8. Provide instructions (complete with illustration if necessary) for using complex graphs.
9. Orient the axis naturally (for example: height on the vertical axis).

TYPES OF GRAPHS

Conventional

These may be:

Linear - describing a straight line - Type A


Curvilinear - describing a curved line - Type B

Types A and B may be used separately, or in combination to present total information.


Type B shows how an additional parameter may be introduced by using multiple traces.

Combining A and B allows additional parameters/interrelationships to be shown between two sets of data.

TYPE A GRAPH, Straight line



TYPE B GRAPH, Curved line




Bar Graphs

Bar graphs may be either vertical or horizontal. Bar graphs can be used to present tabular data in an easy-to-read visual form.


They are used best for discrete data where interpolation is not necessary, and should replace tables whenever possible.

The example below shows horizontal orientation.



Stack Graphs

Stack graphs show the relative magnitudes of two or more variables. The components may be graphically stacked to form either a fixed or varying total.



Nomographs

A nomograph is usually complex and an easy source of errors. Nomographs should normally not be used. (Nomographs are alignment graphs that enable determination, by the aid of a straightedge, of the value of a dependent variable when the values of two independent variables are known.)

Other Types

There are many other types of graphs which may be used. The criteria for selecting any of these should be based on:

- Clarity in providing desired information.
- Ease of use.

The user must be able to extract the desired data accurately and as quickly as possible.

GRAPH CONSTRUCTION

A graph should be labeled, lettered, and numbered so that it can be read while holding the manual in the same position required to read the text. Scales, baseline, parameters, lettering, and numbering should be in bolder print than the minor and intermediate grid lines.

Scale:

A graph in final format in the manual should be to as small a scale as possible with all detail easily legible.

Title Block:

The title block should contain at least:

a. Descriptive title

The descriptive title should be boxed and placed in top left corner. (Be sure it clears the binding of the manual and is clearly visible.)

b. Equipment model

Not necessary in title block if data applies to all models. (However, a statement to this effect should be included in the introductory paragraph.)

c. Example of how to use graph, if not obvious.

Acceptable methods to show an example of how to use the graph in title block are:

- (1) Place a miniature reproduction of the graph at the top center of the title block. Baselines, parameters, guidelines, dashed lines, and arrows should be used judiciously to provide the example desired, simplified by not including grid patterns and numerals.
- (2) Include example on the graph using a dashed line followed by the values used in a sample problem in the text. The problem should be illustrated so that the dashed lines remain clear of the graph area normally used.

NOTE

Refer to the applicable technical content specification for deviations or additions to title block contents.

The title block should:

- a. Be placed above the graph.
- b. Not exceed in area the top quarter of the total image area.
- c. Contain all the information required to use the graph.

Limitations and Restrictions:

1. Scales, curves, and guidelines for each parameter should bracket the lowest value to the limit value for that parameter specified in the manual, and should also extend to the next major unit for that parameter.

2. The lines may be extended to higher units if there is an anticipated increase in the limit value of the parameter specified in the manual, provided the increased limit does not change the basic data.
3. Limit lines should be included and labeled to represent any limitations or restrictions on the equipment or accessories, or any other limitation because of unsatisfactory or impractical equipment characteristics.

Baseline:

On Type B graphs, place baseline at the entry point.

Interception of Lines:

Interception of lines at an angle of less than 30 degrees should be avoided.

Deflector Lines:

Deflector lines may be placed in the graph.

Graph Entry:

Use single graph entries whenever possible. Double entries should be used only when single entries cannot be used.

Grids:

Item	Standard
Grid interval	0.3 inch (0.1 inch minimum)
Gridline width	0.015 - 0.0125 inch
Gridline spacing	Maximum: 20 gridlines per inch Minimum: 5 gridlines per inch

NOTE

Grid spacing may vary from graph to graph so that the full image area of a page can be used.

Item	Standard
Grid scale	Each minor grid unit should represent an easily calculable fraction of the major units such as: 0.05 0.1 0.2 0.5 not 0.4 or 0.125 if the major unit is divided into 10 minor units.
Transfer scale if graph extends to a following page	Entrance scale on new page should match exit scale on previous page.
Gridline frequency	Major (heavy) - every 10 units Intermediate - every 5 units (accented) Minor - each 1/10 unit between major lines

Section 18

FOOTNOTES

	Page		Page
Application	1	In Illustrations	3
Authority	1	General Notes (Complex Illustrations)	3
In Tabular Material	1	General Notes (Simple Illustrations)	4
When to Use	1	Multiple-sheet Illustrations	4
Where to Place	1	Changes and Revisions	4
Style	2		

APPLICATION

In technical manuals, footnotes are generally limited to use in tables, charts, and illustrations. Notations in text should usually be in the form of NOTES, CAUTIONS, and WARNINGS.

As used in this section, the term "footnotes" includes "notes" on illustrations.

AUTHORITY

See the *U. S. Government Printing Office Style Manual* for general guidance on style and format of footnotes.

IN TABULAR MATERIAL

When to Use

1. Use footnotes sparingly.
2. Use footnotes only for explanations or references that don't logically belong within the tabulation proper.
3. Use footnotes to refer to specific items in the tabulation. A notation that applies to the entire tabulation, or to some sizeable portion of it, should be written as a NOTE, CAUTION, or WARNING.

Where to Place

1. Place all footnotes at the end of the tabulation, below the ruled box enclosing the final sheet of a table or within the final ruled box of a tabular figure.
2. If placing the footnotes at the end of the tabulation is not desirable in some particular instance, make references on a page-by-page basis by use of the following symbols (in the sequence indicated):

* asterisk
** double asterisk
† dagger

‡ double dagger
§ section mark
|| parallels

3. If the list of symbols is inadequate for the desired number of footnotes on any page, change the symbols of the tabulation to superior numbers.

NOTES

When required by unusual circumstances, special footnote symbols or arrangement may be used, provided their purpose is obvious or is clearly explained.

Style

1. Make each footnote concise and clear. Maintain parallel construction of similar items.
2. Make certain that all footnotes are referred to at the proper points in the tabulation. Mark the point of reference with superior numbers (numbers placed above the line). Place each reference number to the right of the item affected. In the footnote itself, place the number above the line and one space to the left of the notation.
3. Place the reference number or symbol after any punctuation mark (except the dash, or sometimes, the closing parenthesis). Place the number or symbol before or after the closing parenthesis depending on whether the reference does, or does not, pertain to the parenthesized item only.

EXAMPLES:

Reference numbers in table:

- a. Air compressor¹
- b. Control box, ² switch assembly,
relay assembly

Resultant footnotes:

- ¹ Air compressor supplied by Larson Associates.
- ² Control box supplied by Steelcraft, Inc.

4. Don't use a period after the superior number.
5. Use a period after each footnote, regardless of whether or not the footnote is a complete sentence.
6. Keep footnote reference numbers and symbols in the sequence of their initial appearance. Don't, for example, place the initial reference to the fourth footnote ahead of that to the third footnote, except if necessary for incorporation of a change.
7. Generally, start a new series of symbols for each affected page, but this arrangement may be varied if the situation requires some other clear arrangement.

8. If you must refer to a given footnote more than once on a page (for symbols) or in the complete tabulation (for superior numbers), reuse the original symbol or number for each repetition.
9. Don't use superior numbers in tabulations of mathematical matter in which these numbers could be mistaken for exponents. Use reference symbols or, if desired, superior, lowercase reference letters. In tabulations of other types of mathematical matter, use superior numbers unless this method impairs clarity.
10. The flag-symbol method described for notes in illustrations () may also be used in complex tabular charts where superscript numerals might be overlooked by the reader.

IN ILLUSTRATIONS

1. Observe all applicable rules of this Style Guide in writing notes in illustrations. Rules concerning punctuation, word usage, abbreviations, and nomenclature, as used in preparation of condensed matter, apply to the writing of notes.
2. Don't use notes on an illustration if the application of the note isn't relevant to the manual. (For example, delete manufacturer's fabrication data on schematic diagrams.)
3. Use footnotes in illustrations for material that doesn't logically form part of the artwork proper or of the lettering on the art.
4. Maintain consistency of note style from one illustration to another. Don't confuse your reader by introducing needlessly different styles.

General Notes (Complex Illustrations)

1. In a relatively complex illustration for general reference (schematic, functional diagram, etc), ordinarily identify the footnotes with the heading NOTES (singular NOTE). Punctuate the heading with a colon (:) and place the heading as shown below:

NOTES:

1. ALL RESISTOR VALUES IN OHMS.
2. LOCATIONS OF TERMINAL DESTINATIONS SHOWN ON WIRING DIAGRAM.
2. Place the notes within the crop-marked area in any reasonably conspicuous spot (not necessarily at the "foot" of the illustration).
3. Label the notes with Arabic numerals. Except for numerals enclosed in flag symbols, punctuate each numeral with a period; don't set the numbers above the line.
4. If a note applies to one or more specific point in the artwork, enclose the numeral with a flag symbol (), or similar device, with its apex to the right, pointing toward the note. Use similar symbols, as applicable, in the artwork, with the apex of each flag symbol pointing toward the affected item.

5. Make certain that the point of reference is identified.
6. Use sketches, such as those showing circuit variations, as required, in any applicable notes.

General Notes (Simple Illustrations)

In a relatively simple illustration, or an illustration providing procedures or principles of operation or maintenance, generally show notes in a more emphatic style than those on complex illustrations. Don't necessarily number such notes, but place them and word them to obtain concise, clear meaning.

EXAMPLE:

RELAY DATA

<u>Relay</u>	<u>Energized</u>
K901	When ACTION switch is pressed.
K902	When ant. is not against limit.
K903	When SEARCH button is pressed.

Multiple-Sheet Illustrations

1. For multiple-sheet illustration, initially place all notes on the first sheet. In the initial, complete list, place the general notes ahead of the flag notes. Arrange the flag notes in the order of their appearance on subsequent sheets.

Exception:

If a given flag note occupies excessive space, its appearance on the first sheet may be limited to a reference, such as () SEE SHEET 4.

Exception:

In a highly congested logic tree, or other complex chart, a number of brief flag notes may be run in series across the bottom of the sheet.

2. Repeat each flag note on any subsequent sheet to which it pertains.
3. Repeat each explanatory "legend" on each sheet to which it pertains.
4. Don't repeat ordinary general notes on subsequent sheets.

Changes and Revisions

1. When a note is added by a change, place it at the bottom of the list. It is not necessary to rearrange or renumber the notes except as required for clarity.
2. When a change upsets the initial placement, rearrangement of notes is not necessary for a general revision (reissue), except as required for clarity.

Section 19

EDITING

	Page		Page
Definition	1	Proofreading	4
How a Writer Can		<i>Methods of Proofreading</i>	5
Facilitate Editing	2	Iterations of Proofreading	5
Suggestion to the Editor	2	Edit Marks	6
Desirable Editor Attitudes	3	Brief Summary	6
References for Editing	4	Standard Edit Marks	7

DEFINITION

Editing: Checking manuscript for technical accuracy, conformity to a particular standard of data presentation, and clerical accuracy. Editing is also required to bring a manuscript into the form required for production to obtain a satisfactory final product.

Editing includes doing whatever is necessary to make the manuscript a good-quality, usable product conforming with the specification, contractual and style-guide standards. The editor is responsible for checking all inaccuracies, all violations of the style guide, all violations of specifications or applicable deviations to the specification. Editing includes checking for:

Technical accuracy.

Technical consistency.

Adherence to security regulations, both in marking and routing of classified manuals.

Consistency of any portion of manuscript with other portions of same book or of related and referenced books.

Adherence to rules of the style guide and customs of professional technical writing.

Correctness and completeness of front matter.

Editing also includes:

Correcting defect and inaccuracies revealed by edit.

Clearing up any questionable items of information.

Rewriting as necessary to improve readability, comprehensibility, or usability.

Marking manuscript copy to ensure an accurate typing and printing job.

Proofreading to ensure that the final copy adheres to the input and the editing of the manuscript.

HOW A WRITER CAN FACILITATE EDITING

In addition to technically accurate and complete manuscript content, there are some simple precautions which the writer can take to greatly facilitate the mechanics of editing. Some of these are:

Avoid overcrowding a page.

Double - or triple-space between lines.

Double-double space between paragraphs.

Leave wide margins. Leave at least 1-inch margin on left side so that no information can get lost in punching holes or binding pages.

Write legibly.

Form letters and numbers or symbols recognizably.

Use adequate pressure on writing tool.

Place date in position it is intended to be.

Use standard edit marks as necessary; rewrite if necessary.

Number pages in sequence

Use one side of page only.


Use same size sheets for all entries (8½ x11). Small notepaper may get lost; flaps which need to be lifted on larger sheets become tattered and illegible, and may be overlooked in typing.

By comparison of cost to writer's or editor's time, paper is cheap. Adequate blank space on a page can save time and help ensure understandability of edit. An already overcrowded page which needs heavy edit is a potential source of errors and misunderstandings.

SUGGESTIONS TO THE EDITOR

1. NEVER blank out or erase original input so that it can no longer be referred to. If you have second thoughts about your edit and wish to unedit it, the use of correction tape on edit is acceptable. However, DO NOT use nontransparent correction tape on manuscript original input. Also, if you have totally rewritten a page, DO NOT throw away the original page. There is always a chance that you may have misunderstood the writer's reason for his version and it may be necessary to go back to it. If it is destroyed that becomes impossible.
2. Perform editing in a different color or a different line weight of writing tool than the original manuscript. It should stand out conspicuously from the manuscript for clarity and easy recheck by the original writer. The color and intensity of changes or corrections should be capable of producing legible copies on copying machines available. Yellow wax pencil is helpful for identifying areas checked on schematics or diagrams.
3. Don't overcrowd editing so that it is difficult to understand what goes where. It saves time and errors in the end to rewrite a line or a sentence with the desired changes. (This is particularly pertinent where the manuscript has been single-spaced.) Be liberal with rewriting your desired version as an insert on an additional page, placed before the page to which it applies. On the manuscript page use a caret to show where the insert belongs as shown below.

Marked original page



Insert page



DESIRABLE EDITOR ATTITUDES

Be reader conscious. Think usability. All writing problems must be solved with maximum provision for the needs of the user. At all times ensure maximum readability and comprehensibility as a basic requirement for whoever your readers may be.

Be skeptical. Take nothing for granted. Don't be unduly impressed with apparent authenticity of either source material supplied or the manuscript. Be alert for discrepancies; clear up all questionable items.

Be objective. Have a substantial reason or authority for every change you suggest. Do not make changes on the basis of merely personal preference, or on the basis of what you may think is "conventional" practice. Because it has been done this way for umpteen years does not necessarily mean it is better than the writer's input - - unless it is inconsistent with other parts of the manual or other manuals and may cause confusion. An editor's preferences may be not better than those of the original writer and changing only results in waste of time.

Be accurate and consistent. Avoid substituting a new set of mistakes or inconsistencies for those originally present.

Be well informed. An editor should be an expert in:

- Good grammar
- Style-guide rules
- Standard editing marks
- Security regulations and contractual requirements
- Specifications and deviations applicable
- Technical aspects of equipment or system involved

If the editor is not an expert in all these subjects, then he should take steps to become one.

Be alert for alternatives

If one edit of a manuscript is not satisfactory to the writer, don't revert to the original version without further effort. A large number of accurate alternative wordings and arrangements may be found which satisfy both writer and editor. Remember that the manuscript is basically the writer's responsibility and he must also be happy with the final version. It is, in turn, the writer's responsibility to make sure that the edit does not inadvertently change the meaning of the technical data.

REFERENCES FOR EDITING

U. S. Government Printing Office Style Manual, including Word Division, Supplement
Webster's New International Dictionary
Nicholson's A Dictionary of American-English Usage, Oxford University Press
Specificaitons or deviations as applicable
Project-specific style guide or usage list
Panel nomenclature

PROOFREADING

Proofreading of final copy should be a challenge to the writer, the editor, the typist, the illustrator. The goal of 100-percent correspondence with input (manuscript and edit) is difficult but with sufficient concentration and systematic application it can be achieved within a reasonably close tolerance.

Proofreading is unique to each manual, but in general includes checking for correspondence in:

Spelling
Uppercasing and lowercasing
Punctuating
Hyphenating
Spacing
Indenting
Formatting
Sequencing

Placing Illustrations
Paging
Alining information in tabular materials (vertically and horizontally)
Editing
Separating words correctly
Checking running heads and feet
Collating

When proofreading final copy, be careful to preserve the final page and use whatever method has been set up for corrections on that manual. These may include:

- Overlays
- Blue pencil
- Attached notes
- Margin markings
- Copies

If editing of final copy is necessary, editing should be performed on copies of the final copy so that a record of changes from the manuscript and draft is available.

Methods of proofreading.

Proofreading can be done in various ways:























- a. By 100-percent comparison between manuscript and final copy - line by line, word by word, carefully observing every letter, every space, every punctuation mark. This type of proofreading is suitably performed by someone not familiar with the contents of the manual, as a typist or other person with training in objective observation and comparison. This method is best done by placing the manuscript and the copy side by side and using a ruler on each to pace the corresponding lines or elements.
- b. By mechanical scanning for completeness. For example, if the manuscript contains a table which in column two has 17 entries, count the number of entries in that column in final copy. This method points out omissions quickly and might be used as a check when skimming as described in method 3.
- c. By skimming the items of critical importance on a page - panel nomenclature, numerical values, tolerances, procedural instructions, critical information. This type of proofreading should be reserved for the writer who is thoroughly familiar with the content and capable of selecting the items of criticality.
- d. By careful reading of final copy and spot-checking against input. This type of proofreading could be done by the writer or by an editor thoroughly familiar with the subject of the content and capable of understanding the technical intricacies of the text.
- e. By two people - one reading out loud the manuscript, item by item; the other following in the final copy for compliance with the revision being read. For text, this type of proofreading is time-consuming and inefficient because it takes time to enunciate properly and concentration to listen and observe attentively. However, for long columns of numbers, wiring lists, or symbols, where correspondence from manuscript to final copy is necessarily checked in very short time intervals, the two-people approach for proofreading is recommended.
- f. By all of above methods, or any combination of them.

Iterations of proofreading

The first proofreading is to compare the final copy with original manuscript. When discrepancies are found, these are corrected (using the proper edit marks) and the manual is resubmitted to production for corrections. the correctons may be made by mortising (cut and paste), or by retyping. this type the correction of errors is checked against the marked copy, plus any new errors generated by retyping. This process continues until all errors have been satisfactorily corrected in accordance with instructions.

EDIT MARKS





BRIEF SUMMARY OF EDIT AND PROOFREADER'S MARKS

	Insert period		Caps - used in text
	Insert comma	<i>Cape</i> - - - - -	Caps - several letters or words
:	Insert colon		Add space between lines
;	Insert semicolon		Close up
-	Insert hyphen	 or 	Delete
'	Insert apostrophe		Move right
	Insert space		Move left
()	Parentheses		Move up
[]	Brackets		Move down
¶	Paragraph		Aline vertically
	No paragraph		Aline horizontally
 or 	Transpose		Center horizontally
	Interchange c with a		Center vertically
	Spell out	<i>stat</i>	Let it stand - used in text
	Boldface - used in text		Caret - General indicator used to mark exact positin of insertion or error in text.
<i>l.c.</i> - - - or /	Lowercase		













STANDARD EDIT MARKS

The following chart gives the edit marks most commonly used. If you need additional ones, consult the *GPO Style Manual* or *Webster's New Collegiate Dictionary*. Remember the purpose of edit marks is to communicate the desired changes; the more clearly the mark is written, the more likely others are to understand your change correctly. Strive for clarity in marking a manuscript.

Edit Change	Symbol	Examples/Precautions/Remarks
Add a period	⊙	Circle is necessary so dot is not overlooked.
Move a period to new position	⋈ ⊙	Like this: ...remove cable connectors, <i>from component</i> ⊙ Not this: ...remove cable connectors, <i>from component</i>
Change period to a comma	⋈	...
Change period to a colon	⋈	Add dot <u>above</u> period.
Change period to a semicolon	⋈	Change period to comma, add period <u>above</u> comma. Do not add comma below period because it may be overlooked when typist uses a mechanical paper holder.
Add a comma	,	Add directly. Do not use long curved line that can be mistaken for parenthesis.
Add a hyphen	⋈	Use caret so edit is clearly visible. Like this: receiver⋈transmitter Not this: receiver-transmitter
Add parentheses	()	Insert directly, neatly, like this: Remove setscrew (9) that locks adjustment nut (10) in place.
Add quotation marks	“ ”	Insert directly like this: The circuit provides a corrective "jizzle" voltage.
Add apostrophe	⋈	Use caret downward like this: Operator's indicator
Add word(s)	⋈	Use caret to show place of new word (or words) like this: In the <i>first</i> setting of the switch the . . .

Edit Change	Symbol	Examples/Precautions/Remarks
Delete word(s), part of words, or punctuation marks	 or (depending on space available)	Run the deletion mark <u>through</u> the unwanted items like this: ...and depression of the GYRO ERECT button before closing the . . . <hr/> Not either of these: ...and depress GYRO ERECT button before closing theand pression of the GYRO ERECT button before closing the . . .
Close up space (long space)		When several words have been deleted and no new words substituted, show the new spacing, like this: To install 12A1, and 12A2, two men are required.
Close up space (short space)		cut ^u ff, one word cut ^u ff, delete hyphen, one word preced ^u ing, delete extra letter and close up space.
Substitute new word (s)		Delete unwanted words and indicate with a caret where the wanted word goes, like this: In this setting, the breaker ^{protect} is used as an overload protection device for the control circuit wiring . . . Be careful to put the substituted words where they will be noticed during typing. <u>Not</u> like this: In this setting, the breaker serves as an ^{protect} overload protection device for the control circuit wiring . . .
Add a lengthy piece of text	Use separate 8-1/2 x 11 sheet	Insert new sheet <u>ahead</u> of pages to be changed. Do <u>not</u> : <ul style="list-style-type: none"> • Attach a flap that must be raised to read text underneath. • Use the back side of any sheet. Both of these practices <u>may</u> cause typing errors.

Edit Change	Symbol	Examples/Precautions/Remarks
Correct a spelling		Delete misspelled word and write correct spelling like this:
		Where space is limited, correct letter only, like this:
		Do <u>not</u> write over a letter, like this:
		or put the correction below where it is less easily noticed, like this:
Indicate place for illustration/table		
Indicate place for incorporating added insert on separate page		
Change lowercase to capital		Use triple line under letter(s) if few letters are involved, like this:
		Use dotted line and "caps" if a longer series of words needs to be capitalized, like this: <p style="text-align: center;">Section IX <u>Reassembly and Testing of Component</u> caps</p>
Lowercase a letter		
Lowercase all caps		
Insert space between letters/words/dashes		

Edit Change	Symbol	Examples/Precautions/Remarks								
Add space between lines		X to indicate number of lines to be left blank								
Change position of letters/punctuation		<p>SECTION IX REASSEMBLY AND TESTING OF COMPONENT 9-1. REASSEMBLY.</p> <p>section - to get section "lock" - to get "lock."</p>								
Change position of words		<p>For consecutive words like: Fault <u>procedure</u> <u>isolation</u></p>								
		for: Fault isolation procedure.								
		<p>For separated words like <u>elevation</u> <u>and</u> <u>azimuth</u> to get azimuth and elevation.</p>								
		<p>Be careful not to do this: <u>elevation and</u> <u>azimuth</u> which would read "azimuth elevation and"</p>								
Change sequence of lines		<p>S2 ON. S3 OFF.</p>								
Move data to left		<p>5-1. Remove dust, dirt, and lint from all parts and wiring with a clean, dry brush.</p> <p>Remove grease or oil smudges from all electrical parts with a clean, lint-free cloth.</p>								
Move data to right		<p>5-1. Remove dust, dirt, and lint from all parts and wiring with a clean, dry brush.</p> <p>Remove grease or oil smudges from all electrical parts with a clean, lint-free cloth.</p>								
Center data/heading		<p>SECTION IX REASSEMBLY AND TESTING OF UNIT</p>								
Move data up		<table border="1"> <tr> <td data-bbox="837 1388 1000 1524">System completely inoperative or unstable in operation</td> <td data-bbox="1016 1388 1049 1461">1</td> <td data-bbox="1065 1388 1146 1524">J201 J304</td> <td data-bbox="1162 1388 1308 1482">Connect multimeter for d-c voltage</td> </tr> <tr> <td data-bbox="837 1535 1000 1566">System in warmup mode</td> <td></td> <td></td> <td></td> </tr> </table>	System completely inoperative or unstable in operation	1	J201 J304	Connect multimeter for d-c voltage	System in warmup mode			
System completely inoperative or unstable in operation	1	J201 J304	Connect multimeter for d-c voltage							
System in warmup mode										
Move data down										
Start new paragraph		<p>SAFETY WIRING. Replace safety wiring through clamp screws around motor B3901(1), . . .</p>								
Combine two paragraphs		<p>8-19. SAFETY WIRING. Replace safety wiring through clamp screws around motor 901(1), . . .</p>								

Edit Change

Symbol

Examples/Precautions/Remarks

Align margin




1-5. **MODES OF OPERATION.** The system has three basic modes of operation:

1-6. **AUTOMATIC SEARCH.** During search, the antenna . . .

1-7. **MANUAL SEARCH.** After a target has been selected during automatic search, manual search . . .

Pin	Voltage	
	Indication	Meter Scale
1	310	0-1200
2	0.5	0-3
3	6.3 V ac	0-12
3-4	11	0-300
4	6.3 V ac	0-12
4-3	11	0-300
5	230	0-300
6	0	0-3
7	300	0-1200



Query possible error, inconsistency



Arrow pointing to questioned item.

Delete an edit

*----- stet
(let it stand)*

Place dotted line under item to be left in original form, like this:

. . . , as shown in figure ~~5-4~~ ^{5-5 stet} which makes it read:

. . . , as shown in figure 5-4.


NOTE

Avoid confusion by using "stet" one time only; do not change back and forth. If necessary, rewrite final version.

Convert to boldface



LUBRICATION becomes **LUBRICATION**

Edit Change	Symbol	Examples/Precautions/Remarks
Convert to list style		<p>Whenever enumerating three or more items, the list style is preferred.</p> <p>Example:</p> <p>The front panel handle, two elapsed-time meters, and two indicator lamps.</p> <p>This becomes:</p> <p>The front panel contains: handle two elapsed-time meters two indicator lamps</p> <p>This can be further "improved" to:</p> <p>The front panel contains:</p> <p>(two) elapsed-time meters (two) indicator lamps</p> <p>which then reads:</p> <p>The front panel contains: handle elapsed-time meters (two) indicator lamps (two)</p>

Close up space between lines

((

REASSEMBLY AND TESTING

9-1. Reassembly.

Section 20

LEXICON

The following list of familiar words (item 1) and preferred verbs (item 2) shall be used as a guide to simplify readability and comprehensibility of the manuals. These words should be used wherever possible. However, additional words may be used as needed by

the intended user or peculiarities of the equipment. The procuring activity must approve the use of added words. Mandatory words, i.e., nomenclature and technical designations, are not included.

1. Familiar Words.

A			
a	after	aloud	apron
able	afternoon	already	are
abnormal	afterward	also	area
aboard	again	always	aren't
about	against	ammunition	arise
above	age	among	arithmetic
absent	aged	amount	a.r.m
accept	ago	an	armful
access	agree	and	army
accident	ahead	another	arose
accord	aid	answer	around
accordance	aim	any	arrange
account	air	anybody	arrive
acre	aircraft	anyhow	arrow
across	airfield	anyone	article
act	airplane	anything	as
action	airport	anyway	aside
active	airship	anywhere	ask
add	air	apart	assemble
addition	alarm	apiece	associate
additional	alike	appear	at
address	all	appearance	attach
advantage	allow	application	attack
afar	almost	apply	attempt
affect	alone	approach	attend
	along	approximate	

MIL-HDBK-63038-2 (TM)

attention	bath	between	both
auto	bathe		bottle
automatic	battle		bottom
automatically	battleship	big	bought
automobile	bay	bill	bounce
available	be	bin	bow
away	beach	bind	bowl
	bead	bit	box
awhile	beam	bite	boxcar
ax	bean	biting	brake
		bitter	
		black	branch
		blackboard	brass
		blade	break
		blank	breath
		blanket	breathe
		blast	breeze
		blaze	brick
		bleed	bridge
		blew	brief
		blind	bright
		blindfold	brightness
		block	bring
		blood	broad
		blot	broadcast
		blow	broke
		blue	brook
		board	broom
		boat	brought
		bob	brown
		body	brush
		boil	bubble
		bolt	bucket
		bond	buckle
		book	bud
		boom	build
		boot	building
		borrow	built
			bulb

B

back	beat		
background	became		
backward	because		
bad			
badge	become		
	becoming		
bag	been		
bake	before		
baking			
balance			
ball	began		
	begin		
balloon	beginning		
band	begun		
bandage			
bang			
bank	behind		
	believe		
bar	bell		
bare	belong		
	below		
barrel	belt		
	bench		
base	bend		
basement	beneath		
basic	bent		
basis			
basket	beside		
	best		
bat	bet		
batch	better		

couldn't	daily	destroy	doesn't
count	dam	detach	dolly
counter	damage	dew	done
country	damp	dial	don't
course	danger	diamond	door
court	dare	diameter	doorknob
cover	dark	did	doorstep
crack	dart	didn't	dot
cradle	dash	die	double
cramp	date	difference	down
crank	dawn	different	downstairs
crash	day	difficult	downtown
crawl	daybreak	difficulty	dozen
creek	daytime	dig	drag
creep	dead	dim	drain
crept	deaf	dip	drank
crew	deal	direct	draw
crewmember	death	direction	drawer
cross	decide	dirt	drew
crowd	deck	disable	dried
crown	decrease	disadvantage	drift
 	deed	disassemble	drill
crumble	deep	discover	drink
crush	defeat	discard	drip
crust	defend	discharge	drive
cube	defense	disconnect	driver
cuff	degree	discontinue	drop
cup	delay	dish	drove
cupful	delight	dislike	drown
cure	deliver	dismiss	drowsy
curl		distance	drug
curtain	depart	distribute	drum
curve	depend	ditch	drunk
cushion	deposit	dive	dry
cut	describe	diver	duck
cutting	desert	divide	due
	D	do	dug
	deserve	dock	dull
dab	desire	does	dumb
	desk		

dump	entrance	fail	final
during	envelope	failure	finally
dust	equal	faint	find
duty	equip	fair	fine
dwelt	equipment	fake	finger
dwelt	erase	fall	finish
	E		
	error	false	fire
each	escape	fan	firearm
ear	especially	far	firing
early	estimate	faraway	first
earn	eve	fare	fist
earth	even	far-off	fit
	evening	farther	five
east	ever	fashion	fix
easy	every	fast	flag
edge	everybody	fasten	flake
effect			
effort	everyday	fastener	flame
	everyone	fault	flap
eight	everything	fear	flash
eighteen	everywhere	feather	flashlight
eighth	exact	fed	flat
eighty			
either	examination	feed	flesh
	examine	feel	flew
elbow	except	feet	flies
electric	exchange	fell	flight
electrical	excited	fellow	flip
electricity			
eleven	excuse	felt	flip-flop
	exercise	female	float
else	exit	fence	flood
elsewhere	expect	few	floor
emergency	explain	field	flop
empty			
end	extra	fifteen	flow
	eye	fifth	flutter
enemy		fifty	fly
engine		fight	foam
engineer		figure	fog
enough			
enter	face	file	foggy
	facing	fill	fold
entire	fact	film	follow
	factory		
	F		

foot	further		government	hairpin
for	future		grab	half
force	fuzzy		grade	hall
forehead			grain	halt
forest		G	grand	hammer
forget	gain		grasp	hand
forgot	gallon		grass	handful
fork	game		grave	handle
form	gang		gravel	handwriting
fort	garage		gray	hang
forth	garbage			happen
forty	gas		grease	harbor
forward	gasoline		great	hard
fought	gate		green	hardly
found	gather		greet	hardship
fountain	gave		grew	hardware
four	gear		grind	harm
fourteen	general		groan	harness
fourth	gentle		ground	has
frame	get		group	hasn't
free	getting		groove	haste
freedom	giant		grove	hasty
freeze	give		grow	hat
freight	giving		growth	hatch
frequent	glance		guard	hatchet
fresh	glass		guess	haul
fried	gleam		guidance	have
friend	glide		guide	haven't
	glove		gulf	having
frighten	glow		gum	he
frog	glue		gun	head
from	go		gunpowder	
front	goes			
frost	goal			H
froze	gold			health
			habit	heap
fuel	gone		had	hear
full	good		hadn't	heard
fur	got		hail	heart
furnish	govern		hair	heat

heavy	home	Ill	invite
heel	honk	I'll	iron
height	hood	I'm	is
held	hoof	immediate	island
	hook	importance	isn't
	hoop	important	it
helmet	hop	impossible	item
help	horizontal	improve	its
helpful	horn	in	It's
hem	hose	inaction	itself
	hot	inactive	I've
here	hound	inch	ivory
here's	hour	include	
	how	income	
hickory	however	increase	J
hid			
	howl	indeed	jacket
hidden	hug	indicate	jack
hide	huge	indication	jail
high	hum	indoors	jam
highway	hump	information	jar
hill			
	hundred	injure	jaw
hillside	hung	injury	jelly
hilltop	hunk	ink	jerk
hilly	hunt	inlet	jet
him	hurried	input	jig
himself			
	hurry	insect	job
hind	hurt	insert	jockey
hinge	hush	inside	join
hint	hut	inspect	joint
hip			journey
hire			
		I	
		inspection	judge
		instant	jug
hiss	I	instead	jump
history	ice	instruct	
hit	icy	instruction	junk
hitch	I'd		
	idea	intake	just
holddown		intend	
hold	ideal	interested	K
hole	idle	interesting	
hollow	if	into	keen

keep	late	like	lumber
kept	laundry	likely	lump
kettle	lay	liking	lying
key	lazy	limb	
kick	lead	lime	M
kill	leader	limit	machine
kind	leaf	limp	machinery
kit	leak	line	made
kite	lean	lip	magazine
knee	leap	list	mail
kneel	learn	listen	mailbox
knew	least	lit	main
knife	leather	little	major
knit	leave	live	make
knives	leaving	lively	making
knob	led	living	male
knock	left	load	
knot	leg	loaf	manager
know	lend	loan	manner
known	length	loaves	many
	L	locate	map
	lengthen	location	maple
lace	less	lock	marble
	lesson	locomotive	march
ladder	let	log	mark
laid	let's		
lake	letter	lone	mask
	letting	long	mast
lame	level	look	master
lamp	lever	lookout	mat
land	library	loop	match
lane			
language	lice	loose	mate
	license	loosen	material
lantern	lick	lose	matter
lap	lid	loss	mattress
lard	lie	lost	maximum
large			
lash	life	lot	may
	lift	loud	maybe
last	light	low	me
latch	lightning	lower	meal

mean	mixture	neat	nurse
meant	moment	necessary	nut
measure	month	neck	
meat	moon	need	
mechanical	moonlight	needle	O
meet	mop	needn't	oak
melt	more	neither	oar
member	morning	nest	obey
men	moss	net	observe
mend	most	neutral	ocean
mess	motion	never	occur
message	motor	new	o'clock
met	mount	next	odd
metal	mountain	nickel	of
method	mouth	night	off
middle	move	nine	offer
midnight	movement	nineteen	office
might	moving	ninety	officer
mile	mow	no	often
milk	much	nobody	oil
			old
mill	mud	nod	old-fashioned
millier	muddy	noise	omit
million	mug	noisy	on
mind	mule	non	once
mine	multiply	noon	
miner	must	nor	one
minimum	my	normal	only
minor	myself	north	onward
mint		nose	open
minute		not	openings
mirror	nail	note	opposite
misfit	name	nothing	or
misplace	narrow	notice	orange
miss	nation	now	order
mistake	national	nowhere	ordinary
misty	navy	number	ore
mitt	near	numeral	organ
mitten	nearby	numerical	other
mix	nearly	numerous	otherwise
			ought

N

our	pane	pick	post
ourselves	panel	picture	pot
out	paper	piece	pound
outdoors	paragraph	pile	pour
outfit	park	pilot	powder
outlet	part	pin	power
outline	particular	pine	practice
output	partner	pink	prepare
outside	pass	pint	present
outward	passenger	pipe	press
oven	past	pistol	pressure
over	paste	pit	prevent
overall	pat	pitch	prick
overalls	patch	place	print
overcoat	path	plain	probable
overcome	patter	plan	probably
overhead	pave	plane	problem
overhear	pavement	plant	prompt
overheat	paw	plate	proper
overload	pay	platform	protect
overnight	payment	platter	protection
oversize	pea	play	prove
overtighten	peace	plenty	public
overturn	peak	plow	puddle
own	pear	plug	puff
	peck	pocket	pull
	peculiar	point	pump
pace	pedal	poison	punch
pack	peg	poke	pupil
package	pen	pole	pure
pad			
page	pencil	police	purple
	people		purpose
pail	per	pond	purposely
pain	percent	pool	push
paint	perhaps	poor	put
painting			putting
pair	period	pop	
	permit	popped	
pale	person	portion	
pan	phone	possible	

Q

MIL-HDBK-63038-2 (TM)

scrape	settlement	shot	skip
scratch	seven	should	skirt
scream	seventeen	shoulder	sky
screen	seventh	shouldn't	slam
screw	seventy	shout	slap
screwdriver	several	shovel	slate
scrub	sew	show	slave
sea	shade	shower	sled
seal	shadow	shut	sleep
seam	shady	sick	sleeve
search	shake	side	slept
season	shaking	sidewalk	slice
seat	shall	sideways	slid
second	shape	sight	slide
secret	share	sign	slight
secure	sharp	silence	sling
see	shave	silent	slip
seed	shear	silk	slipped
seek	shed	sill	slippery
seem	sheet	silver	slit
seen	shelf	similar	slow
seesaw	shell	simple	small
select	shield	since	smell
self	shift	sing	smoke
send	shine	single	smooth
sense	shining	sink	snail
sent	shiny	sip	snap
sentence	ship	sir	snapping
separate	shipment	sit	snow
separation	shut	site	snug
serial	shock	sitting	so
series	shoe	situation	soak
serious	shone	six	soap
serve	shook	sixteen	sod
service	shoot	sixth	soft
serviceable	shop	sixty	soil
set	shore	size	soldier
setting	short	skim	sole
settle	shortage	skin	solid

solve	stair	stove	sunshine
some	stake	straight	suppose
somebody	stall	straighten	sure
somehow	stamp	strange	surface
someone	stand	strap	surplus
something	star	straw	swallow
sometime	stare	stream	swam
somewhere	start	street	swamp
soon	starve	strength	swat
sort	state	stretch	sweep
sound	station	strict	sweet
sour	stay	string	swell
south	steamer	strip	swept
space	steel	stripes	swift
spade	steep	strong	swim
spare	steeple	stuck	swimming
spark	steer	study	swing
speak	stem	stuff	switch
spear	step	stump	sword
special	stepping	stung	
speech	stick	subject	
speed	stiff	substance	tab
spike	still	substitute	table
spill	sting	such	tablespoon
spin	stir	suck	tablet
splash	stitch	sudden	tack
spoil	stock	suffer	tag
spoke	stocking	suggest	tail
spoon	stone	suggestion	tailor
spot	stood	suit	take
spread	stool	sum	taking
spring	stoop	summary	talk
sprinkle	stop	summer	tall
square	stopped	sun	tan
squeak	stopping	sunk	tank
squeeze	store	sunlight	tap
stable	storm	sunny	tape
stack	story	sunrise	tar
stage		sunset	task

T

MIL-HDBK-63038-2 (TM)

taste	those	torn	tune
tax	though	toss	tunnel
team	thought	touch	turn
tear	thousand	tow	twelve
teaspoon	thread	toward	twenty
teeth	three	towel	twice
telephone	threw	tower	twig
tell	throat	town	twin
temperature	through	trace	twine
ten	throw	track	twist
tent	thumb	tractor	two
tenth	thunder	trade	type
term	tick	trail	typical
test	tie	trailer	
than	tight	train	U
that	tighten	transfer	umbrella
that's	till	transport	uncover
the	time	transportation	under
their	tin	trap	understand
them	tiny	travel	underwater
then	tip	tray	unfinished
there	tire	three	unfold
these	tired	tried	uniform
they	title	trigger	unit
they'd	to	trim	United States
they'll	toe	trip	unimportant
they're	together		unknown
they've	told	trouble	unless
thick	ton	truck	unlock
thimble	tone	true	unpainted
thin	tongue	truly	unsafe
thing	too	trunk	unsatisfactory
think	took	trust	unscrew
third	tool	truth	unserviceable
thirsty	toolbox	try	unslung
thirteen	toot	tub	unsnap
thirty	toothpick	tube	until
this	top	tug	unusual
thorough	tore	tumble	unwilling

up	wall	west	wish
upon		wet	with
upper	want	we've	within
uppermost	war	what	without
upset	warm	what's	withstand
upside	warn	wheel	won
upward	was	when	wonder
us	wash	whenever	won't
use	washtub	where	wood
useful	wasn't	which	woods
useless	waste	while	wool
usual	watch	whip	woolen
		whipped	word
	water	whirl	wore
	waterproof	whisper	work
valley	wave	whistle	workman
value	wax	white	world
valuable	way	who	worm
various	wayside	who'd	worn
vary	we	whole	worse
vehicle	weak	who'll	worst
vent	weaken	whom	worth
vertical	weapon	who's	would
very	wear	whose	wouldn't
vessel	weary	why	wove
view	weather	wide	wrap
village	weave	width	wrapped
vine	web	wiggle	wreck
violet	we'd	will	wrench
voice	wee	willing	wring
volume	weed	win	write
	week	wind	writing
	weigh	window	written
	weld	wing	wrong
	well	wingnut	wrote
wag			wrung
wagon			
waist	we'll	winter	
wait	went	wipe	Y
wake	were	wire	
walk	we're	wise	yard
yarn	yet	you're	Z
year	you	yourself	
yell	you'd	yourselves	zero
yellow	you'll	you've	zone
yes	your		

2. Preferred Verbs.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Add	To put more in.	Add water to the battery.
Adjust	1. To bring to a specified position or state. 2. To bring to a more satisfactory state; to manipulate controls, levers, linkages, etc., to return equipment from an out-of-tolerance condition to an in-tolerance condition.	1. Adjust the micrometer to the given measurements. 2. Adjust cable tension using the turnbuckles.
Advance	To move forward; to move ahead.	Advance the throttle.
Aid	To give help or support to; to assist.	Aid man B to lift the load.
Alert	To warn; to call to a state of readiness or watchfulness; to notify (a person) of an impending action.	Alert personnel that area will be cleared.
Aline	To bring into line, to line up; to bring into precise adjustment, correct relative position, or coincidence.	Aline slot in turnbuckle barrel with slot in cable terminal.
Allow	1. To permit, to give opportunity to. 2. To allot or provide for.	1. Allow the sediment to settle out. 2. Allow a 2-inch slack in the rope.
Apply	1. To lay or spread on. 2. To energize.	1. Apply sealant to gap between the windshield and the aircraft structure. 2. Apply power or load.
Arrange	To group according to quality, value, or other characteristics; to put in proper order.	Arrange components by size from smallest to largest.
Assemble	To fit and secure together the several parts of; to make or form by combining parts.	Assemble a jet engine in accordance with specified procedures.
Assign	To apportion to for a specific purpose or to particular persons or things; to appoint to a duty.	Assign the various maintenance tasks to technicians.
Assist	To give support or help; to aid.	Assist man B to lift the antenna.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Assure	To make someone sure or certain, to inform positively.	Assure other technicians that all warning lights are off.
Attach	To join or fasten to.	Attach electrical leads to the multi-meter.
Back off	To cause to go in reverse or backward.	Back off nut to the nearest castellation.
Balance	To equalize in weight, height, number, or proportion.	Balance aircraft so that it is stable.
Be sure	To confirm that a proper condition exists, to find out with certainty.	Be sure that the light is off.
Be careful	To exercise caution, to take care.	Be careful not to inhale the fumes of the solvent.
Bend	To turn or force from straight or even to curved or angular; or to force back to an original straight or even position.	Bend wire until it lies flat against the turnbuckle wall.
Bleed	To extract or let out some or all of a contained substance from.	Bleed off tank air pressure.
Blow	To send forth air, particularly from the lungs through the mouth.	Check for obstructions by disconnecting the hose at the air inlet and blowing through it.
Break	1. To separate into parts with suddenness or violence. 2. To pull away.	1. Never break safety wire to release air pressure. 2. Break the bead of the wire.
Calibrate	To determine accuracy, deviation, or variation by special measurement or by comparison with a standard.	Calibrate torque handles at least once each month so that the accuracy can be depended upon.
Cap	To provide with a covering; to install or provide with a device for closing off the end of a tube which has a male fitting.	Cap all lines which have exposed male fittings.
Catch	To prevent from falling to the ground, to capture.	Catch any fluid drippings in a pan.
Center	1. To adjust so that axes coincide. 2. To place in the middle of.	1. Center the nose wheel of the aircraft. 2. Center the pointer on the dial.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Change	To replace with another comparable item; to substitute serviceable equipment for malfunctioning, wornout, or damaged equipment.	Change the switch contact points.
Charge	To restore the active materials in a storage battery by the passage of a direct current through in the opposite direction to that of the discharge.	Charge the battery for a short time before making a specific gravity check.
Check	1. To confirm or establish that a proper condition exists; to ascertain that a given operation produces a specified result; to examine for satisfactory accuracy, safety or performance; to confirm or determine measurements by use of visual or mechanical means.	1. Check that the light is off.
	2. To perform a critical visual observation or check for specific conditions; to test the condition of.	2. Check the components for wear, deterioration or defects.
Check out	To perform specified operations to verify operational readiness of a subcomponent, component, subsystem, or system,	Checkout the landing gear.
Choke	To enrich the fuel mixture of a motor by partially shutting off the air intake of the carburetor.	Choke engine as required to start.
Clamp	To fasten or press two or more parts together so as to hold them firmly.	Clamp the tensiometer to the cable by releasing the handle slowly.
Clean	To wash, scrub, or apply solvents to; remove dirt, corrosion, or grease.	Clean petroleum products from oxygen equipment.
Clear	1. To move people and/or objects away from.	1. Clear the area.
	2. To open the throttle of an idling engine to free it from carbon.	2. Clear the engine.
Close	1. To block against entry or passage; to turn, push, or pull in the direction in which flow is impeded.	1. Close the valve.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
	2. To set a circuit breaker into the position allowing current to flow through.	2. Close the circuit breaker.
Coat	To cover or spread with a finishing protecting layer.	Coat battery cables with grease.
Code	To put into the form or symbols of a system used to represent words; to mark with identifying symbols.	Color code equipment parts.
Collect	To bring together into one body or place; to accumulate.	Collect the required hand tools.
Compare	To examine the character or qualities of two or more items to discover resemblances or differences.	Compare the readings from protractor and template.
Conduct	To lead, manage, or direct.	Conduct the class in proper servicing procedures.
Connect	1. To bring or fit together so as to form a unit, to couple keyed or or matched equipment items. 2. To attach or mate (an electrical device) to a service outlet.	1. Connect the torquemeter to the socket wrench. 2. Connect the soldering iron to the service power outlet.
Control	To exercise restraining or directing influence over, to fix or adjust the time, amount, or rate of.	Control electrical current generation and distribution.
Correct	To make or set right; to alter or adjust so as to bring to some standard or required condition.	Correct any error before proceeding with activity.
Cover	To protect or shelter by placing something over or around.	Cover tires whenever maintenance is done on the aircraft.
Crack	To open slightly (the throttle) of an aircraft engine preparatory to starting the engine.	Crack and lock the throttle to 1/4 open.
Crimp	To compress or deform a connection barrel around a cable to make an electrical connection.	Crimp a connector on the yellow wire.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Cut	To divide into parts using a sharp instrument such as a scissors or knife.	If the prongs of the cotter pin are too long, they should be cut to proper length.
Cycle	To operate an item through its entire range.	Cycle the landing gear from the up position to the down (locked) position and back to the original position.
Destroy	To ruin, demolish, or put out of existence; to make unfit for further use.	Destroy used hydraulic fuel containers.
Disassemble	To take to pieces; to take apart to the level of the next smaller unit or down to all removable parts.	Disassemble the No. 1 engine.
Disconnect	1. To sever the connection between; to separate keyed or matched equipment parts.	1. Disconnect the bleedair hose from the leading edge anti-icing system.
	2. To detach or separate (an electrical device) from a service outlet.	2. Disconnect the soldering iron from the service power outlet.
Disengage	To release or detach interlocking parts, to unfasten; to set free from an inactive or fixed position.	Disengage the parking brake.
Dispose of	To get rid of.	Dispose of unused hydraulic fluid left in the can.
Drain	To draw off (liquid) gradually or completely.	Drain servicing hose after removing it from the filter valve.
Dry	To cause to be free from water or liquid.	Dry bearings with low-pressure air.
Enter	1. To go or come in.	1. Enter the aircraft through the troop doors.
	2. To put on record.	2. Enter the data on the form.
Erect	To put up by fitting together.	Erect a special maintenance stand.
Examine	To perform a critical visual observation or check for specific conditions; to test the condition of.	Examine the component for wear, deterioration or defects.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Extend	To cause to be drawn out to fullest length.	Extend the main landing gear.
Fabricate	To construct from standardized parts.	Fabricate rig pins from 0.25 inch rod.
File	To rub smooth or cut away with a file (i.e., a tool with cutting ridges for forming or smoothing surfaces).	File one end of the rod to a point.
Fill	To put into as much as can be held or conveniently contained.	Fill oil and deicing tanks.
Find	1. To discover or determine by search; to indicate the place, site, or limits of. 2. To discover by study or experiment; to investigate and decide.	1. Find the No. 9 fitting. 2. Find the amount of tension on a cable by following specified procedures.
Flush	To pour liquid over or through; to wash out with a rush of liquid.	Drain and flush the hydraulic system if it has been serviced with a wrong fluid.
Fold	To lay one part over another part of, to reduce the length of bulk by doubling over.	Fold sides of curtain on creases.
Follow	To accept as authority, to obey; to conform with directions or rules.	Follow directions.
Form	To give a particular shape to; to shape or mold into a certain state; to make up.	Form the compound so that it will fill the hole completely.
Furnish	To supply what is needed, to equip.	Furnish a flashlight for man B.
Go to	To proceed to; to transport oneself to a given destination.	Go to the control pedestal and position switches appropriately.
Ground	To connect a current, wire, or a piece of electrical equipment to a land or other specified surface.	Ground the servicing cart.
Guard	To protect from danger, to defend.	Guard the area while maintenance is taking place.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Guide	To manage or direct the movement of.	Guide the maintenance stand safely to its new position.
Hand	To give, pass, or transmit with the hands.	Hand the refueling hose to the technician stationed on the wing.
Handle	To manipulate (load, turn, raise, etc.) objects and equipment manually or with specially designated equipment, such as hoists.	Handle charger cylinders carefully.
Hang	To fasten to some elevated point without support from below, to suspend.	Do not hang tools on projecting parts of the aircraft.
Help	To give support, aid, or assistance to.	Help man B lift the load.
Hold	To have or keep in the grasp.	Hold the power switch in position until the voltmeter stabilizes.
Identify	1. To establish the identity of. 2. To determine the classification of a supply item.	1. Identify components by name and function. 2. Identify the component to be ordered from supply.
Idle	To run an aircraft engine under reduced power without sufficient power being developed for movement of the aircraft.	Idle the engine for 5 minutes at 800 rpm.
Improve	To make greater in amount or degree; to make better.	Improve procedures whenever feasible.
Indicate	To point out.	Indicate which dial should be monitored.
Inflate	To fill with a given amount of gas or air.	Inflate tire to desired pressure.
Inform	To make known to; to give notice, or report the occurrence of.	Inform man B that the brakes have been set.
Insert	To put thrust in, into, or through.	Insert a wire through the hole in the turnbuckle.
Inspect	To perform a critical visual observation or check for specific conditions, to test the condition of.	Inspect the components for wear, deterioration or defects.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Install	1. To perform operations necessary to properly fit an equipment unit into the next larger assembly or system. 2. To place and attach.	1. Install fuel manifold. 2. Install nuts on bolts.
Insure	To make certain, to ensure.	Insure that the area is clear of unnecessary personnel and equipment.
Investigate	To observe or study by close examination and systematic inquiry.	Investigate the cause of the breakdown.
Isolate	To use test equipment to identify or select a source of trouble.	Isolate the source of the malfunction using pressure gages.
Jack	To use one or more jacks (i.e., mechanisms for exerting pressure to lift all or part of an aircraft).	Jack and level the aircraft in accordance with specified procedures.
Join	To bring or fit together so as to form a unit; to couple keyed or matched equipment items.	Join the torquemeter to the socket wrench.
Keep	To remain, to continue in a place.	Keep away from the danger area.
Kick	To strike against with a foot.	Kick the wheel lightly if the strut binds.
Latch	To catch with a device which holds a door when closed, even if not bolted.	Close and latch the aft petal doors.
Leave	1. To go away from, depart. 2. To allot or provide for.	1. Do not leave the area until this activity is complete. 2. Leave a 2-inch slack in the rope.
Let	To permit; to give opportunity to.	Let the engine stabilize.
Level	To cause an aircraft to become even or parallel with the plane of the horizon.	Jack and level the aircraft in accordance with specified procedure.
Lift	To move or cause to be moved from a lower to a higher position; to elevate.	Lift the spoiler control lever to the ARMED position.
Light	To cause to illuminate.	Light the field indicator light.

MIL-HDBK-63038-2 (TM)

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Listen	To pay attention to sound.	Listen to the engine while it is operating.
Load	To place in or on a means of conveyance; to place cargo or aircraft components on an airplane or other vehicle.	Load and secure aircraft components on specified truck.
Locate	1. To find, determine, or indicate the place, site, or limits of. 2. To set or establish in a particular spot, to station.	1. Locate the No. 9 fitting. 2. Locate the test equipment so that it can be seen by both technicians.
Lock	To hold fast or inactive; to fix.	Lock the throttle after it has been properly set.
Look for	To visually search for.	Look for cracks, security, corrosion, and damage during inspection of wheels and tires.
Loop	To make into the form or shape of a loop (i.e., a fold, or doubling of line leaving an aperture between the parts through which another line can be passed).	Loop the wire.
Loosen	To release from restraint, to cause to become less tight fitting.	Loosen the locknut on the relief valve.
Lower	To cause to move down; to depress as to direction.	Lower the exhaust stack into the stowed position.
Lubricate	To put lubricant on specified locations.	Lubricate the wheel bearings.
Maintain	1. To hold or keep in any particular state or condition, especially in a state of efficiency or validity. 2. To sustain or keep up.	1. An aircraft mechanic maintains aircraft. 2. Maintain standard forms on power plant operation.
Make	To carry out or cause to occur.	Make corrections where necessary.
Mark	To label; to provide with an identifying or indicating symbol.	Mark each component before removing it.
Mate	To join or fit together, to couple.	Mate the torquemeter to the socket wrench.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Measure	To determine the dimensions, capacity, or amount by use of standard instruments or utensils.	Measure voltage drop across each unit of resistance.
Mix	To combine or blend into one mass.	Never mix oxygen with other gases.
Modify	To alter or change somewhat the form or qualities of.	A jet engine mechanic modifies turbofan engines.
Move	To change the location or position of.	Move and position a B-4 maintenance stand.
Notify	To make known to; to give notice or report the occurrence of.	Notify man B that the brakes have been set.
Observe	1. To conform one's actions or practice to.	1. Observe precautions.
	2. To visually take note of, to pay attention to.	2. Observe the indicator for changes in airspeed.
Obtain	1. To get or find out by observation or special procedures.	1. Obtain a reading on the outside circle of the tensiometer.
	2. To gain or attain.	2. Obtain the necessary supplies before starting on maintenance.
Open	1. To move from closed position; to make available for passage by turning in an appropriate direction.	1. Open the valve.
	2. To make available for entry or passage by turning back, removing, or clearing away.	2. Open the trap door.
	3. To disengage or pull.	3. Open the appropriate circuit breakers.
Operate	To control equipment in order to accomplish a specific purpose.	Operate crew stands and auxiliary power equipment.
Order	1. To requisition or request from supply.	1. Order three cans of appropriate solvent.
	2. To group according to quality, value, or other characteristics.	2. Order components by size from smallest to largest.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Organize	To arrange elements into a whole of interdependent parts; to form into a coherent unity; to integrate.	Organize the activities of the assisting technicians.
Overhaul	The act of disassembling equipment units down to all removable parts; cleaning; critically inspecting, repairing, restoring, and replacing where necessary; assembling, adjusting, alining, recalibrating, and verifying operational readiness by test or checkout; and packaging for transportation storage.	Overhaul the No. 2 engine.
Pack	To fill completely with grease.	Pack the bearings.
Paint	To apply color or pigment (suspended in suitable liquid) to the surface of.	Paint all exposed surfaces.
Park	To bring (an aircraft) to a stop and leave it standing for a time, usually without pilot, in a specified area.	Park the aircraft between the yellow lines.
Patch	To mend, cover, or fill up a hole or weak spot in.	Patch the tubes where necessary.
Perform	To do, carry out, or bring about; to reach an objective.	Perform a periodic inspection on the landing gear.
Place	To put or set in a desired location or position.	Place the test equipment so that it can be seen by both technicians.
Plan	To devise or project the achievement of.	Plan the day's schedule for the technicians.
Plug	To provide with a device for closing off the end of a tube which has a female fitting.	Plug all lines which have exposed female fittings.
Plug in	To attach or mate (an electrical device) to a service outlet.	Plug in the soldering iron at the service power outlet.
Position	To put or set in given place; to locate.	Position the test equipment so that it can be seen by both technicians.
Prepare	1. To make ready; to arrange things in readiness.	1. Prepare the surface for paint.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
	2. To prepare or make ready for a maintenance activity.	2. Prepare the Trunnion Shaft Kit for removal of the MLG shock strut.
Pre-set	To put in a desired position, adjustment or condition beforehand.	Pre-set tension indicator dial to size of cable being checked.
Press	To act upon through thrusting force exerted in contact.	Press the blower start button.
Pressurize	To apply pressure within by filling with gas or liquid.	Pressurize the booster hydraulic system.
Prevent	To keep from happening or existing.	Prevent oil from spilling over on components.
Process	To submit to a series of actions or operations leading to a particular end.	Process the forms so they will be compatible with new recording methods.
Provide	To supply what is needed, to equip.	Provide a flashlight for man B.
Pull	To exert force upon an object so as to cause motion toward the force.	Pull out knob no. 6 on the oxygen servicing cart.
Pump	1. Raise or lower by operating a device which raises, transfers, or compresses fluids by suction, pressure, or both. To move up and down, or in and out, as if with a pump handle.	1. Pump up the ramp several inches. 2. Pump engine primer knob.
Puncture	To pierce with pointed instrument or object.	Be careful not to puncture tube while probing the inside of it.
Purge	1. To free of sediment or trapped air by flushing or bleeding. 2. To remove fuel or fuel vapors from engine by motorizing engine with fuel switch off.	1. Purge fuel tanks. 2. Purge engines.
Push	1. To press against with force so as to cause motion away from the force. 2. To move away or ahead by steady pressure.	1. Push the blower start button. 2. Push the servicing cart toward the aircraft.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Put	1. To place in or through.	1. Put a wire through the hole in the turnbuckle.
	2. To place or set in a desired position or location.	2. Put the test equipment where it can be seen by both technicians.
	3. To deposit or leave.	3. Put tools out on the bench.
	4. To lay or spread on or in.	4. Put sealant in the gap between the windshield and the aircraft structure.
Raise	To move or cause to be moved from a lower to a higher position, to elevate.	Raise the spoiler control lever to the ARMED position.
Read	To interpret the meaning of by visual observation.	Read the ammeter.
Readjust	To adjust again, to move back to a specified condition; to bring back to an in-tolerance condition.	Readjust the voltage after performing an operational check of the system.
Ready	To prepare for a maintenance activity.	Ready the Trunnion Shaft Kit for removal of the MLG shock strut.
Reassemble	To refit and secure together the parts after they have been taken apart.	Reassemble component before installation on aircraft.
Recap	To cap again; to replace a covering; to reinstall a fitting for closing the end of a tube.	Recap the filler valve.
Recognize	To perceive to be something previously known or designated.	A jet engine mechanic recognizes troubles through evaluation of engine operational checks.
Recommend	To urge the acceptance or use of.	Recommend procedure changes where appropriate.
Recondition	To renew; to bring or put back into good condition.	Recondition the pilot's and copilot's seats.
Reconnect	To rejoin or refasten that which has been separated.	Reconnect aft pistons to forward pistons.
Record	To set down in writing.	Record maintenance time on appropriate form.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Reduce	To cause to be diminished in strength, density, or value.	Reduce pump flow.
Refuel	To put fuel into the tanks of (an aircraft) again.	Refuel the system as outlined in applicable technical manuals.
Regulate	To fix or adjust the time, amount, or rate of; to exercise restraining or directing influence over.	Regulate electrical current generation and distribution.
Reject	To refuse to have, use, or take for some purpose.	Reject components which show excessive wear.
Release	<ol style="list-style-type: none"> 1. To set free from an inactive or fixed position; to unfasten or detach interlocking parts. 2. To let go of. 3. To set free from restraint or confinement. 	<ol style="list-style-type: none"> 1. Release the parking brake. 2. Release tensiometer handle. 3. Release pressure.
Relieve	To ease or set free of a burden; to partially release.	Relieve hydraulic pressure before working on a system.
Remove	<ol style="list-style-type: none"> 1. To perform operations necessary to take an equipment unit out of the next larger assembly or system. 2. To take off or eliminate. 3. To take or move away. 4. To take off devices for closing off the end of a tube. 	<ol style="list-style-type: none"> 1. a. Remove bleed air shutoff valves. b. Remove bolts from nuts. 2. Remove paint. 3. Remove jacks. 4. Remove caps (plugs) from all hydraulic lines.
Repair	To restore damaged, wornout, or malfunctioning equipment to a serviceable, usable, or operable condition.	Repair engine by replacing parts and removing defects.
Repeat	To make, do, or perform again.	If keys do not engage lugs, remove wheel assembly and repeat procedure.
Replace	<ol style="list-style-type: none"> 1. To restore to a former place or position. 	<ol style="list-style-type: none"> 1. Replace covers on jacks.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
	2. To substitute serviceable equipment for malfunctioning, wornout, or damaged equipment.	2. Replace the switch contact points.
Report	1. To describe as being in a specified state. 2. To make known to; to give notice, or report the occurrence of.	1. Report when ready. 2. Report to man B that the brakes have been set.
Request	To ask for.	Request further information if necessary.
Reset	To put back into a desired position, adjustment, or condition.	Reset the field after performing an operational check of the generator.
Retract	To draw up against, or into, the aircraft.	Retract the landing gear.
Return	To bring, send, or put back to a former or proper place.	Return the horizontal stabilizer to the neutral position.
Review	To examine again; to go over, or examine critically or deliberately.	Review procedures which have not been performed for more than two months.
Rework	To reprocess for further use; to revise.	Rework the report forms.
Rig	To assemble, adjust, and align the major components of an aircraft (i.e., airfoils or other surfaces); to fit out (an aircraft) with control cables, bracing cables, pulleys, turnbuckles, etc.	Rig and adjust the mechanical linkage in the flight control system.
Rinse	To cleanse (as from soap used in washing) by clear water.	Rinse the battery after cleaning it with soda water solution.
Rotate	To cause to revolve about an axis or center.	Rotate the door handle counterclockwise until latches retract.
Route	To send by a selected course of travel; to divert in a specified direction.	Route the memo to all affected personnel.
Rub	To move along the surface of a body with pressure.	Rub hands around connections.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Safeguard	To provide a technical contrivance to prevent accident; to comply with precautionary measures or stipulation.	Safeguard technical manuals.
Safety	<p>1. To secure an aircraft part against loosening from vibration.</p> <p>2. To use safety wire to make an aircraft component fast, safe, or secure against loosening from vibration.</p> <p>3. To use a cotter pin to make an aircraft component fast, safe, or secure against loosening from vibration.</p>	<p>1. Safety the lock nut on the relief valve.</p> <p>2. Safety the bolts with wire.</p> <p>3. Safety the bolt with a cotter pin.</p>
Safety wire	To use safety wire to make an aircraft component fast, safe, or secure against loosening from vibration.	Safety wire the bolts.
Salvage	To rescue or save (as from discard, wreckage, or ruin).	Salvage fuel which is drained from tanks.
Scan	To make a wide, sweeping search of; to look through or over hastily.	Scan the flight engineer's panels before beginning maintenance activity.
Schedule	To appoint, assign, or designate for a fixed future time; to make a timetable of.	Schedule maintenance activities for the day.
Screw	<p>1. To attach, fasten, or close by means of a screw.</p> <p>2. To attach by means of a twisting motion in the proper direction.</p> <p>3. To attach screws by means of a twisting motion in the proper direction.</p>	<p>1. Screw the ram safety lock to the ram.</p> <p>2. Screw in jack pad.</p> <p>3. Screw in twelve screws around cover.</p>
Scrub	To clean with hard rubbing.	Scrub all metal parts with a white powder deposit on them.
Secure	1. To make fast or safe.	1. Load and secure components on trucks.

Verbs	Definitions	Examples
	2. To safe (with safety wire or cotter pin) to make aircraft component fast or safe or to keep it from loosening during vibration.	2. a. Secure bolts with safety wire. b. Secure the bolt with a cotter pin.
Select	To take by preference or fitness from a number or group; to pick out, to choose.	Select a battery cell and insert hydrometer nozzle in the cell.
Service	To perform such operations as clean-up, lubrication, and replenishment to prepare for use.	Service each battery cell to only $\frac{1}{8}$ inch above the plates.
Set	1. To put a switch, pointer, or knob into a given position; to put equipment into a given adjustment, condition a mode. 2. To put or place in a desired orientation or location.	1. Set PWR switch to ON. 2. Set the test equipment so that it can be seen by both technicians.
Set up	To prepare or make ready for a maintenance activity.	Set up the Trunnion Shaft Kit for removal of the MLG shock strut.
Shake	To move or cause to move to and fro in a quick, jerky manner.	Shake the container so that the paint will be well mixed.
Shut down	To perform operations necessary to cause an equipment to cease or suspend operation.	Shut down the air conditioning.
Signal	To notify or communicate by signals (i.e., a prearranged sign, notice, or symbol conveying a command, warning, direction, or other message).	Signal the pilot to move the aircraft to the left.
Simulate	To give the appearance or effect of.	Simulate doppler radar signals.
Slide	To cause to move in a smooth manner over a surface.	Slide the stand in close enough to do the work.
Specify	To name or state explicitly or in detail.	Specify the manufacturer's number of the multimeter.
Spill	To cause or allow to fall, flow, or run out.	Be careful not to spill battery acid on clothing, hands.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Spin	To cause to revolve.	Spin wheel by hand until a bearing drag is noticed.
Spray	To apply with a device which disperses a jet of finely divided liquid.	Spray the fuselage and tail sections moving from center to ends.
Start	To perform actions necessary to set into operation, to set going, to begin.	Start the powered AGE.
Stay	To remain, to continue in a place.	Stay away from the danger area.
Stop	To perform actions necessary to cause an equipment to cease or suspend operation.	Stop the air conditioning.
Store	To deposit or leave in a specified place for future use.	Store the wheel covers after maintenance activity is completed.
Stow	To deposit or leave in a specified place for future use.	Stow the wheel covers after maintenance activity is completed.
Strike	To deliver or aim a blow or thrust; to hit.	Strike the designated spot with a hammer.
Submit	To make available, to offer.	Submit request for modification of procedures.
Suggest	To propose as desirable or fitting; to offer for consideration.	Suggest any changes which might be helpful.
Supervise	To oversee; to have or exercise the charge of.	Supervise the repair of the engines.
Support	To hold up or provide a foundation or props for.	Support the elevator at both ends.
Synchronize	To cause to happen at the same time.	Synchronize the activities of man A and B.
Tag	To provide with an identifying or indicating symbol with, or as if with, a tag (i.e., a cardboard, plastic, or metal marker used for identification or classification); to label.	Tag each hydraulic line before removing it.
Take	1. To get into or carry in one's hands or one's possession.	1. Take supplies out to the aircraft.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
	2. To get or find out by observation or special procedures.	2. Take a reading on the outside circle of the tensiometer.
Tap	To strike lightly.	Tap the eye of the cotter pin to seat it.
Test	To perform specified operations to verify operational readiness of a component, subcomponent, system, or subsystem.	Test the true airspeed indicator.
Throw	To move (a switch) so as to make or break a connection.	Throw switch to ON position.
Tie	To fasten, attach, or close by means of a line or cord.	Tie mooring ropes to tie points under wing and on nose.
Tighten	1. To perform necessary operations to fix more firmly in place. 2. To apply a specified amount of force to produce a rotation or twisting motion to fix more firmly in place.	1. Tighten all screws. 2. Tighten the nut to a torque value of 1000 inch-pounds.
Tilt	To cause to slope, lean, or incline.	Tilt maintenance stand backwards until wheels contact the ground.
Torque	To apply a specified amount of force to produce a rotation or twisting motion to fix more firmly in place.	Torque the nut to 1000 inch-pounds.
Tow	To pull along (an aircraft) by means of a towing vehicle and tow bar.	Tow aircraft to the washrack.
Trace	To follow or study out in detail or step by step.	Visually trace the wiring diagram.
Transfer	To convey or cause to pass from one place to another.	Transfer fuel and oil from one place to another.
Transmit	1. To convey or cause to pass from one place to another. 2. To send out a signal by radio waves or wire.	1. Transmit fuel and oil from one place to another. 2. Transmit message to control tower.

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Transport	<p>1. To convey or cause to pass from one place to another.</p> <p>2. To carry by hand or in a vehicle or hoist, or in a container, etc.</p>	<p>1. Transport fuel and oil from one tank to another.</p> <p>2. Transport landing gear to shop on dolly.</p>
Trim	<p>1. To free of excess or extraneous matter by, or as if by, cutting.</p> <p>2. To adjust (a jet engine) to compensate for wear.</p>	<p>1. Trim patch to fit.</p> <p>2. Trim the no. 1 engine.</p>
Troubleshoot	To localize, isolate, and correct the source of a malfunction or breakdown.	Troubleshoot the landing gear control circuit.
Tune	To adjust for precise functioning.	Tune the transmitter maximum output.
Turn	To cause to revolve about an axis or center.	Turn the door handle counterclockwise until latches retract.
Turn off	To shut off or stop the flow of by, or as if by, moving a control to its OFF position.	Turn off power to the signal generator.
Turn on	To cause to flow or operate by, or as if by, moving a control to its ON position.	Turn on power to the signal generator.
Uncap	To remove a device for closing off the end of a tube with a male fitting.	Uncap and unplug all hydraulic lines.
Unlock	To set free from an inactive or fixed position, to unfasten, to detach interlocking parts.	Unlock the parking brake.
Unplug	<p>1. To detach or separate (an electrical device) from a service outlet.</p> <p>2. To remove a device for closing off the end of a tube with female fittings.</p>	<p>1. Unplug the soldering iron.</p> <p>2. Unplug and uncap all hydraulic lines.</p>
Unscrew	<p>1. To loosen or withdraw by turning in the proper direction.</p> <p>2. To draw the screws from.</p>	<p>1. Unscrew the jack pad.</p> <p>2. Unscrew 12 screws around cover.</p>

<i>Verbs</i>	<i>Definitions</i>	<i>Examples</i>
Unwind	To cause to uncoil or unroll.	Unwind hoses from hose rack.
Use	To put into action or service; to avail oneself of; to carry out a purpose or action by means of.	Use only antimagnetic fasteners.
Verify	1. To confirm or establish that a proper condition exists. 2. To establish the truth or accuracy of.	1. Verify that the light is off. 2. Verify the readings before recording them.
Wait	To suspend activity in a sequence of activities until a given condition occurs or a given time has elapsed.	Wait 5 minutes before performing the next task.
Wash	To cleanse by, or as if by, the action of liquid; to remove (dirt) by rubbing or drenching with liquid.	Wash the battery with a cleaning solution and a stiff brush.
Watch	To visually take note of, to pay attention to in order to check on action or change.	Watch the indicator for changes in airspeed.
Wire	To provide with wire, to use wire on.	Wire the circuit.
Withdraw	To take back, away, or out.	Withdraw the bar magnet from the center of the coil.
Wrap	To wind, coil or twine so as to encircle or cover something.	Wrap the wire around the terminal.
Zero	To bring to a desired level or null position.	Zero the protractor to the surface.